# Xerox<sup>®</sup> AltaLink<sup>®</sup> Multifunction Printers

**Xerox**<sup>™</sup>

B8145/B8155/B8170



AltaLink® B8100 Series Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to **www.ConnectKey.com**.

System Specification	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170		
Speed <sup>1</sup>	Up to 45 ppm	Up to 55 ppm	Up to 72 ppm		
Monthly Duty Cycle <sup>2</sup>	Up to 200,000 pages	Up to 250,000 pages	Up to 300,000 pages		
Hard Drive/ Processor/Memory	Minimum 128 GB SSD/ <b>Optional</b> : 500 GB HDD/Intel® Atom™ Quad Core 1.91 GHz/4 GB system memory				
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.0 direct print, NFC; <b>Optional:</b> WiFi/WiFi Direct with Xerox Dual Band Wireless Kit, Bluetooth (iBeacon)				
Controller Features	Configuration Cloning, Configuration Watchdog, Flee	et Orchestrator, Remote Control Panel, Unified Address	s Book		
Copy and Print					
Copy and Print Resolution	<b>Copy:</b> Up to 600 x 600 dpi; <b>Print:</b> Up to 1200 x 240	0 dpi			
First-Print-Out Time (as fast as)	3.8 seconds	3.2 seconds	3.0 seconds		
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	4.4 seconds	3.7 seconds	3.2 seconds		
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6				
Print Features	Application Defaults, Bi-directional Real-time Status, Booklet Layout, Encrypted Secure Print, Hold All Jobs, Imaging Security with AltaLink's proprietary marking and infrared detection technology, Job Identification, Job Monitoring, Long Sheet (Banner) Printing, Print Around, Print from Cloud Repositories (Dropbox, OneDrive, and Google Drive), Print from USB, Print on Alternate Paper, Scaling, Store and Recall Driver Settings, Two-sided Printing (as default), Xerox® Earth Smart Driver Settings; <b>Optional:</b> Print from and Scan to Xerox® DocuShare® Go content management				
Mobile- and Cloud-Ready	ty				
Mobile Connectivity	Near Field Communication (NFC); <b>Optional:</b> Wi-Fi Direct, Wi-Fi (802.11 b/g/n/ac), AirPrint (iOS) including iBeacon (Bluetooth)				
Mobile Printing	Mopria® Print, Apple AirPrint™, Xerox® Print Service (Android), @PrintByXerox App; <b>Optional:</b> Xerox® Workplace Mobile App (iOS/Android)				
Mobile Scanning	Mopria® Scan, Apple AirPrint™, <b>Optional:</b> Xerox® Wo	Mopria® Scan, Apple AirPrint™, <b>Optional:</b> Xerox® Workplace Mobile App (iOS/Android)			
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate.  Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® (xerox.com/ecm),  XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions).				
Xerox® Workplace Central Platform	One-platform consistency for seamless productivity across computers, mobile devices and printers. With Workflow Central's ever-expanding suite of cloud-based workflows, you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable and shareable text, translate to/from over 40 different languages, and automatically redact Personal Identifiable Information using set words or phrases.				
Xerox® Workplace Suite and Xerox® Workplace Cloud	<b>Optional:</b> Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their printer fleet while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud-based version (Workplace Cloud) of this solution.				
Cloud Identity Provider (IdP) Integration	Use your desktop, laptop, or mobile login credential: Ping Identity, and Microsoft® Azure.	s to log in to your AltaLink® MFPs with direct connection	ons to popular cloud identity providers, Okta,		

Scan		
Standard Features	Destinations: Scan to USB/PC via USB port/Email/Network (FTP/SMB), HTTP, HTTPS, SFTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF; Convenience Features: 1-Touch Apps, Imaging Security with AltaLink's proprietary marking and infrared detection technology, Optical Character Recognition (OCR), Password-protected PDF, Scan Preview, Scan to Folder, Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Touchless Workflow Accelerators, TWAIN Support, Unified Address Book	
Optional Features	Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive). Xerox® Scanning App for DocuShare®, other solutions available through various Xerox® Business Innovation Partners at xerox.com/Software-Solutions, Print from and Scan to Xerox® DocuShare® Go content management	
Fax		
Standard Features	Network Server Fax Enablement, Fax Build Job	
Optional Features	Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email or SMB Share)	
Security		
Standard Features	802.1x, Access Control, Audit Log, Automated threat response through Trellix DXL*/Cisco® pxGrid integration, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, Common Criteria Certification (ISO 15408) full system against HCP PP, Configuration Watchdog, Encrypted Secure Print, Encrypted Storage Drive (AES 256-bit, FIPS 140-3), FIPS 140-3, Firmware Verification, HTTPS, Imaging Security (copy, print, scan, email) with AltaLink's proprietary infrared detection technology, IPsec, Job Level Encryption via HTTPS and Drivers, Local Authentication (Internal Database), Trellix Embedded Control Whitelisting*, Trellix ePolicy Orchestrator®*, Network Authentication, Port/IP/Domain Filtering, Security Certificates utilizing ECDSA, Security Dashboard, SFTP and Encrypted Email, SHA-256 Hash Message Authentication, SIEM integration (Splunk, LogRhythm, Trellix ESM*), Signed Email, SNMPv3, TLS 1.1/1.2/1.3, TPM, Trusted Boot, User Access and Internal Firewall, User Permissions	
Optional Features	Trellix Integrity Control*, Smart Card Enablement Kit (CAC/PIV/.NET)³, Xerox® Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-3) with multi-pass Image Overwrite®, Xerox® Workplace Cloud/Suite Print Management and Content Security; WPA2 and WPA3 with Dual Band Wireless Kit; learn more at xerox.com/WorkplaceSolutions	
Print Management		
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement	
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Services; learn more at xerox.com/PrintManagement	

#### Features and Accessories

### Single-Pass Duplex Automatic Document Feeder (DADF)

saves time by simultaneously scanning both sides of a document with up to 270 impressions per minute (ipm).



#### **USER INTERFACE**



Intuitive Tablet-like 10.1-inch
Color Touchscreen is customizable
and lets you perform tasks in just a
few taps. Try it out at
xerox.com/AltaLink8100UI.

#### INNOVATIVE TECHNOLOGIES



Xerox® Integrated RFID Card Reader (optional) adds card-based authentication with support for over 90 access cards.



Near Field Communication (NFC)
Tap-to-Pair allows users to tap their
mobile devices to the AltaLink® B8100
Series user panel and quickly connect

with the MFP.




Smart Proximity Sensor detects when users are nearby. It conserves energy during inactive periods and automatically activates the device when a user approaches.

## PAPER INPUT<sup>4</sup> Two 520 shoot Adjust

**Two 520-sheet Adjustable Trays** (common with all configurations). Tray 1 handles media sizes up to 11.7 x 17 in./A3 and Tray 2 handles media sizes up to 12 x 18 in./SRA3.



**Envelope Kit** (optional — replaces Tray 1) provides feeding of up to 60 envelopes.



High Capacity Tandem Tray Configuration holds a total paper capacity of up to 3,140 sheets.

**Bypass Tray** handles up to 100 sheets; Custom sizes: 3.5 x 3.9 in. to 12.6 x 52 in./89 x 98 mm to 320 x 1,320 mm.

**High Capacity Feeder** (optional) holds
3,000 sheets of letter/A4
paper, increasing the

to 6,140 sheets.

maximum paper capacity



#### Office Finisher

(optional) provides advanced finishing functions, optional crease/score, and saddle-stitch booklet, capable of 60-page booklets (2 to 15 sheets).



**Business Ready** 

(BR) Finisher (optional)

gives you advanced

finishing functions

at a great value.

#### C-Fold/Z-Fold Unit

(optional) adds C-fold, Z-fold, and Z-half-fold capability to the BR Finisher or BR Booklet Maker Finisher.



#### BR Booklet Maker

Finisher (optional) creates 64-page saddle-stitched booklets (2 to 16 sheets).



**Long Sheet Feed Kit** (optional) provides the ability to print up to 12.6 x 52 in./ 320 x 1,320 mm media.





**Dual Offset Catch Tray**(available when no finisher

(available when no finishers are installed; Single Offset Catch Tray with finishers).



Integrated Office Finisher

(optional with B8145/B8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.



Convenience Stapler

(optional) staples up to 50 sheets of 20 lb./75 gsm media.

Device Specification	
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic
Accessories	
Optional	SOOGB HDD Bluetooth Kit Booklet Maker for Office Finisher BR (Business Ready) Finisher (requires Horizontal Transport Kit) BR Booklet Maker Finisher (requires Horizontal Transport Kit) BR Booklet Maker Finisher (requires Horizontal Transport Kit) C-fold/Z-fold Unit for BR Finisher or BR Booklet Maker Finisher Convenience Stapler (includes Work SurfaceS) Envelope Tray (Replaces Tray 1) Foreign Device Interface (Also known as Auxiliary Access Device Interface) for third-party access control devices, such as coin machines and card readers High Capacity Feeder 3000 Ad/Letter Hole Punch (2/3, 2/4, Swedish) Horizontal Transport Kit Integrated Office Finisher (Available with AltaLink® B8145, B8155) Long Sheet Feed Kit (banner printing) Trellix Integrity Control Enablement Kit* Multi-feed Detection Kit (AltaLink® B8170 only) Office Finisher Scan To Cloud Enablement Kit Smart Card Enablement Kit USB Keyboard/Shelf Kit Walk-up Fax (One- or Two-line options, includes LAN Fax) Wii-Fi/Wi-Fi Direct with Dual Band Wireless Kit Xerox® Integrated RFID Card Reader Kit
Electrical Requirements	AltaLink® B8145 AltaLink® B8155 AltaLink® B8170
North America	Voltage: 110-127 VAC +/- 10%       Voltage: 110-127 VAC +/- 10%         Frequency: 50/60 Hz +/- 3%, 15 A       Frequency: 50/60 Hz +/- 3%, 20 A
Europe	Voltage: 220-240 VAC +/- 10%       Voltage: 220-240 VAC +/- 10%         Frequency: 50/60 Hz +/- 3%, 10 A       Frequency: 50/60 Hz +/- 3%, 10 A

Device Specification (continued)				
Power Consumption	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
Running (Average)	115V: 717 watts 230V: 674 watts	115V: 806 watts 230V: 760 watts	115V: 929 watts 230V: 908 watts	
Standby Mode	115V: 71 watts 230V: 71 watts	115V: 72 watts 230V: 70.3 watts	115V: 91.1 watts 230V: 79 watts	
Auto Off/Sleep Mode	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.68 watts 230V: 0.75 watts (Default time to sleep mode = 0 minutes)	
Warm-up (from Off)	As fast as 85 seconds			
Recovery from Sleep	As fast as 4.5 seconds			
Operating Environment				
Required Temperature Range	50 to 82° F/10 to 28° C			
Required Relative Humidity	15% to 85%			
Sound Power Levels	Operating: 63.7/64.2 dB(A) Standby: 40.0/40.0 dB(A)	Operating: 65.2/67.3 dB(A) Standby: 43.0/43.0 dB(A)	Operating: 70.4 dB(A) Standby: 43.0 dB(A)	
Dimensions and Weight				
Base Configuration	Width: 24.4 in./620 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 286 lb./129.5 kg		Width: 24.4 in./620 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 319.2 lb./144.8 kg	
With Office Finisher (with Booklet Mαker)	Width: 47.5 in./1,207 mm  Depth: 28.5 in./723 mm  Height: 44.5 in./1,130 mm  Weight: 370.3 lb./168 kg		Width: 47.5 in./1207 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 406 lb./184.2 kg	
Base Configuration with Business Ready (BR) Finisher	Width: 55 in./1,395 mm       Width: 55 in./1,395 mm         Depth: 28.5 in./723 mm       Depth: 31.2 in./723 mm         Height: 44.5 in./1,130 mm       Height: 46 in./1,169 mm         Weight: 382.3 lb./173.4 kg       Weight: 415.4 lb./188.4 kg		Depth: 31.2 in./723 mm Height: 46 in./1,169 mm	
Base Configuration with BR Booklet Maker Finisher	Width: 59 in./1,496.3 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 419.7 lb./190.4 kg		Width: 59 in./1,496.3 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 453.3 lb./205.6 kg	
Base Configuration with BR Booklet Maker Finisher and C-fold/Z-fold Unit	Width: 64.3 in./1,632 mm       Width: 64.3 in./1,632 mm         Depth: 28.5 in./723 mm       Depth: 31.2 in./723 mm         Height: 44.5 in./1,130 mm       Height: 46 in./1,169 mm         Weight: 530.6 lb./240.7 kg       Weight: 564.2 lb./255.9 kg		Depth: 31.2 in./723 mm Height: 46 in./1,169 mm	
Base Configuration with BR Booklet Maker Finisher, C-fold/Z-fold Unit, and High Capacity Feeder	Width: 93 in./2,361 mm       Width: 93 in./2,361 mm         Depth: 28.5 in./723 mm       Depth: 31.2 in./723 mm         Height: 44.5 in./1,130 mm       Height: 46 in./1,169 mm         Weight: 598.8 lb./271.6 kg       Weight: 632.8 lb./287 kg		Depth: 31.2 in./723 mm Height: 46 in./1,169 mm	
System Certifications/Regulo	atory Compliances			
Certifications	To view the latest list of certifications, go to <b>xerox</b> .	com/OfficeCertifications		

Paper Handling	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Single-Pass Duplex Automat	ic Document Feeder (DADF)		
Capacity <sup>4</sup>	130 sheets		250 sheets
Speed (Up to)	82 ppm black-and-white (simplex) 141 ipm black-and-white (duplex)		135 ppm black-and-white (simplex) 270 ipm black-and-white (duplex)
Paper Sizes Sensed	3.4 x 4.9 in. to 11.7 x 17 in./85 x 125 mm to 297 x 4:	32 mm	
Weights	16 lb. to 32 lb. bond/60 to 128 gsm		
Bypass Tray (Standard)			
Capacity <sup>4</sup>	100 sheets		
Sizes	<b>Custom Sizes:</b> 3.5 x 3.9 in. to 12.6 x 52 in./89 x 98 n	nm to 320 x 1320 mm (SEF); <b>Optional:</b> Long Sheet F	eed Kit (Banner Printing)
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm, <b>Long sh</b>	eets/banners (>19 in./483 mm): 28lb Bond - 120lb I	ndex/106 - 220 gsm
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Reloaded Lightweight Glossy Card Stock Reloaded Lightweight Glossy Card Stock Reloaded Preprinted Recycled Transparencies  Long Sheets/Banners: Card Stock Card Stock Card Stock Reloaded Lightweight Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Card Stock		
Trays 1 and 2 (Standard)	3 3		
Capacity <sup>4</sup>	520 sheets each		
Sizes	<b>Tray 1:</b> Custom Sizes: 5.5 x 7.2 in. to 11.7 x 17 in./14 <b>Tray 2:</b> Custom Sizes: 5.5 x 7.2 in. to 12 x 18 in./140		
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Mediα Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Labels Letterhead Lightweight Lightweight Card Stock Lightweight Glossy Card Stock Ligh		

Paper Handling (continued)	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170		
High Capacity Tandem Tray	High Capacity Tandem Tray (Available with all models)				
Capacity <sup>4</sup>	<b>Tray 3:</b> 867 sheets <b>Tray 4:</b> 1,133 sheets				
Sizes	8.5 x 11 in./A4, JIS B5, Executive (7.25 x 10.5 in) LEF				
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm				
Media Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted				
Envelope Tray (Optional - Re	places Tray 1)				
Capacity <sup>4</sup>	Up to 60 envelopes				
Sizes	#10 Commercial (9.25 x 4.125 in.)/Monarch, DL, C5 Custom Sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./98 x 148 m	nm to 162 x 241 mm			
Weights	20 lb. to 24 lb. bond/75 to 90 gsm				
High Capacity Feeder (HCF)	(Optional with all models)				
Capacity <sup>4</sup>	3,000 sheets				
Sizes	Standard Sizes: 8.5 x 11 in. or 7.25 x 10.5 in./A4 or B5 LEF				
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm				
Total Capacity	Total Capacity				
Device Total Capacity <sup>4</sup>	High Capacity Tandem Tray Module: 3,140 sheets High Capacity Tandem Tray Module with High Capa	city Feeder: 6,140 sheets			

Finishing	AltaLink® B8145	taLink® B8155	AltaLink® B8170
Output Trays (Standard) (Du	। ual Offset Catch Trays not available with Integrated C	Office Finisher and limited to one with Office	Finisher and BR Finishers)
Stacking Tray Capacity <sup>4</sup>	Dual Offset Catch Tray: Up to 250 sheets each Left Side Face-up Tray: Up to 100 sheets		
Integrated Office Finisher (C	Optional with AltaLink® B8145/B8155)		
Stacking Tray Capacity <sup>4</sup>	500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4 or 25	50 sheets of 20 lb. bond/80 gsm – 11 x 17 in./A3	
Sizes	3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 432 m	m	
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Stapling	Single/Dual Position Auto-Stapling: 50 sheets maximum: Letter/A4/B5 size sheets (less than 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (le		
Office Finisher (Optional)			
Stacking Tray Capacity <sup>4</sup>	2,000 sheets unstapled or 1,000 sheets single stapled or	750 sheets dual stapled (8.5 x 11 in./A4)	
Stacking Tray Sizes	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432	? mm	
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Multiposition Stapling	50 sheets maximum: Letter/A4/B5 size sheets (less than 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (le		
Hole Punch (Optional)	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch		
Booklet Maker for Office Fin	isher (Score/Crease, Saddle-stitch Staple) (Optional)		
Top Tray Capacity <sup>4</sup>	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or	less)	
Sizes	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Tabloid – 11 x 17 in./A3 SEF		
Saddle-Stitch Stapling	2-15 sheets/8-60 page booklet 16 lb. bond to 80 lb. cover/64 to 220 gsm		
Score/Crease	1-15 sheets/unstapled 16 lb. bond to 28 lb. bond/64 to 105 gsm		
Business Ready (BR) Finishe	r (Optional) (Requires Horizontal Transport Kit)		
Capacity <sup>4</sup>	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 1-	4 in./A3 or 200 sets (single-position staple) 8.5 x	11 in./A4
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 4 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling	1 2	
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4, and B5 sizes supported		
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch		
BR Booklet Maker Finisher (	Optional) (Requires Horizontal Transport Kit)		
Capacity <sup>4</sup>	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstage Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled 200 stapled sets of 8.5 x 11 in./A4 (single-position staplidual or 4-position stapling) or 100 stapled sets of 11 x 1	l or ing or	
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 4 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling		
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4, and B5 sizes supported		
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch		
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsn Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported	n coated or 5 sheets at 177 to 220 gsm coated)	

Finishing (continued)	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
C-fold/Z-fold Unit (Optional	with BR Finisher and BR Booklet Maker Finisher)			
Types	C-fold, Z-fold, and Z-half-fold			
Capacity <sup>4</sup>	40 sheets			
Sizes	C-fold and Z-fold: Letter – 8.5 x 11 in./A4 SEF only Z-half-fold: Tabloid – 11 x 17 in./A3 only			
Weights	16 lb. to 24 lb. bond/64 to 90 gsm			
Output Trays	Envelope Tray: C-fold, Z-fold, and Tri-fold Stacker Tray or Top Tray: Z-half-fold			
Convenience Stapler (Option	nal - Includes Work Surface <sup>5</sup> )			
Capacity <sup>4</sup>	50-sheet stapling 5,000 staples Requires separate power outlet			
Сору	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
First-Copy-Out Time (from platen/warmed up)	As fast as 4.4 seconds	As fast as 3.7 seconds	As fast as 3.2 seconds	
Sides (input:output)	1-1, 1-2, 2-2, 2-1	1-1, 1-2, 2-2, 2-1		
Quantity	1 to 9,999			
Resolution (max)	Up to 600 x 600 dpi			
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% incremen	ts		
Concurrency	Program-ahead to allow the job to be queued while	the initial job is processed (Copy, Print, Fax, and Scan	)	
Copy Features	Annotation and Bates™ stamping Authentication for Services Auto Paper Select Auto Reduction & Enlargement (To fit selected pape Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (Enables page-level programming and also Collation Covers (Front only, front and back, back only, printed Dividers (blank) Edge Erase Features Help (Intuitive text and graphic description ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Imaging Security Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling Touchless Workflow Accelerators Transparencies	o lets you proof each section or delete the last section I inside and out: Blank or Printed)	as the job is built)	

Print	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170		
Resolution (up to)	1200 x 2400 dpi				
Print Features	Finishing Fit to New Paper Size Hold All Jobs Image Options (Toner Saver, Resoluti Job Identification (Print ID or Banner LAN Fax (requires optional Fax Kit) Long Sheet/Banner Layout/Watermark N-up (up to 16 pages per sheet) Paper Selection by Attribute Sample Print From Cloud Repositories (Dropt Saved Job Secure Print with Timed Deletion Special Pages (exception page progra	ther Sheet Enable/Disable thet Layout or Selection or Print (specific time) User Permissions on hing on New Paper Size All Jobs oge Options (Toner Saver, Resolution (Standard, Enhanced, High)) dentification (Print ID or Banner, Print ID in margins on the first page only or all pages) Fax (requires optional Fax Kit) Sheet/Banner ut/Watermark or 16 pages per sheet) or Selection by Attribute Sample Set From Cloud Repositories (Dropbox, OneDrive, and Google Drive) d Job or Print with Timed Deletion ial Pages (exception page programming: covers, inserts, exception pages) e and Recall Driver Settings ainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)			
Print from USB	Allows walk-up printing from Type A I Supports direct printing from a comp Supported file formats: PDF, JPEG, TI Color jobs can be printed as black-an	outer via Type B USB port FF, PS, PCL			
Operating Systems	Windows 10 (32 and 64 bit) Windows 11 (32 and 64 bit) MacOS 10.13.x, 10.14.x, 10.15.x, 11.8 Red Hat Linux 6.x, 7.x, 8.x Ubuntu Linux 20.04.x, 22.04.x SuSe Linux Server 12.3-13.x, 15.x  MS Windows 2012 Server (32 and 64 MS Windows 2016 Server (32 and 64 MS Windows 2019 Server (32 and 64 MS Windows 2022 Server (32 and 64 RS Windows 2022 Server (32 and 64 Red Hat Linux Server 7.x, 8.x SuSe Linux Server 12.2-12.4, 15.x	4 bit) 4 bit) 4 bit)			
Network Protocols	· ·		00, IPv4/IPv6, WSD		
Font Capability	PCL: 93 scalable fonts, line printer, ar	nd bitmap font (including Cyrillic font support) Pos	tScript 3: 173 Type 1 fonts, 2 Multiple Master fonts		
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade, and manage non-Xerox and Xerox® Devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management. Support for Microsoft Universal Print.				
Xerox® Pull Print Driver	driver. The Xerox® Pull Print Driver ext		single driver in a Pull Print environment. Uses a single queue and single ig assets. IT administrators no longer need to manage and configure d others.		
Unified Address Book for Fax	ified Address Book for Fax, Email, and Scan to				
Features	Services supported: Fax, Email, Scant Maximum contacts: 5,000 Contacts: Supports 1 or more destinc Favorites for quick access of all servic	ations			

Scan	AltaLink® B8145	AltaLink® B8155	A	ltaLink® B8170
Concurrency	Scan while the system is printing, c concurrent jobs)	copying, or while it is transferring scan to network or	fax jobs (priority is for	return of scanned originals and printing
Input Speed (up to)	82 ppm black-and-white and color (simplex) 141 ipm black-and-white and color (duplex) 135 ppm black-and-white and color (simplex) 270 ipm black-and-white and color (duplex)			
Resolution	150 x 150 dpi to 600 x 600 dpi			
Bit Depth	1-bit (black-and-white), 8-bit (gray	rscale), 24-bit (color)		
Maximum Scan Area	11 x 17 in./A3			
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS sca	n templates and share via device cloning to other m	nultifunction printers' c	onfirmation sheet options
Network Protocols	SFTP, FTP, SMB, HTTP, HTTPS			
File Compression		JPEG, LZW) MMR compression – single or multiple pages) b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, Jl	BIG Arithmetic Compre	ession, Deflate (for black-and-white and within
Document Management Fields (Metadata)		data fields per network scan to file templates and ur I name, default value, and other configurations	nlimited fields within th	e template –
Scan Features	Auto Background and Shadow Sup Bound Originals Compression Quality/File Size Con Edge Erase Imaging Security Mixed Size Originals Original Type (Photo and Text, Pho Reduction/Enlargement Scan Build Job Scan Preview Single Touch Scan buttons (up to 1 Size for Size (for mixed size original Touchless Workflow Accelerators TWAIN Support/WIA 2.0 Support	trol oto, Text, Map, Newspaper/Magazine) 10)		
Scan to Email (Standard)				
Scan Features	Auto send to self     Email signatures (6 lines each of     Email signing (requires Smart Ca     Scan to Email S/MIME Encryptio     Touchless Workflow Accelerators	n	nfigurable), email Embe	edded Web Server confirmation sheet options
Directory Access	Address list via LDAP (Windows Ac	tive Directory, Exchange, Notes, Domino), Device Ad	ddress Book	
Scan To				
Standard Features	Scan to Email Scan to Home Scan to Mailbox Scan to Network (using Secure FTF Scan to Network Folder (using Secure FTF Scan to PC/Server Client (SMB or F Scan to PC via USB port Scan to USB	ure FTP/HTTP/HTTPS)		
Optional Features	Scan to Cloud Repositories (Dropb	ox, OneDrive, and Google Drive)		
Workflow Scanning (Option	al)			
Scanning Software	Autostore v7 eCopy ShareScan v5.2 eCopy ScanStation v5.2			
Scanning Apps and Xerox App Gallery		icrosoft OneDrive, Microsoft Office 365™, Box®, Xero n the Xerox App Gallery: <b>xerox.com/AppGallery</b>	ox® Workplace Mobile A	App (iOS/Android)

Security	AltaLink® B8145	AltαLink® B8155	AltaLink® B8170
Features	Audit Log		
-	Audit Log     Cisco® Identity Services Engine (ISE) compatible     Configuration Watchdog (Monitor and remediate     802.1x     Admin Password Reset     Audit Log     Automatic Software Upgrade     Email Alerts     FIPS 140-3     Hold All Jobs     Immediate Job Overwrite®     Installation Policies     Trellix Embedded Control®     PII - Login Name     PostScript Passwords     Remote Services Enablement     Remote Start (Mopria® or AirPrint™)     Reprint Saved Jobs     Scan to Mailbox (Internal storage)     Scheduled Disk Overwrite®     Secure Passcode Length     Secure Print Device Policies     SIEM     SNMP     System Timeout     USB (Print from USB)     USB Port Management     User Data Encryption     Expanded Authentication     Digitally signed PDF (when using Smart Card au     Encrypted and authentication to SMTP server fe     Encrypted/Password-protected PDF (when using     FIPS 140-3, 256 bit Hard Disk Encryption, TLS, II     Immediate Image Overwrite/Securely delete jol     Local Authentication (internal database)	thentication) or Scan to Email g Email and Network Scan Templates only) PPS, HTTPS, SFTP, SNMPv3 ps using approved algorithms9 device services via Kerberos (UNIX/Windows Servental) includes sanitation of unused area of disk9 elentication)	
	Smart Card authentication – 144k CAC/PIV Card     Expanded Authorization		
	Trellix Embedded Control* (whitelisting), Trellix Ini Port disablement including USB ports Security Dashboard Security Information and Event Management (SII) WPA2 and WPA3 are supported by the Dual Band	tegrity Control* (optional) EM) support for Trellix Enterprise Security Manager	*, LogRhythm, and Splunk
Xerox® Integrated RFID Card Reader (Optional kit)	Integrated support for most industry security cards the multifunction printer panel	providing additional security; with embedded mult	tifunction printer card readers in

Fax	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
Network Server Fax Features		<u> </u>		
Compatibility	ITU (CCITT) group 3; Various Xerox® Business Innovation Partner Solutions			
Maximum Scan Area	11 x 17 in./A3			
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in./A3) Add to Send List (200 numbers maximum) Build Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text)			
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print			
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi			
Walk-up Fax Features (Option	nal; Customer-Installable – 1 and 2 lines)			
Compatibility	ITU (CCITT) Group 3			
Speed/Modems	One or Two V.34 modems: 33,600 bps. Less than 4 s	econds per page transmission time		
Compression/Speed	MH/G3, MR/G3, MMR/SG3, JBIG/SG3			
Resolution	Walk-up Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes			
Fax Send Features	Auto Fax Transmission Reduction Automatic Cover Sheets Automatic Memory Resend Batch Send (up to memory capacity) Delay Start, Build Job, Favorites Device Address Book (up to 5,000 contacts) LAN Fax (fax from print driver) Page-by-page Job Status at the Machine PSTN Fax			
Fax Receive Features	Auto Answer Delay One- or Two-sided Printing Output Tray Selection Receive Print Mode – Manual (size, margin, stock, he Receive Timestamp Secure Receive Stapled or Unstapled Up to 200 Password Protected Mailboxes	ader)/Auto		
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only			
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On-demand Overwrite <sup>9</sup> Report, Mailbox Report, Broadcast Report			
Directory Access	Utilizes the Unified Address Book Group fax available			
Auto Redial	Up to 14 attempts (per country requirements) 1 to 25-minute intervals			
Auto Resend	Up to 5 attempts			

Device Management	
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP
	MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System- Power MIB, Fleet Orchestrator, Configuration Watchdog, Xerox® Easy Assist App
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX, or any other operating system:
	Works with any SNMP-managed printer from any manufacturer
	<ul> <li>Remote configuration of SNMP v3</li> <li>Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and</li> </ul>
	asset management • Requires Windows 7 and Internet Explorer 6.0 and higher
	Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote installation
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:  • Device monitoring and troubleshooting  • Remote configuration of SNMP v3  • Extensive reporting and discovery of new devices
	Usage collection, chargeback, and billing capabilities
Xerox® Workplace Cloud	Auto-detect Xerox® Device Manager server and download configurations files for touchless remote installation  Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection.
	The following data can be shared: Software update files, clone files, and 1-Touch App files. Auto-assembly feature allows a new AltaLink® to automatically set itself on the network and configure.
Novell NDPS/NEPS	Server gateway application: centralized management tool
Xerox® Device Types	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP
for SAP R/3 Intelligent Barcode Utility (optional)	environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. For more information, visit office.xerox.com/Software-Solutions
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download.  office.xerox.com/Software-Solutions
Xerox® Embedded Web Server – Integrated Device Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller:  Tray status/contents Consumables status Alerts
Job Submission	Remote Control Panel  Print ready flor: DS_DCL_TIEF_DDE_IDG_TXT_DDN
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard
Browsers	Microsoft Edge version 88+ Microsoft Chromium Edge version 79+ Mozilla Firefox 91.9.0, 100.0 Safari 13.1.2, 14.1.2, 15.4 Opera 2020, 2021 Google Chrome version 80.0.x+
Support	Install print/scan drivers and online support available via support.xerox.com
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic
Remote Services	
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox <sup>®</sup> Automαtic Supplies Replenishment (ASR)	Automatically orders supplies for output devices from Xerox based on actual usage, eliminating the need to manually manage supplies inventory.
Accounting	
Xerox® Standard Accounting	
Tracking	Copy, Print, Fax, Scan, and Email usage
Accounting	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools.</li> <li>Administrator can import or export User Accounts, Group Accounts, General Accounts, and User Limits via an industry-standard CSV file.</li> </ul>

#### Accounting Options – Network Accounting (Allows central server to manage all accounting) • Enhanced network accounting with up-to-the-minute data on how the system is being used • Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan, and server fax • Numerous solutions are available through Xerox Alliance Partners. For details, visit www.xerox.com • Security enhancements with the addition of HTTPS protocol support • Device requests account authentication from third-party server enabling larger databases of users and accounts • Accept Authentication Login at the control panel and pass to third-party Networking Account • Interface with third-party accounting terminal for accounting user interface **Supplies** Description Yield Toner Cartridge<sup>6</sup> Black 52,000 pages Transfer Belt Cleaner 1 Assembly 160,000 pages Second Bias Transfer Roll 200,000 pages 1 Assembly Staple Cartridges For BR Finisher, Integrated Office Finisher, Office Finisher, and Convenience Stapler (1 cartridge per carton) 5,000 each cartridge For BR Booklet Maker (1 cartridge per carton) 5,000 each cartridge For Office Finisher Booklet Maker (8 cartridges per carton) 2,000 each cartridge For Integrated Office Finisher, Office Finisher, BR Finisher, and Convenience Stapler (3 refills per carton) Staple Refills 5,000 each refill Xerox® Smart Kit® Drum Cartridge7 1 Cartridge 200,000 pages **Waste Toner Container** 1 Cartridge (AltaLink® B8145/8155) 121,000 pages w/o Suction Filter Waste Toner Container 1 Cartridge (AltaLink® B8170) 121,000 pages with Suction Filter9

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. For more information, visit <a href="https://www.xerox.com/About-Xerox/Recycling">www.xerox.com/About-Xerox/Recycling</a>.

For more information, visit us at www.xerox.com/Office



<sup>1</sup> Declared in accordance with ISO/IEC 24734.

 $<sup>^{2}</sup>$  Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis

<sup>&</sup>lt;sup>3</sup> Not available in all geographies.

<sup>&</sup>lt;sup>4</sup> Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

<sup>&</sup>lt;sup>5</sup> Sold separately in some geographies.

<sup>&</sup>lt;sup>6</sup> Average standard pages. Declared in accordance with ISO/IEC 19752. Toner yield can vary due to many factors, including but not limited to image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes, and image quality set-points.

<sup>&</sup>lt;sup>7</sup> Average drum yield is based on a run length of 5 pages of 8.5 x 11 in./A4 LEF pages, with a split of 35% color/65% black-and-white pages.

<sup>&</sup>lt;sup>8</sup> Waste Toner Container yield will vary depending on the image type, area coverage %, and job run length.

<sup>&</sup>lt;sup>9</sup> With optional hard drive.

<sup>\*</sup> Trellix DXL formerly known as McAfee® DXL, Trellix Embedded Control Whitelisting formerly known as McAfee® Embedded Control Whitelisting,
Trellix ePolicy Orchestrator® formerly known as McAfee® ePolicy Orchestrator®, Trellix ESM formerly known as McAfee® ESM, Trellix Integrity Control formerly
known as McAfee® Integrity Control, Trellix Enterprise Security Manager formerly known as McAfee® Enterprise Security Manager. Trellix brand name will be
reflected in future firmware releases.