# Xerox<sup>®</sup> AltaLink<sup>®</sup> Color Multifunction Printers

xerox™

C8130/C8135/C8145/C8155/C8170



Xerox® AltaLink® C8100 Series Color Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.

System Specification	AltαLink® C8130	AltaLink® C8135	AltaLink® C8145	AltαLink® C8155	AltαLink® C8170	
Speed <sup>1</sup>						
Color/Black-and-White	Up to 30/30 ppm	Up to 35/35 ppm	Up to 45/45 ppm	Up to 55/55 ppm	Up to 70/70 ppm	
Monthly Duty Cycle <sup>2</sup>	Up to 90,000 pages	Up to 110,000 pages	Up to 200,000 pages	Up to 300,000 pages	Up to 300,000 pages	
Hard Drive/Processor/ Memory	Minimum 128 GB SSD/ <b>Option</b>	nal: 500 GB HDD/Intel Atom® Q	uad Core 1.91 GHz/4 GB system	memory (8 GB system memory a	AltaLink® C8170)	
Connectivity	Ethernet 10/100/1000 Base-T,	, High-speed USB 2.0 direct prin	t, NFC, <b>Optional:</b> WiFi/WiFi Direc	ct with Xerox® Dual Band Wireles	ss Kit, Bluetooth (iBeacon)	
Controller Features	Configuration Cloning, Configu	ıration Watchdog, Fleet Orchest	rator, Remote Control Panel, Unif	ied Address Book		
Optional Controller	Xerox® EX-c C8100 Print Server	r Powered by Fiery®				
Copy and Print						
Copy and Print Resolution	<b>Copy:</b> Up to 600 x 600 dpi; <b>Pri</b>	<b>int:</b> Up to 1200 x 2400 dpi				
First-Print-Out Time (as fast as)	5.7 seconds color/4.2 seconds	black-and-white	4.9 seconds color/3.8 seconds black-and-white	4.5 seconds color/3.2 seconds black-and-white	3.8 seconds color/3.0 seconds black-and-white	
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	6.1 seconds color/4.5 seconds black-and-white		5.5 seconds color/4.4 seconds black-and-white	4.7 seconds color/3.7 seconds black-and-white	4.0 seconds color/3.2 seconds black-and-white	
Page Description Language	Adobe® PostScript® 3™, Adobe®	® PDF, PCL® 5c/PCL® 6				
Print Features	marking and infrared detectior (Dropbox, OneDrive, and Goog	Application Defaults, Bi-directional Real-time Status, Booklet Layout, Encrypted Secure Print, Hold All Jobs, Imaging Security with AltaLink's proprietary marking and infrared detection technology, Job Identification, Job Monitoring, Long Sheet (Banner) Printing, Print Around, Print from Cloud Repositories (Dropbox, OneDrive, and Google Drive), Print from USB, Print on Alternate Paper, Scaling, Store and Recall Driver Settings, Two-sided Printing (as default), Xerox® Earth Smart Driver Settings; Optional: Print from and Scan to Xerox® DocuShare® Go content management				
Mobile and Cloud-ready						
Mobile Connectivity	Near Field Communication (NF	FC); <b>Optional:</b> Wi-Fi Direct, Wi-F	i (802.11 b/g/n/ac), AirPrint (iOS	) including iBeacon (Bluetooth)		
Mobile Printing	Mopria® Print, Apple AirPrint™, Xerox® Print Service (Android), @PrintByXerox App; <b>Optional:</b> Xerox® Workplace Mobile App (iOS/Android), AirPrint™ (iOS) including iBeacon (Bluetooth)					
Mobile Scanning	Mopria® Scan, Apple AirPrint™, <b>Optional:</b> Xerox® Workplace Mobile App (iOS/Android)					
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate.  Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® (xerox.com/ecm), XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions)					
Xerox® Workplace Central Platform	One-platform consistency for seamless productivity across computers, mobile devices and printers. With Workflow Central's ever-expanding suite of cloud-based workflows, you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable and shareable text, translate to/from over 40 different languages, and automatically redact Personal Identifiable Information using set words or phrases					

Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution
Cloud Identity Provider (IdP) Integration	Use your desktop, laptop, or mobile login credentials to log in to your AltaLink® MFPs with direct connections to popular cloud identity providers Okta, Ping Identity, and Microsoft® Azure
Scan	
Standard Features	Destinations: Scan to USB/PC via USB port/Email/Network (FTP/SMB), HTTP, HTTPS, SFTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF; Convenience Features: 1-Touch Apps, Imaging Security with AltaLink's proprietary marking and infrared detection technology, Optical Character Recognition (OCR), Password-protected PDF, Scan Preview, Scan to Folder, Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Touchless Workflow Accelerators, TWAIN Support, Unified Address Book
Optional Features	Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive). Xerox® Scanning App for DocuShare®, other solutions available through various Xerox® Business Innovation Partners at xerox.com/Software-Solutions, Print from and Scan to Xerox® DocuShare® Go content management
Fax	
Standard Features	Fax Build Job, Network Server Fax Enablement
Optional Features	Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email, or SMB Share
Security	
Standard Features	802.1x, Access Control, Audit Log, Automated threat response through Trellix DXL*/Cisco® pxGrid integration, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) Integration, Common Criteria Certification (ISO 15408), Configuration Watchdog, Encrypted Secure Print, Encrypted Storage Drive (AES 256-bit, FIPS 140-3), FIPS 140-3, Firmware Verification, HTTPS, Imaging Security (copy, print, scan, email) with AltaLink's proprietary marking and infrared detection technology, IPsec, Job Level Encryption via HTTPS and Drivers, Local Authentication (Internal Database), Trellix Embedded Control Whitelisting*, Trellix ePolicy Orchestrator®*, Network Authentication, Port/IP/Domain Filtering, Security Certificates utilizing ECDSA, Security Dashboard, SFTP and Encrypted Email, SHA-256 Hash Message Authentication, SIEM integration (Splunk, LogRhythm, Trellix ESM*), Signed Email, SNMPv3, TLS1.1/1.2/1.3, TPM, Trusted Boot, User Access and Internal Firewall, User Permissions
Optional Features	Trellix Integrity Control*, Smart Card Enablement Kit (CAC/PIV/.NET)³, Xerox® Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-3) with multi-pass Image Overwrite³, Xerox® Workplace Cloud/Suite Print Management and Content Security; WPA2 and WPA3 with Dual Band Wireless Kit; learn more at xerox.com/WorkplaceSolutions
Print Management	
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Service; learn more at xerox.com/PrintManagement

#### Features and Accessories

#### Single-Pass Duplex Automatic Document Feeder (DADF)

saves time by simultaneously scanning both sides of a document with up to 270 impressions per minute (ipm).



#### **USER INTERFACE**



Intuitive Tablet-like 10.1-inch Color Touchscreen is customizable and lets you perform tasks in just a few taps. Try it out at xerox.com/AltaLink8100UI.

#### PAPER INPUT<sup>4</sup>

Two 520-sheet Adjustable Trays (common with all configurations). Tray 1 handles media sizes up to 11.7 x 17 in./A3 and Tray 2 handles media sizes up to 12 x 18 in./SRA3.



Envelope Kit (optional — replaces Tray 1) provides feeding of up to 60 envelopes.



#### High Capacity Tandem Tray Configuration holds a total paper capacity of up to

3,140 sheets.

#### Four Tray Module Configuration

(available for C8130/C8135) holds a total of up to 2,180 sheets.

Bypass Tray handles up to 100 sheets; Custom sizes: 3.5 x 3.9 in. to 12.6 x 52 in./89 x 98 mm



to 320 x 1,320 mm.

Feeder (optional) holds 3,000 sheets of letter/A4 paper, increasing the to 6,140 sheets.

#### **INNOVATIVE TECHNOLOGIES**



Xerox® Integrated RFID Card Reader (optional) adds card-based authentication with support for over 90 access cards.



Near Field Communication (NFC) Tap-to-Pair allows users to tap their mobile devices to the AltaLink® C8100 Series user panel and quickly connect with the MFP.



Smart Proximity Sensor detects when users are nearby. It conserves energy during inactive periods and automatically activates the device when a user approaches.

#### PAPER OUTPUT/FINISHERS<sup>4</sup>



Office Finisher

(optional) provides

advanced finishing

functions, optional

crease/score and



Business Ready

gives you advanced

finishing functions

at a great value.

(BR) Finisher (optional)



#### C-Fold/Z-Fold Unit (optional) adds C-fold, Z-fold and Z-half-fold capability to the BR Finisher or BR Booklet Maker Finisher.



BR Booklet Maker Finisher (optional) creates 64-page saddle-stitched booklets (2 to 16 sheets).

maximum paper capacity



#### LONG SHEET PRINTING

Long Sheet Feed Kit (optional) provides the ability to print up to 12.6 x 52 in./ 320 x 1.320 mm media.



#### saddle-stitch booklet, capable of 60-page

booklets (2 to 15 sheets).



#### **Dual Offset Catch Tray**

(available when no finishers are installed; Single Offset Catch Tray with finishers).



### Integrated Office Finisher

(optional with C8130/C8135/ C8145/C8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.



## Convenience Stapler (optional) staples up to

50-sheets of 20 lb./75 gsm media.

Device Specification		
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegiar Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic	ı, Danish,
Accessories		
Optional	500GB HDD Bluetooth Kit Booklet Maker for Office Finisher BR (Business Ready) Finisher (requires Horizontal Transport Kit) BR (Business Ready) Finisher (requires Horizontal Transport Kit) BR Booklet Maker Finisher (requires Horizontal Transport Kit) C-fold/Z-fold Unit for BR Finisher or BR Booklet Maker Finisher Convenience Stapler (includes Work Surface5) Envelope Tray (Replaces Tray 1) Foreign Device Interface (Also known as Auxiliary Access Device Interface) for third-party access control devices, such as coin machines and car- High Capacity Feeder 3000 Ad/Letter Hole Punch (2/3, 2/4, Swedish) Horizontal Transport Kit Integrated Office Finisher (Available with AltaLink® C8130, C8135, C8145, C8155) Long Sheet Feed Kit (banner printing) Trellix Integrity Control Enablement Kit* Multi-feed Detection Kit (AltaLink® C8170 only) Office Finisher Scan To Cloud Enablement Kit3 Unicode Font Kit USB Keyboard/Shelf Kit Walk-up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi/Wi-Fi Direct with Dual Band Wireless Kit Xerox® EX-c C8100 Print Server Powered by Fiery® Xerox® Integrated RFID Card Reader Kit	d readers
Electrical Requirements	AltaLink® C8130 AltaLink® C8135 AltaLink® C8145 AltaLink® C8155 AltaLink® C81	70
North America	Voltage: 110-127 VAC +/- 10%       Voltage: 110-12         Frequency: 50/60 Hz +/- 3%, 15 A       Frequency: 50/20 A	27 VAC +/- 10 % /60 Hz +/- 3 % ,
Europe	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A  Voltage: 220-24 Frequency: 50/60 Hz +/- 3%, 10 A  Voltage: 220-24 Frequency: 50/60 Hz +/- 3%, 10 A	40 VAC +/- 10 % /60 Hz +/- 3 % ,

Device Specification (continued)						
Power Consumption	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170	
Running (Average)	115V: 576 watts 230V: 586 watts	115V: 600.3 watts 230V: 595.8 watts	115V: 717 watts 230V: 674 watts	115V: 806 watts 230V: 760 watts	115V: 929 watts 230V: 908 watts	
Standby Mode	115V: 67 watts 230V: 71 watts	115V: 64 watts 230V: 70 watts	115V: 71 watts 230V: 71 watts	115V: 72 watts 230V: 70.3 watts	115V: 91.1 watts 230V: 79 watts	
Auto Off/Sleep Mode	115V: 0.69 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.69 watts 230V: 0.72 watts (Default time to sleep mode = 0 minutes)	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.68 watts 230V: 0.75 watts (Default time to sleep mode = 0 minutes)	
Warm-up (from Off)	As fast as 85 seconds					
Recovery from Sleep	As fast as 4.5 seconds					
Operating Environment						
Required Temperature Range	50 to 82° F/10 to 28° C					
Required Relative Humidity	15% to 85%					
Sound Power Levels	Operating: 63.7/64.2 dB(A) Standby: 40.0/40.0 dB(A)		Operating: 65.2/67.3 dB(A) Standby: 43.0/43.0 dB(A)		Operating: 70.4 dB(A) Standby: 43.0 dB(A)	
Dimensions and Weight						
Base Configuration	Width: 24.4 in./620 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 316 lb./143.1 kg				Width: 24.4 in./620 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 352.1 lb./159.7 kg	
With Integrated Office Finisher (C8130, C8135, C8145, C8155)	Width: 32.2 in./819 mm Depth: 28.5 in./723 mm Height: 44.55 in./1,130 mm Weight: 340 lb./154.2 kg				N/A	
With Office Finisher (with Booklet Maker)	Width: 47.5 in./1,207 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 402.3 lb./182.5 kg				Width: 47.5 in./1207 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 439 lb./199 kg	
Base Configuration with Business Ready (BR) Finisher	Width: 55 in./1,395 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 412.3 lb/187 kg				Width: 55 in./1,395 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 448.4 lb./203.4 kg	
Base Configuration with BR Booklet Maker Finisher	Width: 59 in./1,496.3 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 449.7 lb./204 kg				Width: 59 in./1,496.3 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 486.3 lb./220.6 kg	
Base Configuration with BR Booklet Maker Finisher and C-fold/Z-fold Unit	Width: 64.3 in./1,632 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 560.6 lb./254.3 kg				Width: 64.3 in./1,632 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 597.2 lb./270.9 kg	
Base Configuration with BR Booklet Maker Finisher, C-fold/Z-fold Unit and High Capacity Feeder	Width: 93 in./2,361 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 628.8 lb./285.2 kg				Width: 93 in./2,361 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 665.8 lb./302 kg	
System Certifications/Regulo	atory Compliance					
Certifications	To view the latest list of certific	ations, go to <b>xerox.com/Office</b>	Certifications			

Paper Handling	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Single-Pass Duplex Automat	ic Document Feeder (DADF)	'		<u> </u>	
Capacity <sup>4</sup>	130 sheets				250 sheets
Speed (Up to)	82 ppm black-and-white and a 141 ipm black-and-white and				135 ppm black-and-white and color (simplex) 270 ipm black-and-white and color (duplex)
Paper Sizes Sensed	3.4 x 4.9 in. to 11.7 x 17 in./85	x 125 mm to 297 x 432 mi	m		
Weights	16 to 32 lb. bond/60 to 128 g	sm			
Bypass Tray (Standard)					
Capacity <sup>4</sup>	100 sheets				
Sizes	Custom Sizes: 3.5 x 3.9 in. to	12.6 x 52 in./89 x 98 mm to	320 x 1320 mm (SEF); <b>Optior</b>	nal: Long Sheet Feed Kit (Banner	Printing)
Weights	16 lb. bond to 110 lb. cover/52	2 to 300 gsm, <b>Long sheets/</b>	<b>banners</b> (>19 in./483 mm): 28	lb Bond - 120lb Index/106 - 220	gsm
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Glossy Card Stoc Hole Punched Labels Letterhead Lightweight Card Stock Reloac Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Preprinted Recycled Transparencies  Long Sheets/Banners: Card Stock Reloaded Lightweight Card Stock Lightweight Card Stock Card Stock Card Stock Reloaded Lightweight Card Stock Card Stock Card Stock Card Stock Reloaded Lightweight Card Stock Card Stock Reloaded Lightweight Card Stock Reloace	ck k Reloaded ded Reloaded			
Trays 1 and 2 (Standard)	Lightweight card Stock Neloud	acu .			
Capacity <sup>4</sup>	520 sheets each				
Sizes	<b>Tray 1:</b> Custom Sizes: 5.5 x 7.2 <b>Tray 2:</b> Custom Sizes: 5.5 x 7.2		82 mm to 297 x 432 mm (SEF) 2 mm to SRA3 (SEF)		
Weights	16 lb. bond to 110 lb. cover/52	2 to 300 gsm			
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Plain Plain-Reloaded Preprinted Recycled Transparencies	ck ck Reloaded ded			

Paper Handling (continued)	AltαLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltαLink® C8170		
Four Tray Module (Trays 3 a	nd 4) (Available on C8130/C8	135)			'		
Capacity <sup>4</sup>	Tray 3: 520 sheets Tray 4: 520 sheets						
Sizes	<b>Trays 3 and 4:</b> 5.5 x 7.2 in. to	<b>Trays 3 and 4:</b> 5.5 x 7.2 in. to 12 x 18 in./140 x 182 mm to SRA3 mm (SEF)					
Weights	16 lb. bond to 110 lb. cover/52	2 to 300 gsm					
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Plain Plain-Reloaded Preprinted Recycled Transparencies	ck ck Reloaded ded					
High Capacity Tandem Tray	•						
Capacity <sup>4</sup>	Tray 3: 867 sheets Tray 4: 1,133 sheets						
Sizes	8.5 x 11 in./A4, JIS B5, Executi	ve (7.25 x 10.5 in) LEF					
Weights	16 lb. bond to 110 lb. cover/52	2 to 300 gsm					
Media Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted						
Envelope Tray (Optional - Re	places Tray 1)						
Capacity <sup>4</sup>	Up to 60 envelopes						
Sizes	#10 Commercial (9.25 x 4.125 Custom Sizes: 3.9 x 5.8 in. to 6		52 x 241 mm				
Weights	20 lb. to 24 lb. bond/75 to 90	gsm					
High Capacity Feeder (HCF)	(Optional with all models)						
Capacity <sup>4</sup>	3,000 sheets						
Sizes	Standard Sizes: 8.5 x 11 in. or	7.25 x 10.5 in./A4 or B5 LEF					
Weights	16 lb. bond to 110 lb. cover/52	2 to 300 gsm					
Total Capacity							
Device Total Capacity <sup>4</sup>	Four Tray Module: 2,180 sheet Four Tray Module with High Co High Capacity Tandem Tray M High Capacity Tandem Tray M	apacity Feeder: 5,180 sheets lodule: 3,140 sheets	der: 6,140 sheets				

Finishing	AltaLink® C8130 AltaLink® C8135 AltaLink® C8145 AltaLink® C8155 AltaLink® C8170
Output Trays (Standard) (Du	al Offset Catch Trays not available with Integrated Office Finisher and limited to one with Office Finisher and BR Finishers)
Stacking Tray Capacity <sup>4</sup>	Dual Offset Catch Tray: Up to 250 sheets each Left Side Face up Tray: Up to 100 sheets
Integrated Office Finisher (C	Optional with AltaLink® C8130/C8135/C8145/C8155)
Stacking Tray Capacity <sup>4</sup>	500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4 or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in./A3
Sizes	3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 432 mm
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm
Stapling	Single/Dual Position Auto-Stapling: 50 sheets maximum: Letter/A4/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers)
Office Finisher (Optional)	
Stacking Tray Capacity <sup>4</sup>	2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4)
Stacking Tray Sizes	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm
Multiposition Stapling	50 sheets maximum: Letter/A4/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers)
Hole Punch (Optional)	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
Booklet Maker for Office Fin	isher (Score/Crease, Saddle-stitch Staple) (Optional)
Top Tray Capacity <sup>4</sup>	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or less)
Sizes	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Tabloid – 11 x 17 in./A3 SEF
Saddle-Stitch Stapling	2-15 sheets/8-60 page booklet 16 lb. bond to 80 lb. cover/64 to 220 gsm
Score/Crease	1-15 sheets/unstapled 16 lb. bond to 28 lb. bond/64 to 105 gsm
Business Ready (BR) Finishe	r (Optional) (Requires Horizontal Transport Kit)
Capacity <sup>4</sup>	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 488 mm for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4, and B5 sizes supported
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
BR Booklet Maker Finisher (	Optional) (Requires Horizontal Transport Kit)
Capacity <sup>4</sup>	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 488 mm for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4, and B5 sizes supported
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported

Finishing (continued)	AltaLink® C8130 AltaLink® C8135 AltaLink® C8145 AltaLink® C8155 AltaLink® C8170							
C-fold/Z-fold Unit (Optional	with BR Finisher and BR Bo	with BR Finisher and BR Booklet Maker Finisher)						
Types	C-fold, Z-fold, and Z-half-fold	d						
Capacity <sup>4</sup>	40 sheets							
Sizes	C-fold and Z-fold: Letter – 8. Z-half-fold: Tabloid – 11 x 1							
Weights	16 lb. to 24 lb. bond/64 to 9	0 gsm						
Output Trays	Envelope Tray: C-fold, Z-fold Stacker Tray or Top Tray: Z-h							
Convenience Stapler (Optio	nal - Includes Work Surface	5)						
Capacity <sup>4</sup>	50-sheet stapling 5,000 staples Requires separate power ou	tlet						
Сору	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170			
First-Copy-Out Time (from platen/warmed up Color/Black-and-White)	As fast as 6.1 seconds/ As fast as 4.5 seconds		As fast as 5.5 seconds/ As fast as 4.4 seconds	As fast as 4.7 seconds/ As fast as 3.7 seconds	As fast as 4.0 seconds/ As fast as 3.2 seconds			
Sides (input-output)	1-1, 1-2, 2-2, 2-1							
Quantity	1 to 9,999							
Resolution (max)	Up to 600 x 600 dpi							
Reduction/Enlargement	Variable zoom from 25 % to	400% in 1% increments						
Concurrency	Program-ahead to allow job	to be queued while initial job	is processed (Copy, Print, Fax, an	d Scan)				
Copy Features	Program-ahead to allow job to be queued while initial job is processed (Copy, Print, Fax, and Scan)  Annotation and Bates™ stamping (with color capability and font size adjustment) Authentication for Services (i.e., Color Copy) Auto Paper Select Auto Reduction & Enlargement (to fit selected paper size) Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Imaging Security Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Color Stapling Touchless Workflow Accelerators							

Print	AltaLink® C8130	AltαLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170	
Resolution (up to)	1200 x 2400 dpi					
Print Features	Delay Print (specific time) Use Finishing Fit to New Paper Size Hold All Jobs Image Options (Toner Saver Imaging Security Job Identification (Print ID of LAN Fax (requires optional F Layout/Watermark Long Sheet/Banner N-up (up to 16 pages per sh Paper Selection by Attribute Print From Cloud Repositorie Saved Job (color jobs can be Secure Print with Timed Dele Special Pages (exception pa Store and Recall Driver Settin	r By Words) Bi-directional Real- ser Permissions  , Resolution (Standard, Enhance) or Banner, Print ID in margins of fax Kit)  eet) Sample Set es (Dropbox, OneDrive, and Goe e printed as monochrome) etion ge programming: covers, inser- ngs ox® Earth Smart Settings, Dupli	ced, High)) on first page only or all pages) ogle Drive) ts, exception pages)	rint ID, Smart Sample Set, Hold	All Jobs)	
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, PCL Color jobs can be printed as black-and-white					
Operating Systems	Windows 10 (32 and 64 bit) Windows 11 (32 and 64 bit) MacOS 10.13.x, 10.14.x, 10.15.x, 11.0.x, 12.x Red Hat Linux 6.x, 7.x, 8.x Ubuntu Linux 20.04.x, 22.04.x SuSe Linux Server 12.3-13.x, 15.x  MS Windows 2012 Server (32 and 64 bit) MS Windows 2016 Server (32 and 64 bit) MS Windows 2019 Server (32 and 64 bit) MS Windows 2022 Server (32 and 64 bit) MS Windows 2022 Server (32 and 64 bit) MS Windows 2022 Server 12.2-12.4, 15.x					
Network Protocols		et Printing Protocol, LPR/LPD, F ing over IP	Raw Socket Printing/Port 9100,	IPv4/IPv6, WSD		
Font Capability	PCL: 93 scalable fonts, line p	rinter, and bitmap font (includ	ling Cyrillic font support) PostSo	cript 3: 173 Type 1 fonts, 2 Multi	ole Master fonts	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade, and manage Xerox® Devices and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management. Support for Microsoft Universal Print					
Xerox <sup>®</sup> Pull Print Driver	driver. The Xerox® Pull Print [	Driver extends convenience ac		assets. IT administrators no long	nent. Uses a single queue and single er need to manage and configure	
Unified Address Book for Fax	, Email, and Scan to					
Features	Services supported: Fax, Emo Maximum contacts: 5,000 Contacts: Supports 1 or mor Favorites for quick access of	e destinations				

Scan	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170	
Concurrency	Scan while the system is pri concurrent jobs)	nting, copying, or while it is tro	nsferring scan to network or fax	jobs (priority is for return of scanne	d originals and printing	
Input Speed (up to)	82 ppm black-and-white and color (simplex) 141 ipm black-and-white and color (duplex) 1270 ipm black-and-wcolor (duplex) 135 ppm black-and-wnd-wnd-wnd-wnd-wnd-wnd-wnd-wnd-wnd-w					
Resolution	150 x 150 dpi to 600 x 600	dpi				
Bit Depth	1-bit (black-and-white), 8-b	it (grayscale), 24-bit (color)				
Maximum Scan Area	11 x 17 in./A3					
Scan Template Management	Support 250 scan template Create Xerox® CentreWare®		via device cloning to other multi	function printers' confirmation shee	et options	
Network Protocols	SFTP, FTP, SMB, HTTP, HTT	PS				
File Compression		IH, G4 MMR compression – sin DF/A-1b (MRC, JPEG, G3 MH,		Arithmetic Compression, Deflate (fo	or black-and-white and within	
Document Management Fields (Metadata)	1 to 6 user programmable name, default value, and		scan to file templates and unlim	ited fields within the template – Me	tadata field consists of field	
Scan Features	Auto Background and Shac Bound Originals Compression Quality/File Si Edge Erase Imaging Security Mixed Size Originals Scan B Original Type (Photo and To Reduction/Enlargement Scan Preview Single Touch Scan buttons Size for Size (for mixed size Touchless Workflow Acceler TWAIN Support/WIA 2.0 Si	ze Control  uild Job  ext, Photo, Text, Map, Newspap  (up to 10)  originals)  ators	per/Magazine)			
Scan to Email (Standard)						
Scan Features	Auto send to self     Email signatures (6 lines of Email signing (requires Srean to Email S/MIME En Touchless Workflow Accel	nart Card option) cryption	nail message body (user configi	urable), email Embedded Web Serve	r confirmation sheet options	
Directory Access	Address list via LDAP (Wind	ows Active Directory, Exchang	e, Notes, Domino), Device Addre	ess Book		
Scan To						
Standard Features	Scan to Email Scan to Home Scan to Mailbox Scan to Network (using Sec Scan to Network Folder (usi Scan to PC/Server Client (SI Scan to PC via USB port Scan to USB	ng Secure FTP/HTTP/HTTPS)				
Optional Features	Native Scan to Cloud Repos	sitories (Dropbox, OneDrive, ar	d Google Drive) <sup>3</sup>			
Workflow Scanning (Option	al features)					
Scanning Software	Autostore v7 eCopy ScanStation v5.2 ecopy ShareScan v5.2					
Scanning Apps and Xerox App Gallery		orive, Microsoft OneDrive, Micr lable in the Xerox App Gallery:		orkplace Mobile App (iOS/Android)		

Audit Log	Security	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
<ul> <li>Trellix Embedded Control* (whitelisting), Trellix Integrity Control* (optional)</li> <li>Port disablement including USB ports</li> <li>Security Dashboard</li> <li>Security Information and Event Management (SIEM) support for Trellix Enterprise Security Manager*, LogRhythm, and Splunk</li> </ul>	-	Audit Log Cisco® Identity Services En Configuration Watchdog (N 802.1x Admin Password Reset Audit Log Automatic Software Upg Email Alerts FIPS 140-3 Hold All Jobs Immediate Job Overwrite Installation Policies Irrellix Embedded Control PII - Login Name PostScript Passwords Remote Services Enablen Remote Start (Mopria® o Remote Start (Mopria® o Remote Start (TWAIN) Reprint Saved Jobs Scan to Mailbox (Interna Scheduled Disk Overwrite Secure Passcode Length Secure Print Device Polici SIEM SNMP System Timeout USB (Print from USB) USB (Scan to USB) USB Port Management User Data Encryption Expanded Authentication Digitally signed PDF (whe Encrypted and authentic Encrypted and authentic Encrypted Authentication (Int Network authentication (Int Network authentication (Int Network authentication (Int Network authentication (Int Secure Data Secure Print (up to 10 dig Expanded Authorization Authorization per user pe SA access based on netw Secure Network Access User Permissions requiree Full System Common Crite Hide Print Job Names Imaging Security	gine (ISE) compatible Monitors and remediates 75 st grade  grade	cation) to Email and Network Scan Templates o 1.3, IPPS, HTTPS, SFTP, SNMPv: g approved algorithms <sup>9</sup> e services via Kerberos (UNIX/W cludes sanitation of unused are bort (2048 bit certificate key)/.N attion) stures (e.g., color access, or time b) Protection Profile for Hardcopy	areas):  (inly) 3  (indows Server 2008), SMB (Windows Server 2008), SMB (Wi	ndows Server 2008,
• WPA2 and WPA3 are supported by the Dual Band Wireless Kit  Xerox® Integrated RFID Card Reader  Integrated support for most industry security cards providing additional security; with embedded multifunction printer card readers in the multifunction printer panel		Hide Print Job Names     Imaging Security     IP Filter, IPsec, IPv6, TLS V     Trellix Embedded Control*     Port disablement including     Security Dashboard     Security Information and E     WPA2 and WPA3 are support.  Integrated support for most	1.1, V1.2, V1.3, SNMP V1/V2/ (whitelisting), Trellix Integrity I USB ports Event Management (SIEM) su orted by the Dual Band Wirel industry security cards provic	V3, HTTPs, 802.1X, SFTP Control* (optional) ipport for Trellix Enterprise Secu	rity Manager*, LogRhythm, and	· 

Fax	AltaLink® C8130	AltaLink® C8135	AltαLink <sup>®</sup> C8145	AltaLink® C8155	AltαLink® C8170			
Network Server Fax Features								
Compatibility	ITU (CCITT) group 3; Various X	TU (CCITT) group 3; Various Xerox® Business Innovation Partner Solutions						
Maximum Scan Area	11 x 17 in./A3	1 x 17 in./A3						
Fax Send Features	Add to Send List (200 numbers	ne- or Two-sided Scanning (up to 11 x 17 in./A3) dd to Send List (200 numbers maximum) uild Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text)						
Fax Print Features	One- or Two-sided Printing, Stap	ole, Secure Print						
Transmission Resolution	Superfine: 400 x 200 dpi (Scan Fine: 200 x 200 dpi Standard: 200 x 100 dpi	at 600 x 600 dpi)						
Walk-up Fax Features (Option	nal; Customer-Installable – 1 a	nd 2 lines)						
Compatibility	ITU (CCITT) Group 3							
Speed/Modems	One or Two V.34 modems: 33,6	500 bps. Less than 4 seconds p	oer page transmission time					
Compression/Speed	MH/G3, MR/G3, MMR/SG3, JBI	G/SG3						
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 6 Receive: Accepts all sizes	500 x 600 dpi						
Fax Send Features	Automatic Cover Sheets Automatic Memory Resend Batch Send (up to memory cap Delay Start, Build Job, Favorites Device Address Book (up to 5,0 LAN Fax (fax from print driver)	Automatic Memory Resend Batch Send (up to memory capacity) Delay Start, Build Job, Favorites Device Address Book (up to 5,000 contacts) LAN Fax (fax from print driver) Page-by-page Job Status at the Machine PSTN Fax						
Fax Receive Features	Auto Answer Delay One- or Two-sided Printing Output Tray Selection Receive Print Mode – Manual (size, margin, stock, header)/Auto Receive Timestamp Secure Receive Stapled or Unstapled Up to 200 Password Protected Mailboxes							
Fax Forward	Forward to Email or SMB Locati Fax Forward on Receive Only	on						
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite <sup>9</sup> Report, Mailbox Report, Broadcast Report							
Directory Access	Utilizes the Unified Address Boo Group fax available	Jtilizes the Unified Address Book Group fax available						
Auto Redial	Up to 14 attempts (per country 1 to 25 minute intervals	requirements)						
Auto Resend	Up to 5 attempts							

Device Management			
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS		
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System-Power MIB, Fleet Orchestrator, Configuration Watchdog, Xerox® Easy Assist App		
Xerox® CentreWαre® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX, or any other operating system:  • Works with any SNMP-managed printer from any manufacturer  • Remote configuration of SNMP v3  • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management  • Requires Windows 7 and Internet Explorer 6.0 and higher  • Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote install		
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:  • Device monitoring and troubleshooting  • Remote configuration of SNMP v3  • Extensive reporting and discovery of new devices  • Usage collection, chargeback, and billing capabilities  • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install		
Xerox® Workplace Cloud	Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server		
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files, and 1-Touch App files. Auto-assembly feature allows a new AltaLink® to automatically set itself on the network and configure		
Novell NDPS/NEPS	Server gateway application: centralized management tool		
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download.  office.xerox.com/Software-Solutions		
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at office.xerox.com/Software-Solutions		
Xerox® Embedded Web Serve	er — Integrated Device Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller:  • Tray status/contents  • Consumables status  • Alerts  • Remote Control Panel		
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard		
Browsers	Microsoft Edge version 88+ Microsoft Chromium Edge version 79+ Mozilla Firefox 91.9.0, 100.0 Safari 13.1.2, 14.1.2, 15.4 Opera 2020, 2021 Google Chrome version 80.0.x+		
Support	Install print/scan drivers and online support available via support.xerox.com		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic		
Remote Services			
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time		
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for output devices from Xerox based on actual usage, eliminating the need to manually manage supplies inventory		

Accounting				
Xerox® Standard Accounting (Standard)				
Tracking	Copy, Print, Fax, Scan, and Email usage			
Accounting	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)			
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>Administrator has the ability to import or export User Accounts, Group Accounts, General Accounts, and User Limits via an industry standard CSV file</li> </ul>			
Accounting Options – Netwo	Accounting Options – Network Accounting (Allows central server to manage all accounting)			
	Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan, and server fax Numerous solutions are available through Xerox Alliance Partners. For details, visit www.xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third-party Networking Account Interface with third-party accounting terminal for accounting user interface			
Xerox <sup>®</sup> EX-c C8100 Print Serv	er Powered by Fiery® (Optionαl)			
Processor	AMD® GX-424CC processor, 2.4 GHz, Quad-Core, 2M cache			
Memory (ESS)	2 GB			
System Disk	500 GB HDD			
Page Description Language	PostScript v 3020			
Features	Access Controls Automatic two-sided printing Booklet Maker – booklet wizard to create booklets Calibration Digitally Signed Software Updates Expert Color Settings: Profile, Rendering, and Simulation Encryption of critical information Fiery API Fiery Command WorkStation for Mac and Windows clients (customer provided) Fiery Gmmand WorkStation for Mac and Windows clients (customer provided) Fiery FreeForm Create to create personalized files for free Image Enhance IP Fittering Integrates with common cost accounting software, Xerox® Standard Accounting, Xerox® App Gallery Apps, and more Job Preview Job Preview Job Preview Poht Tom USB flash drive PostScript Security Port Blocking Secure Erase Secure Printing Spool-RIP-Print simultaneously Standard support for long sheet banners User Authentication Watermarks			
Connectivity	10Base-T/100Base-TX/1000Base-T Ethernet			
Optional	Fiery Options Bundle (Fiery Spot-On, Auto Trapping, Hot Folders, Virtual Printers), Fiery Hot Folders/Virtual Printers, Fiery Spot-On, Fiery Color Profiler Suite w/EFI ES-2000 Spectrophotometer, Network Switch to connect both printer and Fiery Server to network			

Supplies	Description	Yield		
Toner Cartridge <sup>6</sup>	Black Cyan Magenta Yellow	59,000 pages 28,000 pages 28,000 pages 28,000 pages		
Transfer Belt Cleaner	1 Assembly	160,000 pages		
Second Bias Transfer Roll	1 Assembly	200,000 pages		
Staple Cartridges	For BR Finisher, Integrated Office Finisher, Office Finisher, and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge		
	For BR Booklet Maker (1 cartridge per carton)	5,000 each cartridge		
	For Office Finisher Booklet Maker (8 cartridges per carton)	2,000 each cartridge		
Staple Refills	For Integrated Office Finisher, Office Finisher, BR Finisher, and Convenience Stapler (3 refills per carton)	5,000 each refill		
Fan Filter	1 Assembly (AltaLink® C8170)	500,000 pages		
Xerox® Smart Kit®				
Drum Cartridge <sup>7</sup>	1 Cartridge per Color	180,000 pages		
Waste Toner Container w/o Suction Filter <sup>8</sup>	1 Cartridge (AltaLink® C8130/35/45/55)	69,000 pages		
Waste Toner Container with Suction Filter <sup>9</sup>	1 Cartridge (AltaLink® C8170)	69,000 pages		

<sup>&</sup>lt;sup>1</sup> Declared in accordance with ISO/IEC 24734.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.



 $<sup>^{2}</sup>$  Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Not available in all geographies.

Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

Sold separately in some geographies.

<sup>&</sup>lt;sup>6</sup> Average standard pages. Declared in accordance with ISO/IEC 19798. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes, and image quality set-points.

Average drum yield is based on a run length of 5 pages of 8.5 x 11 in./A4 LEF pages, with split of 35% color/65% black-and-white pages.

<sup>8</sup> Waste Toner Container yield will vary depending on type of image, area coverage %, and job run length.

With optional hard drive.

Trellix DXL formerly known as McAfee® DXL, Trellix Embedded Control Whitelisting formerly known as McAfee® Embedded Control Whitelisting, Trellix Policy Orchestrator® formerly known as McAfee® ePolicy Orchestrator®, Trellix Enterprise Security Manager formerly known as McAfee® END Integrity Control Enablement Kit formerly known as McAfee® Integrity Control Enablement Kit, Trellix Enterprise Security Manager formerly known as McAfee® Enterprise Security Manager. Trellix brand name will be reflected in future firmware releases.