



Xerox® VersaLink® B415 Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to **ConnectKey.com**.

System Specification		
Speed ¹	Up to 50/47 ppm Letter/A4	
	Duplex Print Speed: Up to 24/24 ipm Letter/A4	
Monthly Duty Cycle ²	Up to 175,000 pages	
Processor/Memory/ Hard Drive	Quad Core 1.2GHz/2 GB system memory/32GB eMMC/ Optional : 500+GB HDD	
Connectivity	Gigabit Ethernet 10/100/1000/Hi-Speed USB 2.0 (Type A), Hi-Speed USB (Type B), NFC, Optional: Wireless Network Adapter (802.11 b/g/n/ac + BLE)	
Controller Features	Unified Address Book, Remote Control Panel, Configuration Cloning, Fleet Orchestrator, Configuration Watchdog, Security Dashboard	
Copy and Print		
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 1200 dpi	
First-Print-Out Time (as fast as)	5.4 seconds black-and-white	
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	5.3 seconds black-and-white	
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6	
Print Features	Print from USB, Print from Cloud Repositories (Dropbox, OneDrive, and Google Drive), Encrypted Secure Print, Xerox® WorkCentre® Earth Smart Driver Settings, Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs, Print Around, Print on Alternate Paper	
Mobile and Cloud Ready		
Universal Print Ready	Native Microsoft Universal Print Ready is a cloud print service, available to Microsoft 365 subscribers. It removes the need for on-site print servers and leverages the built-in drivers included in the Windows 10 and 11 PCs. You can enjoy the benefits of cloud hosting with a driverless setup for all Windows 10 and 11 clients. Utilize the Xerox Print Support App (PSA) to gain access to the Xerox Print Properties user interface.	
Mobile Connectivity	Optional: Wi-Fi Direct, Wi-Fi (802.11 b/g/n/αc), AirPrint (iOS) including iBeacon³ (Bluetooth) for AirPrint Discovery	
Mobile Printing	Mopria® Print, Apple® AirPrint®, Xerox® Print Service (Android), Xerox @PrintByXerox App; Optional : Xerox® Workplace App (iOS/Android), iBeacon³ (Bluetooth) for AirPrint Discovery	
Mobile Scanning	Mopria® Scan, Apple® AirPrint® Scan (macOS only); Optional: Xerox® Workplace Mobile App (iOS/Android), Scan to Microsoft OneDrive, Google Drive and DropBox ⁴	
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate. Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® Content Management Platform (xerox.com/ecm), XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions)	
Xerox® Workflow Central Platform	Optional: One-platform consistency for seamless productivity across computers, mobile devices and printers. With Workflow Central's ever-expanding suite of cloud-based workflows you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable and shareable text, translate to/from over 40 different languages, and automatically redact Personal Identifiable Information using set words or phrases	

wis designed to save customers time and money by providing effective control over their rough a set of robust workflows. Xerox enables ultimate customer flexibility by offering these Suite) and with a cloud based-version (Workplace Cloud) of this solution to your VersaLink® MFPs with direct connections to popular cloud identity providers HTTPS, FTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF;), Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Password-protected PDF, Support, Touchless Workflow Accelerators, Workflow Automation provides programmable Drive), Xerox® Scanning App for DocuShare®, other solutions available through various 2-Solutions, Print from and Scan to Xerox® DocuShare® Go Content Management Platform	
, HTTPS, FTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF;), Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Password-protected PDF, Support, Touchless Workflow Accelerators, Workflow Automation provides programmable Drive), Xerox® Scanning App for DocuShare®, other solutions available through various	
), Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Password-protected PDF, Support, Touchless Workflow Accelerators, Workflow Automation provides programmable Drive), Xerox® Scanning App for DocuShare®, other solutions available through various	
), Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Password-protected PDF, Support, Touchless Workflow Accelerators, Workflow Automation provides programmable Drive), Xerox® Scanning App for DocuShare®, other solutions available through various	
,	
Fax Build Job, Network Server Fax Enablement, Walk-up Fax includes LAN Fax, Direct Fax, Fax Forward to Email, or SMB Share	
802.1x, IPsec, HTTPS, SFTP and Encrypted Email, Firmware Verification, Security Manager, LogRhythm SIEM integration, Splunk SIEM integration, Network Authentication, SNMPv3, SHA-256 Hash Message Authentication, TLS1.1/1.2/1.3, Security Certificates utilizing ECDSA, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, Local Authentication (Internal Database), FIPS 140 User Access and Internal Firewall, Port/IP/Domain Filtering, Audit Log, Access Control, User Permissions, Configuration Watchdog, Trusted Platform Module (TPM 2.0), Trusted Boot, AES 256-bit, FIPS 140, Job Level Encryption via HTTPS and Drivers, Signed Email, Common Criteria Certification ⁵ , Encrypted Secure Print, Image Overwrite for optional hard disks ⁶	
Xerox® RFID Card Reader, Hard Disk (AES 256-bit) with multi-pass Image Overwrite ⁶ , Xerox® Workplace Cloud/Suite Print Management and Content Security; learn more at xerox.com/WorkplaceSolutions	
Email), Network Accounting Enablement	
tions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print ement	

Features and Accessories



Single-Pass Duplex Automatic Document Feeder (DADF) saves time by simultaneously scanning both sides of two-sided documents with up to 104/98 ipm Letter/A4. High paper capacity drives productivity, especially for tasks that require large batches of scanned or copied documents.



The intuitive, tablet-like, 7-inch tiltable touch screen allows you to personalize your experience to get more done in fewer taps.
Gain access to an array of productivity boosting apps through the Xerox App Gallery.

The 100-Sheet Bypass Tray handles sizes from 3×8.5 in to 8.5×14 in/76 $\times 148$ mm to 216×356 mm

550-Sheet Tray handles media sizes from 3 x 5.8 in to 8.5 x 14 in/76 x 148 mm to 216 x 360 mm

OPTIONAL PAPER FEEDING

550-Sheet Tray

Add up to three additional 550-sheet trays.



XEROX® EASY ASSIST APP

With businesses moving to a more flexible work environment, workers need the right technology in place to keep productive and get back to what really matters. Xerox Easy Assist App allows you to easily and securely manage your device right from your mobile phone, with real-time monitoring of printer performance and instant access to self-support services - all without the need for any IT support. Learn more at xerox.com/EasyAssist.



OPTIONAL ACCESSORIES

The Convenience Stapler

For simple stapling needs, the Convenience Stapler provides offline stapling of printed output and original documents. Staples up to 20 sheets 20 lb/75 gsm.



Wireless Network Adapter



Printer Stand

500+GB Hard Disk



RFID Card Reader Kits

Device Specification	Device Specification		
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic, Croatian, Ukrainian		
Accessories			
Optional	Convenience Stapler Wireless Network Adapter 500+GB HDD Scan To Cloud Enablement Kit ⁵ Unicode Font Kit		
Electrical Requirements			
North America	Voltage: 110–127 VAC +/-10% Frequency: 50/60Hz +/- 3%, 10A		
Europe	Voltage: 220–240 VAC +/-10% Frequency: 50/60Hz +/- 3%, 5A		
Power Consumption			
Running (Average)	Simplex: 644W Duplex: 407W		
Standby Mode	17W		
Auto Off/Sleep Mode	1.6W (Default time to sleep mode = 1 minute) 49 seconds		
Warm-up (from Off)	135 seconds		
Recovery from Sleep	As fast as 2.9 seconds		
Operating Environment	nment		
Required Temperature Range	50 to 90°F/10 to 32.2°C		
Required Relative Humidity	15 to 80% RH		
Sound Power Levels	Operating: 7.1 B(A) or less Standby: 3.1 B(A) or less		
Sound Pressure Levels	Operating: 55 db(A) or less Standby: 15 db(A) or less		
Dimensions and Weight	Packaged	Unpackaged	
Printer	Width: 22 in/559 mm Depth: 23 in/584 mm Height: 25.9 in/659 mm Weight: 56.4 lb/25.6 kg	Width: 18.9 in/479 mm Depth: 17.8 in/452 mm Height: 20.2 in/514 mm Weight: 47.9 lb/21.7 kg	
550-Sheet tray	Width: 16.9 in/428 mm Depth: 18.4 in/468 mm Height: 7.6 in/193 mm Weight: 12.2 lb/5.5 kg	Width: 15.3 in/389 mm Depth: 14.7 in/373 mm Height: 4.26 in/108 mm Weight: 10.4 lb/4.7 kg	
Printer Stand	Width: 20.7 in/525 mm Depth: 22.2 in/565 mm Height: 9.2 in/235 mm Weight: 37.7 lb/17.1 kg	Width: 18.2 in/463 mm Depth: 20 in/510 mm Height: 17.3 in/440 mm Weight: 32.7 lb/14.8 kg	
System Certifications/Regul	System Certifications/Regulatory Compliance		
Certifications	To view the latest list of certifications, go to xerox.com/OfficeCertifications		

Paper Handling			
Single-Pass Duplex Automatic Document Feeder (DADF)			
Capacity ⁷	100 sheets		
Speed (Up to)	Letter: 104 ipm duplex, 52 ppm simplex, (black-and-white), 84 ipm duplex, 42 ppm simplex, (color) A4: 98 ipm duplex, 49 ppm simplex, (black-and-white), 80 ipm duplex, 40 ppm simplex, (color)		
Paper Sizes	4.1 x 5.8 in to 8.5 x 14 in/ 105 x148 mm to 216 x 356 mm		
Weights	14 to 32 lb bond/52 to 120 gsm		
Bypass Tray (Standard)			
Capacity ⁷	100 sheets		
Sizes	Custom Sizes: 3 x 5.8 in to 8.5 x 14 in/76 x 148 mm to 216 x 356 mm		
Weights	16 to 58 lb bond/60 to 216 gsm		
Media Types	Plain Paper, Light Paper, Heavy Paper, Letterhead, Cardstock, Recycled, Bond, Labels, Glossy, Vinyl, Pre-Printed, Envelope, Colored Paper, Rough Cotton, Custom		
Trays 1 (Standard)	Trays 1 (Standard)		
Capacity ⁷	550 sheets		
Sizes	Tray 1: Custom Sizes: 4.1 x 5.8 in to 8.5 x 14 in/105 x148 mm to 216 x 356 mm		
Weights	16 to 32 lb bond/60 to 120 gsm		
Media Types	Plain Paper, Light Paper, Heavy Paper, Letterhead, Cardstock, Recycled, Bond, Labels, Glossy, Vinyl, Pre-Printed, Envelope, Colored Paper, Rough Cotton, Custom		
Optional Paper Feeding			
Capacity ⁷	550-Sheet Tray: Add up to 3 additional 550-sheet trays		
Sizes	4.1 x 5.8 in to 8.5 x 14 in/ 105 x148 mm to 216 x 356 mm		
Weights	16 to 32 lb bond/60 to 120 gsm		
Media Types	Plain Paper, Light Paper, Heavy Paper, Letterhead, Cardstock, Recycled, Bond, Labels, Glossy, Vinyl, Pre-Printed, Envelope, Colored Paper, Rough Cotton, Custom		
Total Capacity			
Device Total Capacity ⁷	Base Model: 650 sheets 550-Sheet Tray: Add up to 3 additional 550-sheet trays		
Paper Output	250 sheets		

Сору	
First-Copy-Out Time (from platen/ Black-and-White)	As fast as 5.3 seconds black-and-white letter
Sides (input-output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution (max)	Up to 600 x 600 dpi
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments
Concurrency	Program-ahead to allow job to be queued while initial job is processed (Copy, Print, Fax, and Scan)
Copy Features	Annotation and Bates™ stamping (with font size adjustment) Authentication for Services (i.e., Copy) Auto Paper Select Auto Reduction & Enlargement (to fit selected paper size) Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Build Job is supported for all Copy (500+GB HDD is required) and ScanTo/Email/Workflow Scanning/Server Fax/Embedded Fax (500+GB HDD is not required) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Frase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Touchless Workflow Accelerators

Print		
Resolution (up to)	1200 x 1200 dpi	
Print Features	Application Defaults Banner Sheet Enable/Disable Booklet Layout Cover Selection Fit to New Paper Size Hold All Jobs Image Options (Resolution (Enhanced, High) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) LAN Fax (requires optional Fax Kit) Layout/Watermark N-up (up to 16 pages per sheet) Paper Selection by Attribute Print From Cloud Repositories (Dropbox, OneDrive, and Google Drive) Sample Set Saved Job (color jobs can be printed as black-and-white) Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) Two-sided Printing (as default) User Permissions	
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, PCL Color jobs can be printed as black-and-white	
Operating Systems	Windows Server 2012 and R2 Windows Server 2016 Windows Server 2019 Windows Server 2022 Windows 8.1 Windows 10 Windows 11 Mac OS 11.x, 12.x, 13.x Fedora® Core Ubuntu® iOS Android Note: For latest supported versions please visit our Drivers & Downloads page and specify your device at support.xerox.com	
Network Protocols	TCP/IP: HTTP/HTTPS, IPP/IPPS, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD Microsoft Windows Networking over IP Support for Microsoft Universal Print Bonjour®, AirPrint®, Mopria®, ThinPrint Most protocols not in use can be disabled	
Font Capability	PCL: 93 scalable fonts, line printer, and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade, and manage Xerox® Devices and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management.	
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy, and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with many third-party print solutions.	
Unified Address Book for Fax	, Email and Scan to	
Features	Services supported: Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of all services supported	

Scan		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)	
Input Speed (up to)	Letter: 104 ipm duplex, 52 ppm simplex, (black-and-white), 84 ipm duplex, 42 ppm simplex, (color) A4: 98 ipm duplex, 49 ppm simplex, (black-and-white), 80 ipm duplex, 40 ppm simplex, (color)	
Resolution	200 x 200 dpi up to 600 x 600 dpi	
Bit Depth	1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)	
Maximum Scan Area	8.5 x 14 in (215.9 x 355.6 mm), Legal	
Platen	Up to 8.5 x 14 in (216 x 356 mm) Document Feeder: Up to 8.5 x 14 in (216 x 356 mm)	
Scan Template Management	Support 250 scan templates Create Xerox® Embedded Web Server (EWS) scan templates and share via device cloning to other multifunction printers' confirmation sheet options	
Network Protocols	SFTP, FTP, SMB, HTTP, HTTPS	
File Compression	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression – single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for black-and-white and within MRC)) Linearized PDF/PDF/A	
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value, and other configurations • Customized fields viewed on user interface for variable data input	
Scan Features	Auto Background and Shadow Suppression Bound Originals Compression Quality/File Size Control Edge Erase Mixed Size Originals Scan Build Job Original Type (Photo and Text, Photo, Text, Newspaper/Magazine) Reduction/Enlargement Scan Build Job Single Touch Scan buttons (up to 10) Size for Size (for mixed size originals) Touchless Workflow Accelerators TWAIN Support/WIA 2.0 Support	
Scan to Email (Standard)		
Scan Features	Auto send to self Email signatures (6 lines each of 128 character max), email message body (user configurable), email Embedded Web Server confirmation sheet options Email signing (requires Smart Card option) Scan to Email S/MIME Encryption Touchless Workflow Accelerators	
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino), Device Address Book	
Scan To		
Standard Features	Scan to Email Scan to Home Scan to Home Scan to Mailbox Scan to Network (using Secure FTP/HTTP/HTTPS) Scan to Network Folder (using Secure FTP/HTTP/HTTPS) Scan to PC/Server Client (SMB or FTP) Scan to USB	
Optional Features	Native Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive5	
Workflow Scanning (Optiona	Il features)	
Scanning Apps and Xerox App Gallery	Scan to: Dropbox, Google Drive, Microsoft OneDrive, Microsoft Office 365, Box, Xerox® Workplace Mobile App (iOS/Android) See the full list of apps available in the Xerox App Gallery: xerox.com/AppGallery	

Security

Features

- Audit Log
- Cisco® Identity Services Engine (ISE) compatible • Configuration Watchdog (Monitors and remediates security settings in the following areas):
- 802.1x
- Admin Password
- Audit Log
- Automatic Software Upgrade
- Email Alerts
- Fax Passcode Length
- FIPS
- Hold All Jobs
- Infrared Security
- Installation Policies
- Job Data Removal/Immediate Job Overwrite/Schedule Disk Overwrite (depending on HDD or SSD)
- Personally Identifiable Information (PII)
- Postscript Passwords
- Remote Services Enablement
- Remote Start (AirPrint or Mopria)
- Remote Start (TWAIN)
- Reprint Saved Jobs
- Scan to Mailbox (Internal Storage)
- Secure Print Device Policies (Conceal Job Names only)
- SIEM
- SNMP
- Timeout and Resume
- Trellix Embedded Control
- USB (Print from USB)
- USB (Scan to USB)
- USB Port Management
- Expanded Authentication
- Digitally signed PDF (when using Smart Card authentication) Encrypted and authentication to SMTP server for Scan to Email
- Encrypted/Password Protected PDF (when using Email and Network Scan Templates only)
- FIPS 140 256 bit Hard Disk Encryption⁴, TLS 1.1/1.2/1.3, IPPS, HTTPS, SFTP, SNMPv3
- Immediate Image Overwrite/Securely delete jobs using approved algorithms⁶
- Local Authentication (internal database)
- Network authentication to access device and/or device services via Kerberos (UNIX/Windows Server 2008), SMB (Windows Server 2008, Windows server 2012), NDS, LDAP authentication
- On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk⁶
- Smart Card authentication 144k CAC/PIV Card Support (2048 bit certificate key)/.NET
- Secure Data
- Secure Print (up to 10 digit PIN or Network Authentication)
- Expanded Authorization
- Authorization per user per service
- SA access based on network credentials
- Secure Network Access
- User Permissions required to access Print and Print Features (e.g., color access, or time restrictions) reflects in the print driver
- Hide Print Job Names
- IP Filter, IPsec, IPv6, TLS V1.0, V1.2, V1.3, SNMP V1/V2/V3, HTTPs, 802.1X, SFTP
- Port disablement including USB ports,
- LogRhythm SIEM integration
- Splunk SIEM integration

Fax			
Walk-up Fax Features	Valk-up Fax Features		
Compatibility	ITU (CCITT) Group 3		
Speed/Modems	Single V.34 modem: V.34 33600 – 2400 BPS. Less than 4 seconds per page transmission time		
Compression/Speed	MH/G3, MR/G3, MMR/SG3, JBIG/SG3		
Resolution	Walkup Send: BW Resolution 200 x 100 dpi, 204 x 98 dpi (Receive) Fine 200 x 200 dpi (Send) 200 x 200 dpi, 204 x 196 dpi (Receive) 300 x 300 dpi, 204 x 391 dpi (Receive) UltraFine 600 x 600 dpi (Send) 600 x 600 dpi, 400 x 400 dpi, 408 x 391 dpi (Receive) Receive: Accepts all sizes		
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Device Address Book (up to 5,000 contacts) Touchless Workflow Accelerators		
Fax Receive Features	One- or Two-sided Printing Receive Print Mode — Manual (size, margin, stock, header)/Auto Output Tray Selection Secure Receive Receive Timestamp Auto Answer Delay		
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only		
Fax Reports	Activity, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite ⁶ Report, Mailbox Report, Broadcast Report		
Directory Access	Utilizes the Unified Address Book Group fax available		
Auto Redial	Up to 14 attempts (per country requirements) 1 to 25 minute intervals		
Auto Resend	Up to 5 attempts		

Device Management			
Administrative Protocols	DHCP, BOOTP, SNMP, HTTP, HTTPS, AutoIP (Self Assigned Address) DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS, Bonjour		
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System-Power MIB, Fleet Orchestrator, Configuration Watchdog		
Xerox® Easy Assist App	Xerox Easy Assist App allows you to easily and securely manage your device right from your mobile phone, with real-time monitoring of printer performance and instant access to self-support services – all without the need for any IT support		
Xerox® CentreWare® Web Software	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX, or any other operating system: • Works with any SNMP-managed printer from any manufacturer • Remote configuration of SNMP v3 • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management • Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote install		
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Remote configuration of SNMP v3 • Extensive reporting and discovery of new devices • Usage collection, chargeback, and billing capabilities • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install		
Xerox® Workplace Cloud	Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server		
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files, and 1-Touch App files. Auto-assembly feature allows a new VersaLink® to automatically set itself up on the network to be automatically configured		
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download. office.xerox.com/Software-Solutions		
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at office.xerox.com/Software-Solutions		
Xerox [®] Embedded Web Serve	er – Integrated Device Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel		
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator		
Browsers	Microsoft Edge Safari Mozilla Firefox Opera Chrome Brave Browser		
Support	Install print/scan drivers and online support available via support.xerox.com		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Arabic, Croatian, Ukrainian		
Remote Services Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming		
Automatic Supplies Replenishment (ASR)	end-user involvement and ensures that meter reads are submitted to Xerox on time Automatically orders supplies for Xerox® Devices based on actual usage, eliminating the need to manually manage supplies inventory		
Workplace Cloud Direct	Embedded device agent technology allows your printer to connect directly with Xerox Workplace Cloud for a zero network footprint offering a 'true' cloud-only Print Management and Mobile solution.		
Accounting			
Xerox® Standard Accounting	(Standard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 2,495 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)		
Features	Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export User Accounts, Group Accounts, General Accounts, and User Limits via an industry standard CSV file		

Accounting Options – Network Accounting (Allows central server to manage all accounting) Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan, and server fax Numerous solutions are available through Xerox Alliance Partners. For details, visit xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third-party Networking Account Interface with third-party accounting terminal for accounting user interface **Installation Considerations** Clear area around the device is necessary for access and ventilation. The below table shows the area needed on each side for correct installation. 12 in/305 mm 3.94 in/100 mm Rear Left 2 56 in/65 mm Right 4.33 in/110 mm Front 12 in/305 mm What's In The Box All items contained in VersaLink® B415 Multifunction Printer Power Cord the box: Installation Guide Product Information Flyer Product Safety Sheet Software Update Flyer Software and Documentation CD Black cartridge: 6,000 print capacity8 North America and Europe' All other regions Xerox® Supplies and Accessories 006R04728 Genuine Xerox Black Standard Capacity Toner Cartridge, Xerox® VersaLink® B415 Multifunction Printer (6,000 Pages)8 006R04725 Genuine Xerox Black High Capacity Toner Cartridge, Xerox® VersaLink® B415 Multifunction Printer (14,000 Pages)® 006R04726 006R04729 Genuine Xerox Black Extra High Capacity Toner Cartridge, Xerox® VersaLink® B415 Multifunction Printer (25,000 Pages)8 006R04727 006R04730 Genuine Xerox Black Imaging Kit, Xerox® VersaLink® B415 Multifunction Printer (75,000 Pages)9 013R00702 013R00702 Xerox Staple Cartridge (5,000 Staples) 008R13347 008R13347 Optional Xerox® Accessories 550-Sheet Tray 097N02469 097N02470 Wireless Network Adapter 500+GB Hard Disk 097N02443 Xerox Convenience Stapler (110v) 097N02442 Xerox Convenience Stapler (220v) 097N02463

097505244

Xerox Printer Stand

Europe (XE): U.K., France, Germany, Spain, Italy, Netherlands, Belgium, Norway, Sweden, Finland, Denmark, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland Andorra, Azores, Corsica, Greenland, Iceland, Lichtenstein, Luxembourg, Madeira, San Marino

- Declared in accordance with ISO/IEC 24734.
- $Maximum\ volume\ capacity\ expected\ in\ any\ one\ month.\ Not\ expected\ to\ be\ sustained\ on\ a\ regular\ basis.$
- Undergoing evaluation.
- Requires Wireless Network Adapter
- Not available in all geographies
- Requires 500+GB Hard Disk.
- Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.
- 8 Average standard pages. Declared in accordance with ISO/IEC 19798. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes, and image quality set-points.
- Average drum yield is based on a run length of 5 pages of 8.5 x 11 in/A4 LEF
- Not all countries support Green World Alliance. Please check local legislation.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program.¹⁰ Visit xerox.com/About-Xerox/Recycling.

For more information, visit us at xerox.com/Office.

 $@\ 2023\ Xerox\ Corporation.\ All\ rights\ reserved.\ Xerox@,\ CentreWare@,\ ConnectKey@,\ DocuShare@,\ Global\ Print\ Driver@,\ Green\ World\ Alliance@,\ VersaLink@,\ ConnectKey@,\ DocuShare@,\ Global\ Print\ Driver@,\ Green\ World\ Alliance@,\ VersaLink@,\ ConnectKey@,\ DocuShare@,\ Global\ Print\ Driver@,\ Green\ World\ Alliance@,\ VersaLink@,\ Vers$ and WorkCentre® are trademarks of Xerox Corporation in the United States and/or other countries, XMPie® is a trademark of XMPie Inc.



^{*} North America (NA): U.S., Canada





Xerox® VersaLink® B625 Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to **ConnectKey.com**.

System Specification		
Speed ¹	Black-and-White: Up to 65/61 ppm Letter/A4 Duplex Print Speed: 39/37 ipm Letter/A4	
Monthly Duty Cycle ²	Up to 300,000 pages	
Processor/Memory/ Hard Drive	Quad Core 1.2GHz /4 GB system memory/32GB eMMC/ Optional : 500+GB HDD	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.0 direct print, NFC; Optional: WiFi/WiFi Direct with Xerox® Wireless Network Adapter	
Controller Features	Unified Address Book, Remote Control Panel, Configuration Cloning, Fleet Orchestrator, Configuration Watchdog, Security Dashboard	
Copy and Print		
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 1200 dpi	
First-Print-Out Time (as fast as)	4.1 seconds black-and-white	
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	4.6 seconds black-and-white	
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6	
Print Features	Print from USB, Print from Cloud Repositories (Dropbox, OneDrive, and Google Drive), Encrypted Secure Print, Xerox® Earth Smart, Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs, Print Around, Print on Alternate Paper	
Mobile and Cloud Ready		
Universal Print Ready	Microsoft Universal Print is a cloud print service, available to Microsoft 365 subscribers. It removes the need for on-site print servers and leverages the built-in drivers included in the Windows 10 and 11 PCs. You can enjoy the benefits of cloud hosting with a driverless setup for all Windows 10 and 11 clients. Utilize the Xerox Print Support App (PSA) to gain access to the Xerox Print Properties user interface.	
Mobile Connectivity	Optional: Wi-Fi Direct, Wi-Fi (802.11 b/g/n/ac)AirPrint (iOS) including iBeacon ³ (Bluetooth) for AirPrint Discovery	
Mobile Printing	Mopria® Print, Apple® AirPrint®, Xerox® Print Service (Android), @PrintByXerox App; Optional: Xerox® Workplace App (iOS/Android), iBeacon³ (Bluetooth) for AirPrint Discovery	
Mobile Scanning	Mopria® Scan, Apple® AirPrint® Scan; Optional: Xerox® Workplace Mobile App (iOS/Android), Scan to Microsoft OneDrive, Google Drive and DropBox	
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate. Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® Content Management Platform (xerox.com/ecm), XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions)	
Xerox® Workflow Central Platform	Optional: One-platform consistency for seamless productivity across computers, mobile devices and printers. With Workflow Central's ever-expanding suite of cloud-based workflows you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable and shareable text, translate to/from over 40 different languages, and automatically redact Personal Identifiable Information using set words or phrases	

Print Management Standard Features Optional Features	Xerox® Standard Accounting Feature (Copy, Print, Scan, Fax, Email), Network Accounting Enablement Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners.	
Optional Features	Xerox® RFID Card Reader, Hard Disk (AES 256-bit, FIPS 140) with multi-pass Image Overwrite ⁷ , Xerox® Workplace Cloud/Suite Print Management and Content Security; learn more at xerox.com/WorkplaceSolutions	
Standard Features	802.1x, IPsec, HTTPS, SFTP and Encrypted Email, Firmware Verification, LogRhythm SIEM integration, Splunk SIEM integration, Network Authentication, SNMPv3, SHA-256 Hash Message Authentication, TLS1.1/1.2/1.3, Security Certificates utilizing ECDSA, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, Local Authentication (Internal Database), User Access, Port/IP/Domain Filtering, Audit Log, Access Control, User Permissions, Configuration Watchdog, Trusted Platform Module (TPM 2.0), Trusted Boot, AES 256-bit, FIPS 140-3, Job Level Encryption via HTTPS and Drivers, Signed Email, Common Criteria Certification®, Encrypted Secure Print, Immediate Image Overwrite for optional hard disks?	
Security		
Standard Features	Fax Build Job, Network Server Fax Enablement, Secure Fax Receive, Fax Forward to server, Walk-up Fax includes LAN Fax, Direct Fax, Fax Forward to Email, or SMB Share	
Fax		
Optional Features	Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive), Xerox® Scanning App for DocuShare®, other solutions available through various Xerox® Business Innovation Partners at xerox.com/Software-Solutions, Print from and Scan to Xerox® DocuShare® Go Content Management Platform	
Standard Features	Destinations: Scan to USB/Email/Network SFTP, SMB, HTTP, HTTPS, FTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF; Convenience Features: Optical Character Recognition (OCR), Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Password-protected PDF, Unified Address Book, Scan to Folder, 1-Touch Apps, TWAIN Support, Touchless Workflow Accelerators	
Scan		
Cloud Identity Provider (IdP) Integration	Use your desktop, laptop, or mobile login credentials to log in to your VersaLink® MFPs with direct connections to popular cloud identity providers Okta, Ping Identity, and Microsoft® Azure	
Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution	

Features and Accessories

Single-Pass Duplex Automatic Document

Feeder (DADF) saves time by simultaneously scanning both sides of two-sided documents with up to 150/144 ipm Letter/A4. High paper capacity drives productivity, especially for tasks that require large batches of scanned or copied documents.



The intuitive, tablet-like, 7-inch tiltable touch screen allows you to personalize your experience to get more done in fewer taps. Gain access to an array of productivity boosting apps through the Xerox App Gallery.

The 100-Sheet Bypass Tray handles media sizes from 3×5 in to 8.5×14 in/76.2 x 127 mm to 216×356 mm

The 550-Sheet Tray handles media sizes from 3.9×7.5 in to 8.5×14 in/98.4 x 191 mm to 216 x 356 mm



OPTIONAL PAPER FEEDING

550-Sheet Tray

Add up to 3 additional 550-sheet trays for a total paper capacity of 2,300 pages.



Add an optional 2,100-sheet tray for even higher capacity. Can be combined with two optional 550-sheet trays. (Requires Caster Base)





OPTIONAL ACCESSORIES

Wireless Network Adapter

The Caster Base allows

for easy moving of floor-standing configurations.

Printer Stand

500+GB Hard Disk

Card Reader Kit



XEROX® EASY ASSIST APP

With businesses moving to a more flexible work environment, workers need the right technology in place to keep productive and get back to what really matters. Xerox Easy Assist App allows you to easily and securely manage your device on the go right from your mobile phone, with real-time monitoring of printer performance and instant access to self-support services - all without the need for any IT support. Learn more at xerox.com/EasyAssist.



Device Specification		
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic, Croatian, Ukranian	
Accessories		
Optional	Wireless Network Adapter 500+GB HDD Scan To Cloud Enablement Kit Unicode Font Kit	
Electrical Requirements		
North America	Voltage: 110-127 VAC +/-10 % Frequency: 50/60Hz +/- 3 % , 11.6A	
Europe	Voltage: 220-240 VAC +/-10% Frequency: 50/60Hz +/- 3 %, 5.3A	
Power Consumption		
Running (Average)	Simplex: 796W Duplex: 568W	
Standby Mode	31 watts	
Auto Off/Sleep Mode	1.7 watts (Default time to sleep mode = 1 minute)	
Warm-up (from Off)	As fast as 127 seconds	
Recovery from Sleep	As fast as 2.9 seconds	
Operating Environment		
Required Temperature Range	50 to 90°F/ 10 to 32.2°C	
Required Relative Humidity	8 to 80% RH	
Sound Power Levels	Operating: 7.2 B(A) or less Standby: 3.2 B(A) or less	
Sound Pressure Levels	Operating: 56 db(A) or less Standby: 14 db(A) or less	
Dimensions and Weight	Packaged	Unpackaged
Base Configuration	Width: 21.7 in/550 mm Depth: 25. 6 in/650 mm Height: 22.2 in/565 mm Weight: 65.8 in/28.9 mm	Width: 22.0 in/558.8 mm Depth: 22.8 in/578.4 mm Height: 29.1 in/739.1 mm Weight: 97.2 lb/44.1 kg
550-Sheet Tray	Width: 19.6 in/498 mm Depth: 23.5 in/598 mm Height: 7.7 in/196 mm Weight: 18.1 lb/8.2 kg	Width: 16.9 in/428 mm Depth: 20.1 in/510 mm Height: 4.3 in/110 mm Weight: 13.5 lb/6.2 kg
2,100-Sheet Tray	Width: 21.4 in/543.49 mm Depth: 23.5 in/598 mm Height: 18.9 in/479 mm Weight: 20.4 lb/6.8 kg	Width: 16.9 in/428 mm Depth: 20.1 in/510 mm Height: 13.8 in/350 mm Weight: 39 lb/17.7 kg
Caster Base	Width: 34.0 in/864 mm Depth: 35.0 in/889 mm Height: 9.0 in/229 mm Weight: 63.1 lb/28.6 kg	Width: 20.5 in/521 mm Depth: 27.3 in/693 mm Height: 5.0 in/126 mm Weight: 17.4 lb/7.9 kg
Printer Stand	Width: 20.7 in/525 mm Depth: 22.2 in/565 mm Height: 9.2 in/235 mm Weight: 37.7 lb/17.1 kg	Width: 18.2 in/463 mm Depth: 20 in/510 mm Height: 17.3 in/440 mm Weight: 32.7 lb/14.8 kg
System Certifications/Regulo	atory Compliance	
Certifications		To view the latest list of certifications, go to xerox.com/OfficeCertifications

Paper Handling			
Single-Pass Duplex Automatic Document Feeder (DADF)			
Capacity ⁴	200 sheets		
Speed (Up to)	Duplex: 150 ipm/144 ipm Letter/A4 (Color and Black-and-White) Simplex: 75 ppm/72 ppm Letter/A4 (Color and Black-and-White)		
Paper Sizes	3.0 x 5.0 in to 8.5 x 14 in/76 x 127 mm to 216 x 355 mm		
Weights	14 to 32 lb bond/52 to 120 gsm		
Bypass Tray (Standard)			
Capacity ⁴	100 sheets		
Sizes	Custom Sizes: 3 x 5 in to 8.5 x 14 in/76.2 x 127 mm to 216 x 356 mm		
Weights	16 to 47 lb bond/60 to 176 gsm		
Media Types	Bond Card Stock Custom Duplex Envelopes Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted Recycled		
Trays 1 (Standard)			
Capacity ⁴	550 sheets		
Sizes	Tray 1: Custom Sizes: 3.9 x 7.5 in to 8.5 x 14 in/98.4 x 191 mm to 216 x 356 mm		
Weights	16 to 47 lb bond/60 to 176 gsm		
Media Types	Bond Card Stock Custom Duplex Envelopes Glossy Card Stock Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted Recycled		

Paper Handling (continued)			
Additional Trays (Optional)			
Capacity ⁴	550-Sheet Tray: Add up to 3 additional 550-sheet trays 2,100-Sheet Tray: Add an optional 2,100-sheet tray. Can be combined with up to two optional 550-sheet trays. (Requires Caster Base)		
Sizes	3.9 x 7.5 in to 8.5 x 14 in/98 x 191 mm to 216 x 356 mm		
Weights	16 to 47 lb bond/60 to 176 gsm		
Media Types	Bond Card Stock Custom Duplex Envelopes Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted Recycled		
Total Capacity			
Device Total Capacity ⁴	Base Model: 650 sheets 550-Sheet Tray: Add up to 3 additional 550-sheet trays for a total capacity of 2,300 sheets. 2,100-Sheet Tray: Add an optional 2,100-sheet tray for a total capacity of 2,750 sheets. Can be combined with up to two optional 550-sheet trays for a total capacity of 3,850 sheets. (Requires Caster Base) Paper Output: 550 sheets		

Сору	
First-Copy-Out Time (from platen/warmed up/ Black-and-White)	As fast as 4.6 seconds
Sides (input-output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution (max)	Up to 600 x 600 dpi
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments
Concurrency	Program-ahead to allow job to be queued while initial job is processed (Copy, Print, Fax, and Scan)
Copy Features	Annotation and Bates™ stamping (with font size adjustment) Authentication for Services Auto Paper Select Auto Reduction & Enlargement (to fit selected paper size) Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (Enables page-level programming) Build Job is supported for all Copy (500+GB HDD³ is required) and ScanTo/Email/Workflow Scanning/Server Fax/Embedded Fax (500+GB HDD³ is not required) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Touchless Workflow Accelerators

Print		
Resolution (up to)	1200 x 1200 dpi	
Print Features	Application Defaults Banner Sheet Enable/Disable Booklet Layout Cover Selection Fit to New Paper Size Hold All Jobs Image Options (Resolution (Enhanced, High)) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) LAN Fax (requires optional Fax Kit) Layout/Watermark N-up (up to 16 pages per sheet) Paper Selection by Attribute Print From Cloud Repositories (Dropbox, OneDrive, and Google Drive) Sample Set Saved Job Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) Two-sided Printing (as default) User Permissions	
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, PCL	
Operating Systems	Windows Server 2008 SP2 (32- and 64-bit) Windows Server 2012 and R2 (64-bit) Windows Server 2012 and R2 (64-bit) Windows Server 2016 (64-bit) Windows Server 2019 (64-bit) Windows 8 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Windows 11 (32- and 64-bit) Mac OS 10.13, 10.14, 10.15 Fedora® Core Ubuntu® Note: For latest supported versions please visit our Drivers & Downloads page and specify your device at support.xerox.com	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD Microsoft Windows Networking over IP Support for Microsoft Universal Print Bonjour® AirPrint® Mopria® IPv6 Most protocols not in use can be disabled	
Font Capability	PCL: 93 scalable fonts, line printer, and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade, and manage Xerox® Devices and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management	
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy, and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos®, and others	
Unified Address Book for Fax	, Email and Scan to	
Features	Services supported: Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of all services supported	

Scan			
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)		
Input Speed (up to)	Duplex: 150 ipm/144 ipm Letter/A4 (Color and Black-and-White) Simplex: 75 ppm/72 ppm Letter/A4 (Color and Black-and-White)		
Resolution	200 x 200 dpi to 600 x 600 dpi		
Bit Depth	1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)		
Maximum Scan Area	8.5 x 14 in (215.9 x 355.6 mm), Legal		
Platen	Up to 8.5 x 14 in (216 x 356 mm) Document Feeder: Up to 8.5 x 14 in (216 x 356 mm)		
Scan Template Management	Support 250 scan templates Create Xerox® Embedded Web Server (EWS) scan templates and share via device cloning to other multifunction printers' confirmation sheet options		
Network Protocols	SFTP, FTP, SMB, HTTP, HTTPS		
File Compression	Color TIFF (1) or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression – single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for black-and-white and within MRC)) Linearized PDF/PDF/A		
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value, and other configurations Customized fields viewed on user interface for variable data input		
Scan Features	Auto Background and Shadow Suppression Bound Originals Compression Quality/File Size Control Edge Erase Mixed Size Originals Scan Build Job Original Type (Photo and Text, Photo, Text, Map, Newspaper/Magazine) Reduction/Enlargement Single Touch Scan buttons (up to 10) Size for Size (for mixed size originals) Touchless Workflow Accelerators TWAIN Support/WIA 2.0 Support		
Scan to Email (Standard)			
Scan Features	Auto send to self Email signatures (6 lines each of 128 character max), email message body (user configurable), email Embedded Web Server confirmation sheet options Email signing (requires Smart Card option) Scan to Email S/MIME Encryption Touchless Workflow Accelerators		
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino), Device Address Book		
Scan To			
Standard Features	Scan to Email Scan to Home Scan to Mailbox Scan to Network (using Secure FTP/HTTP/HTTPS) Scan to Network Folder (using Secure FTP/HTTP/HTTPS) Scan to PC/Server Client (SMB or FTP) Scan to USB		
Optional Features	Native Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive)		
Workflow Scanning (Options	al features)		
Scanning Apps and Xerox App Gallery	Scan to: Dropbox, Google Drive, Microsoft OneDrive, Microsoft Office 365, Box, Xerox® Workplace Mobile App (iOS/Android) See the full list of apps available in the Xerox App Gallery: xerox.com/AppGallery		

Security

Features

- Audit Log
- Cisco® Identity Services Engine (ISE) compatible • Configuration Watchdog (Monitors and remediates 75 security settings in the following areas):
- 802.1x
- Admin Password Reset
- Audit Log
- Automatic Software Upgrade
- Email Alerts
- FIPS 140
- Hold All Jobs
- Immediate Job Overwrite⁷
- Installation Policies
- PII Login Name
- PostScript Passwords
- Remote Services Enablement
- Remote Start (TWAIN)
- Reprint Saved Jobs
- Scan to Mailbox (Internal storage)
- Scheduled Disk Overwrite7
- Secure Passcode Length
- Secure Print Device Policies
- SIEM
- SNMP
- System Timeout
- USB (Print from USB)
- USB (Scan to USB)
- USB Port Management
- User Data Encryption
- Expanded Authentication
- Digitally signed PDF (when using Smart Card authentication)
- Encrypted and authentication to SMTP server for Scan to Email
- Encrypted/Password Protected PDF (when using Email and Network Scan Templates only)
- FIPS 140 256 bit Hard Disk Encryption⁷, TLS 1.1/1.2/1.3, IPPS, HTTPS, SFTP, SNMPv3
- Immediate Image Overwrite/Securely delete jobs using approved algorithms⁷
- Local Authentication (internal database)
- Network authentication to access device and/or device services via Kerberos (UNIX/Windows Server 2008), SMB (Windows Server 2008, Windows server 2012), NDS, LDAP authentication
- On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk 7
- Smart Card authentication 144k CAC/PIV Card Support (2048 bit certificate key)/.NET
- Secure Data
- Secure Print (up to 10 digit PIN or Network Authentication)
- Expanded Authorization
- Authorization per user per service
- SA access based on network credentials
- Secure Network Access
- User Permissions required to access Print and Print Features (e.g., time restrictions) reflects in the print driver
- Hide Print Job Names
- IP Filter, IPsec, IPv6, TLS V1.0, V1.2, V1.3, SNMP V1/V2/V3, HTTPs, 802.1X, SFTP
- Port disablement including USB ports
- LogRhythm SIEM integration
- Splunk SIEM integration

Fax			
Walk-up Fax Features			
Compatibility	ITU (CCITT) Group 3		
Speed/Modems	Single V.34 modem. V.34 33600 – 2400 BPS. Less than 4 seconds per page transmission time		
Compression/Speed	MH/G3, MR/G3, MMR/SG3, JBIG/SG3		
Resolution	Walkup Send: BW Resolution Standard 200 x 100 dpi (Send) 200 x 100 dpi, 204 x 98 dpi (Receive) Fine 200 x 200 dpi (Send) 200 x 200 dpi, 204 x 196 dpi (Receive) SuperFine 300 x 300 dpi (Send) 300 x 300 dpi, 204 x 391 dpi (Receive) UltraFine 600 x 600 dpi (Send) 600 x 600 dpi, 400 x 400 dpi, 408 x 391 dpi (Receive) Color Resolution Fine 200 x 200 dpi (Send) 200 x 200 dpi (Receive) SuperFine 300 x 300 dpi (Send) 300 x 300 dpi, 400 x 400 dpi (Receive) Receive: Accepts all sizes		
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity) Device Address Book (up to 5,000 contacts) Touchless Workflow Accelerators		
Fax Receive Features	One- or Two-sided Printing Receive Print Mode – Manual (size, margin, stock, header)/Auto Output Tray Selection Up to 200 Password-protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay		
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only		
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite ⁷ Report, Mailbox Report, Broadcast Report		
Directory Access	Utilizes the Unified Address Book Group fax available		
Auto Redial	Up to 14 attempts (per country requirements) 1 to 25 minute intervals		
Auto Resend	Up to 5 attempts		

Device Management			
Administrative Protocols	DHCP, BOOTP, SNMP, SLPv2, HTTP, HTTPS, AutoIP (Self Assigned Address), TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS, Bonjour,		
	syslog (for SIEM)		
Xerox Easy Assist App	Xerox Easy Assist App allows you to easily and securely manage your device on the go right from your mobile phone, with real-time monitoring of printer performance and instant access to self-support services – all without the need for any IT support.		
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System-Power MIB, Fleet Orchestrator, Configuration Watchdog		
Xerox® CentreWare® Web Software	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX, or any other operating system: • Works with any SNMP-managed printer from any manufacturer • Remote configuration of SNMP v3 • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management • Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote install		
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Remote configuration of SNMP v3 • Extensive reporting and discovery of new devices • Usage collection, chargeback, and billing capabilities • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install		
Xerox® Workplace Cloud	Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server		
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files, and 1-Touch App files. Auto-assembly feature allows a new VersaLink® to automatically set itself up on the network to be automatically configured		
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download. office.xerox.com/Software-Solutions		
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at office.xerox.com/Software-Solutions		
Xerox® Embedded Web Serve	er – Integrated Device Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel		
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator		
Browsers	Brave Browser Chrome Microsoft Edge Mozilla Firefox Opera Safari		
Support	Install print/scan drivers and online support available via support.xerox.com		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic, Ukranian, Croatian		
Remote Services			
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time		
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® Devices based on actual usage, eliminating the need to manually manage supplies inventory		
Xerox [®] Workplαce Cloud Direct	Embedded device agent technology allows your printer to connect directly with Xerox Workplace Cloud for a zero network footprint offering a 'true' cloud-only Print Management and Mobile solution		

Accounting					
Xerox® Standard Accountin	g (Standard)				
Tracking	Copy, Print, Fax, Scan and Email usage				
Accounting	Up to 2,495 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)				
Features	Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export User Accounts, Group Accounts, General Accounts, and User Limits via an industry standard CSV file				
Accounting Options – Netw	ork Accounting (Allows central server to manage all accounting)				
	Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan, and server fax Numerous solutions are available through Xerox Alliance Partners. For details, visit xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third-party Networking Account Interface with third-party accounting terminal for accounting user interface				
Installation Considerations					
Clear area around the device is necessary for access and ventilation. The table to the right shows the area needed on each side for correct installation.	Top: 6 in/152 mm Rear: 6 in/152 mm Left: 6 in/152 mm Right: 6 in/152 mm Front: 16 in/406 mm				
What's In The Box					
All items contained in the box: AC Power Cord Installation Guide Product Information Flyer Product Safety Sheet Software Update Flyer Software and Documentation CD Black Print Cartridge: 10,000 page capacity ⁵					
Supplies and Accessories		North America and Europe*	All other regions		
Genuine Xerox Black Stand	ard Capacity Toner Cartridge, Xerox B625 Multifunction Printer (10,000 Pages) ⁵	006R04668	N/A		
Genuine Xerox Black High-	Capacity Toner Cartridge, Xerox B625 Multifunction Printer (25,000 Pages) ⁵	006R04669**	006R04672		
Genuine Xerox Black Extra	High-Capacity Toner Cartridge, Xerox B625 Multifunction Printer (42,000 Pages) ⁵	006R04670	006R04673		
Genuine Xerox Black Imaging Kit, Xerox B625 Multifunction Printer (150,000 Pages) ⁶		013R00699	013R00699		
Optional Accessories					
550-Sheet Tray		097N02445	097N02445		
2,100-Sheet Tray		097N02446			
500+GB Hard Disk		097N02443			
Wireless Network Adapter		097N02444			
Xerox Printer Stand		097S05244			
Caster Base		097N02447			

^{*} North America (NA): U.S., Canada

Europe (XE): U.K., France, Germany, Spain, Italy, Netherlands, Belgium, Norway, Sweden, Finland, Denmark, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland Andorra, Azores, Corsica, Greenland, Iceland,

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. Visit xerox.com/About-Xerox/Recycling.

For more information, visit us at xerox.com/Office.



Lichtenstein, Luxembourg, Madeira, San Marino ** Available in North America only

[#] Currently undergoing evaluation

¹ Declared in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

 $^{^{\}rm 3}$ Wireless Network Adapter is required for iBeacon.

A Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

A Verage standard pages. Declared in accordance with ISO/IEC 19752. Toner yield can vary due to many factors, including but not limited to, image areacoverage, image content, media size, media orientation, run mode, application types, monthly print volumes, and image quality set-points.

 $^{^6}$ Average drum yield is based on a run length of 5 pages of 8.5 x 11 in/A4 LEF 7 Requires 500+GB Hard Disk