



The VersaLink® C7000 Color Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.

SYSTEM SPECIFICATIONS	VERSALINK® C7000
One-Sided Speed ¹ 8.5 x 11 in./A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm	Up to 35 ppm (pages per minute) long edge feed (LEF) Up to 22 ppm Up to 19 ppm
Two-Sided Speed ¹ 8.5 x 11 in./A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm	35 ppm (pages per minute) LEF Up to 14 ppm Up to 13 ppm
Monthly Duty Cycle ²	Up to 153,000 pages/month
Recommended Average Monthly Print Volume ³	Up to 10,000 pages
Hard Drive	320 GB HDD (Optional)
Processor	1.05 GHz Dual-Core
Memory	2 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian

DEVICE SPECIFICATIONS						
ELECTRICAL REQUIREMENTS						
North America	Voltage: 110-127V-10 % Frequency: 50/60 Hz +/-					
Europe and Other Geographies	Voltage: 220-240V +/-10 Frequency: 50 Hz +/-3%					
POWER CONSUMPTION						
Printing ⁴	For 110V: 1.6 kWh For 220V: 1.6 kWh					
Standby Mode ⁴	110V: 94 watts or less 220V: 94 watts or less					
Sleep Mode ⁴	110V: 1.0 watts or less 220V: 1.4 watts or less					
OPERATING ENVIRONMENT						
Required Temperature Range (Storage)	32° to 95° F (0° to 35° C)					
Required Temperature Range (Operating)	50 to 90° F (10 to 32° C)					
Required Relative Humidity	10% to 85%					
Sound Power Levels	Standby: 4.10 B(A) or le					
Sound Pressure Levels	Printing: 52.5 dB(A) Standby: 26.0 dB(A) Full System (including finisher) Printing: 60.0 dB(A) Standby: 26.0 dB(A)					
Boot Time (from Off to UI Ready)	As fast as 98 seconds					
Warm-up Time (from Sleep to UI Ready)	As fast as 12 seconds					
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT		
Base Unit	23.23 in./590 mm	26.41 in./670.8 mm	25.08 in./637 mm	119.71 lb./54.3 kg		
Base Unit with Single Tray with Stand Module	24.24 in./615.7 mm	24.24 in./615.7 mm 26.41 in./670.8 mm 44.04 in./1118.6 mm 171.08 lb./77.6 kg				
Base Unit with Three Tray Module	24.24 in./615.7 mm	24.24 in./615.7 mm 26.41 in./670.8 mm 44.04 in./1118.6 mm 178.75 lb./81.8 kg				
Base Unit with Three Tray Module and Integrated Office Finisher (type A)	24.24 in./615.7 mm	26.41 in./670.8 mm	44.04 in./1118.6 mm	215.17 lb./97.6 kg		
Office Finisher (type GAR)	25.73 in./653.6 mm 26.41 in./670.8 mm 38.90 in./988 mm 195.99 lb./88.9 kg					

CERTIFICATIONS	
To view the latest list of certificati	ions, go to www.xerox.com/OfficeCertifications.
PRINT	
First-Print-Out Time	As fast as 7.6 seconds color
	As fast as 5.1 seconds black-and-white
Print Resolution	Up to 1200 x 2400 dpi
Page Description Languages	Adobe® PostScript® 3™ PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL
Maximum Print Area	4 mm from Lead edge of paper, 2 mm from Side and Trail edges of paper
Print Features	Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Color Adjustments (lightness, contrast, saturation, color balance) Color Correction Draft Mode Finishing (requires finishing) Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default – DN configuration) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.Support.Xerox.com.

Fonts	PostScript fonts: 136 PCL fonts: 83
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.
MOBILE SOLUTIONS AND MOBIL	E DEVICE APPS
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Mopriα® Certified	ConnectKey [®] Technology-enabled print devices are Mopria [®] certified. Mopria [®] certification ensures you can print wirelessly from your Mopria [®] supported (Android) smart phone, tablet and other mobile devices instantly and easily.
Xerox® @printbyXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
Xerox® Print Services plug-in for Android™ (Free αt Google Plαy™ Store)	The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.
SOFTWARE SOLUTIONS	
Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the device.

SECURITY	
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM)
	*Requires HDD/Productivity Kit
ACCOUNTING	IS (NETWORK ASSOCIATIONS (STANDARD)
	NG/NETWORK ACCOUNTING (STANDARD)
Tracking Accounting	Print usage Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NETW	ORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)
	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device print usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account
PAPER HANDLING	
BYPASS TRAY	-
Capacity ⁵	100 sheets
Sizes	Custom sizes: 3.5 x 3.87 in. to 11.69 x 17 in./88.9 x 98.4 mm to 297 x 431.8 mm

Weights One-sided: Two-sided:	16 lb. bond to 80 lb. c 16 lb. bond to 60 lb. c			
Types	Bond Plain Paper Cardstock Custom Envelopes	Hole Punched Labels Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Pre-Printed Recycled	
TRAY 1	,			
Capacity ⁵	520 sheets			
Sizes	Custom sizes: 5.5 x 7.	17 in. to 11.69 x 17 in./139.7 x 182.0 r	mm to 297.0 x 431.8 mm	
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. c 16 lb. bond to 60 lb. c			
Types	Bond Plain Paper Cardstock Custom Hole Punched	Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled	
SINGLE TRAY MODULE (OPTIONAL)			
Capacity ⁵	520 sheets			
Sizes	Custom sizes: 5.5 x 7.1	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm		
Weights One-sided: Two-sided:		16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm		
Types	Bond Plain Paper Cardstock Custom Hole Punched	Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled	
SINGLE TRAY MODULE V	VITH STAND (OPTIONAL)			
Capacity ⁵	520 sheets			
Sizes	Custom sizes: 5.5 x 7.	17 in. to 11.69 x 17 in./139.7 x 182.0 r	mm to 297.0 x 431.8 mm	
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. c 16 lb. bond to 60 lb. c			
Types	Bond Plain Paper Cardstock Custom Hole Punched	Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled	
THREE TRAY MODULE (C	PTIONAL)			
Capacity ⁵	Tray 2: 520 sheets Tray 3: 520 sheets Tray 4: 520 sheets			
Sizes	Custom sizes: 5.5 x 7.1	17 in. to 11.69 x 17 in./139.7 x 182.0 r	mm to 297.0 x 431.8 mm	
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. c 16 lb. bond to 60 lb. c			

Types	Bond Plain Paper Cardstock Custom Hole Punched	Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled		
ENVELOPE TRAY – REPLACES TR	RAY 1 (OPTIONAL)				
Capacity ⁵	Up to 60 envelopes				
Sizes		#10 commercial, Monarch, DL, C5 Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./98 x 148 mm to 162 x 241 mm			
Weights	20 lb. bond to 25 lb. bo	nd/75 to 90 gsm			
TOTAL CAPACITY					
Base Unit Capacity ⁵	620 sheets				
Single Tray Module Capacity ⁵	1,140 sheets				
Single Tray Module with Stand Capacity ⁴	1,140 sheets				
Three Tray Module Capacity ⁵	2,180 sheets				
FINISHING					
OUTPUT TRAYS					
Center Output Catch Trays	500 sheets; tray offsets	5			
INTEGRATED OFFICE FINISHER	BOTH TYPES A AND GA	R (OPTIONAL)			
Stacking Tray	500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4 or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in./A3				
Sizes	3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 432 mm				
Weights	16 lb. bond to 80 lb. cover/60 to 220 gsm (Type GAR up to 256 gsm)				
Stapling	Single Auto stapling: 50 sheets maximum: Letter/A4/B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4-size sheets (less than 90 gsm or (2) 220 gsm covers) (Type GAR supports dual stapling)				
DEVICE MANAGEMENT					
Network Protocols	TCP/IP: HTTP/HTTPS, II LDAP Bonjour®/AirPrint™ Most protocols not in u	-	w Socket Printing/Port 9100, IPv4/IPv6, WSD		
Administrative Protocols	DHCP, SNMP, WINS, HT	TTP, HTTPS, TLS, SNTP, MDNS			
REMOTE CONTROL PANEL					
	 IT administrators and on any device 	convenient technical support and use d other authorized users can control t nce is identical to performing tasks di	he device remotely from a web page		
XEROX® CENTREWARE® WEB					
	management from aWorks with any SNMIProvides help with de	ny workstation, whether running Win P-managed printer from any manufa	th checks and troubleshooting, and device		

5 . 6 .				
Device Status	Tray Status/Contents Consumables Status			
	Consumables StatusBilling/UsageQuick Links			
	Online Support			
Print Queue Viewing	Job print queue management — view and delete			
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)			
Device Administration	Allows simple, remote installation setting of config	uration options and management of the device		
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™			
REMOTE SERVICES				
Xerox® Automatic Meter Reading (AMR)		g meter reads for tracking and billing of Xerox® device d-user involvement and ensures that meter reads are		
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output de manually manage supplies inventory.	evices based on actual usage, eliminating the need to		
WHAT'S IN THE BOX				
	 Starter Capacity Print Cartridge: One of each (Cy Black: 5,300 print capacity⁶ Imaging Drum – One of each (Cyan, Magenta, Y Quick Use Guide Quick Install Guide Software and Documentation CD (with Drivers, Warranty Statement) Power Cord 	'ellow, Black): 82,200 print capacity) ⁶		
SUPPLIES AND ACCESSORIES				
	QUANTITY	FART NOWIDER		
SUPPLIES	T			
Standard Capacity Print Cartridges	Cyan: 3,300 standard pages ⁶ Magenta: 3,300 standard pages ⁶	106R03764 106R03763		
Time cardiages	Yellow: 3,300 standard pages ⁶	106R03762		
	Black: 5,300 standard pages ⁶ 106R03761			
High Capacity Print Cartridges	Cyan: 10,100 standard pages ⁶	106R03760		
	Magenta: 10,100 standard pages ⁶ Yellow: 10,100 standard pages ⁶	106R03759 106R03758		
	Black: 10,700 standard pages ⁶	106R03757		
Worldwide Metered	tridge Magenta: 10,100 standard pages ⁷ 106R03755			
Print Cartridge				
	Yellow: 10,100 standard pages ⁷ 106R03754 Black: 10,700 standard pages ⁷ 106R03753			
CMYK Drum Cartridge	82,200 standard pages ⁸ 113R00782			
Waste Toner Bottle	21,200	115R00129		
Fuser	120V Fuser	115R00137		
. 450.	220V Fuser 115R00138			

Staple Refills for Finishers (3 refills per container)	15,000 staples (5,000 each refill)	008R12941	
Staple Cartridge for Finishers (1 cartridge per container)	5,000 staples (5,000 each cartridge)	008R12964	
ACCESSORIES/OPTIONS			
Single Tray Module (does not inclu	de stand)	097S04910	
Single Tray with Stand Module		097S04907	
Three Tray Module		097S04908	
Envelope Tray (This replaces Tray 1)		497K17720	
Integrated Office Finisher (Type A)		097S04911	
Integrated Office Finisher (Type GAR)		097S04847	
HDD (320 GB hard drive) (Optional)		497K17740	
Wireless Network Adapter Kit		497K16750	
Internal Card Reader/RFID Kit		497K18120 (Western Hemisphere) 497K18140 (Eastern Hemisphere)	

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.



¹ Declared print speed in accordance with ISO/IEC 24734.
2 Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
3 Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.
4 Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.
5 Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.
6 Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.
7 Assumptions: Toner cartridge yield is based on 5% area coverage on 8.5 x 11 in./A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set-points.
8 Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: https://www.office.xerox.com/latest/SUPGL-01.pdf.





The VersaLink® C8000W Color Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.xerox.com/C8000W

SYSTEM SPECIFICATIONS	VERSALINK® C8000W/DT
One-Sided Speed ¹ 8.5 x 11 in./A4 8.5 x 11 in./A4 SEF 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm/ 12 x 18 in/SRA3/320 x 450 mm	Up to 45 ppm (pages per minute) long edge feed (LEF) Up to 32 ppm Up to 26 ppm Up to 22 ppm
Two-Sided Speed ¹ 8.5 x 11 in./A4 8.5 x 11 in./A4 SEF 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm/ 12 x 18 in/SRA3/320 x 450 mm	Up to 45 ppm LEF Up to 32 ppm Up to 17 ppm Up to 15 ppm
Monthly Duty Cycle ²	Up to 205,000 pages per month
Recommended Average Monthly Print Volume ³	Up to 20,000 pages per month
Hard Drive	320 GB HDD (Optional)
Processor	1.6 GHz Dual-Core
Memory	4 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan

North America	DEVICE SPECIFICATIONS					
Frequency: 50/60 Hz +/-3%, 12A	ELECTRICAL REQUIREMENTS					
Frequency: 50/60 Hz +/-3%, 10A	North America					
Printing4	Europe and Other Geographies	Voltage: 220-240V +/- 10 Frequency: 50/60 Hz +/-3	0% %, 10A			
For 220V: 2.32 kWh	POWER CONSUMPTION					
220V: 73.8 Watts or less	Printing ⁴					
DPERATING ENVIRONMENT Required Temperature Range (Storage) Required Temperature Range (Operating) Required Relative Humidity 15% to 85% Must be 22.5% or below if humidity is at 85% Required Relative Humidity 15% to 85% Must be 62.5% or below at 32° C Sound Power Levels Printing: 6.63 B(A) or less Standby: 3.24 B(A) or less Standby: 3.24 B(A) or less Standby: 3.36 B(A) Sound Pressure Levels Printing: 6.63 B(B or less Standby: 15.4 dB or less Standby: 15.4 dB or less Full System (including finisher) Printing: 57.1 dB Standby: 15.2 dB Boot Time (From Off to UI Ready) Warm-up Time (From Sleep to UI Ready) Less than 10 seconds (without HDD) Less than 16 seconds (with HDD) DIMENSIONS AND WEIGHT (UNPACKAGED) WiDTH DEPTH HEIGHT WEIGHT WEIGHT WEIGHT WEIGHT WEIGHT 10.3 in./809.3 mm 178 lb./80.8 kg Two-Tray Module 26.3 in./668.5 mm 28.5 in./723 mm 10.3 in./261.2 mm 60.0 lb./27.2 kg	Standby Mode ⁴					
Required Temperature Range (Storage) Required Temperature Range (Operating) Required Temperature Range (Operating) Required Relative Humidity 15% to 85% Must be 62.5% or below if humidity is at 85% Required Relative Humidity 15% to 85% Must be 62.5% or below at 32° C Sound Power Levels Printing: 6.63 B(A) or less Standby: 3.24 B(A) or less Standby: 3.36 B(A) Standby: 3.36 B(A) Standby: 3.36 B(A) Standby: 15.4 dB or less Full System (including finisher) Printing: 57.1 dB Standby: 15.2 dB Boot Time (From Off to UI Ready) Less than 60 seconds Warm-up Time (From Sleep to UI Ready) Less than 10 seconds (with ut HDD) Less than 16 seconds (with HDD) DIMENSIONS AND WEIGHT (UNPACKAGED) WIDTH DEPTH HEIGHT WEIGHT WEIGHT WEIGHT WEIGHT WEIGHT To 10.3 in./809.3 mm 178 lb./80.8 kg Two-Tray Module 26.3 in./668.5 mm 28.5 in./723 mm 10.3 in./261.2 mm 60.0 lb./27.2 kg	Sleep Mode ⁴					
Range (Storage) 50° to 83° F (10° to 28° C) Must be 28° C or below if humidity is at 85% Required Relative Humidity 15% to 85% Must be 62.5% or below at 32° C Sound Power Levels Printing: 6.63 B(A) or less Standby: 3.24 B(A) or less Standby: 3.24 B(A) or less Standby: 3.36 B(A) Sound Pressure Levels Printing: 7.56 B(A) Standby: 13.4 dB or less Standby: 15.4 dB or less Full System (including finisher) Printing: 57.1 dB Standby: 15.2 dB Boot Time (From Off to UI Ready) Less than 60 seconds Warm-up Time (From Sleep to UI Ready) Less than 10 seconds (with HDD) Less than 16 seconds (with HDD) DIMENSIONS AND WIDTH DEPTH HEIGHT WEIGHT WersaLink® C8000W/DT 24.4 in./620 mm 28.5 in./723 mm 31.9 in./809.3 mm 178 lb./80.8 kg Two-Tray Module 26.3 in./668.5 mm 28.5 in./723 mm 10.3 in./261.2 mm 60.0 lb./27.2 kg	OPERATING ENVIRONMENT					
Range (Operating) Must be 28° C or below if humidity is at 85% Required Relative Humidity 15% to 85% Must be 62.5% or below at 32° C Sound Power Levels Printing: 6.63 B(A) or less Standby: 3.24 B(A) or less Full System (including finisher) Printing: 7.56 B(A) Standby: 3.36 B(A) Sound Pressure Levels Printing: 56.8 dB or less Standby: 15.4 dB or less Standby: 15.4 dB or less Full System (including finisher) Printing: 57.1 dB Standby: 15.2 dB Boot Time (From Off to UI Ready) Warm-up Time (From Sleep to UI Ready) Less than 10 seconds (without HDD) Less than 16 seconds (with HDD) DIMENSIONS AND WIDTH DEPTH HEIGHT WEIGHT VersaLink® C8000W/DT 24.4 in./620 mm 28.5 in./723 mm 10.3 in./261.2 mm 60.0 lb./27.2 kg		Below 48° C, and in comp	oliance with MN2-810.13			
Sound Power Levels						
Standby: 3.24 B(A) or less	Required Relative Humidity	15% to 85% Must be 62.5	5% or below at 32° C			
Standby: 15.4 dB or less Full System (including finisher) Printing: 57.1 dB Standby: 15.2 dB Boot Time (From Off to UI Ready) Warm-up Time (From Sleep to UI Ready) Less than 10 seconds (without HDD) Less than 16 seconds (with HDD) DIMENSIONS AND WIDTH DEPTH HEIGHT WEIGHT WEIGHT VersaLink® C8000W/DT 24.4 in./620 mm 28.5 in./723 mm 31.9 in./809.3 mm 178 lb./80.8 kg Two-Tray Module 26.3 in./668.5 mm 28.5 in./723 mm 10.3 in./261.2 mm 60.0 lb./27.2 kg	Sound Power Levels	Standby: 3.24 B(A) or less Full System (including finisher) Printing: 7.56 B(A)				
(From Off to UI Ready) Less than 10 seconds (without HDD) (From Sleep to UI Ready) Less than 16 seconds (with HDD) DIMENSIONS AND WEIGHT (UNPACKAGED) WIDTH DEPTH HEIGHT WEIGHT VersaLink® C8000W/DT 24.4 in./620 mm 28.5 in./723 mm 31.9 in./809.3 mm 178 lb./80.8 kg Two-Tray Module 26.3 in./668.5 mm 28.5 in./723 mm 10.3 in./261.2 mm 60.0 lb./27.2 kg	Sound Pressure Levels	Standby: 15.4 dB or less Full System (including finisher) Printing: 57.1 dB				
(From Sleep to UI Ready) Less than 16 seconds (with HDD) DIMENSIONS AND WEIGHT (UNPACKAGED) WIDTH DEPTH HEIGHT WEIGHT VersaLink® C8000W/DT 24.4 in./620 mm 28.5 in./723 mm 31.9 in./809.3 mm 178 lb./80.8 kg Two-Tray Module 26.3 in./668.5 mm 28.5 in./723 mm 10.3 in./261.2 mm 60.0 lb./27.2 kg		Less than 60 seconds				
WEIGHT (UNPACKAGED) 24.4 in./620 mm 28.5 in./723 mm 31.9 in./809.3 mm 178 lb./80.8 kg Two-Tray Module 26.3 in./668.5 mm 28.5 in./723 mm 10.3 in./261.2 mm 60.0 lb./27.2 kg						
Two-Tray Module 26.3 in./668.5 mm 28.5 in./723 mm 10.3 in./261.2 mm 60.0 lb./27.2 kg		WIDTH	DEPTH	HEIGHT	WEIGHT	
	VersaLink® C8000W/DT	24.4 in./620 mm	28.5 in./723 mm	31.9 in./809.3 mm	178 lb./80.8 kg	
Tandem Tray Module 26.3 in./668.5 mm 28.5 in./723 mm 10.3 in./261.2 mm 74.5 lb./33.8 kg	Two-Tray Module	26.3 in./668.5 mm	28.5 in./723 mm	10.3 in./261.2 mm	60.0 lb./27.2 kg	
, , , , , , , , , , , , , , , , , , , ,	Tandem Tray Module	26.3 in./668.5 mm	28.5 in./723 mm	10.3 in./261.2 mm	74.5 lb./33.8 kg	
High-Capacity Feeder 15.3 in./389 mm 23.7 in./602.9 mm 15.0 in./380.01 mm 63.9 lb./29.0 kg	High-Capacity Feeder	15.3 in./389 mm	23.7 in./602.9 mm	15.0 in./380.01 mm	63.9 lb./29.0 kg	
Office Finisher 19.7 in./501 mm 25.7 in./653 mm 38.7 in./983 mm 55.1 lb./25 kg	Office Finisher	19.7 in./501 mm	25.7 in./653 mm	38.7 in./983 mm	55.1 lb./25 kg	
Booklet Maker Option for Office Finisher 11.75 in./298.5 mm 26.4 in./673 mm 42.5 in./1080 mm 22.0 lb./10 kg		11.75 in./298.5 mm	26.4 in./673 mm	42.5 in./1080 mm	22.0 lb./10 kg	
BR Booklet Maker Finisher 30.28 in./769.2 mm 28.5 in./723 mm 41.5 in./1055.1 mm 134.3 lb./60.9 kg	BR Booklet Maker Finisher	30.28 in./769.2 mm 28.5 in./723 mm 41.5 in./1055.1 mm 134.3 lb./60.9 kg				

DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C8000W/DT	32.8 in./833 mm	28.2 in./717 mm	33.4 in./852 mm	209.4 lb./95 kg
High-Capacity Feeder	20.7 in./526 mm	29.8 in./756 mm	19.3 in./491 mm	74.3 lb./33.7 kg
Two-Tray Module	32.7 in./830 mm	33.5 in./850 mm	15.75 in./400 mm	72.7 lb./33 kg
Tandem Tray Module	32.7 in./830 mm	33.5 in./850 mm	15.75 in./400 mm	86 lb./39 kg
Office Finisher	31.1 in./790 mm	38.9 in./990 mm	21.8 in./555 mm	77.1 lb./35 kg
Booklet Maker Option for Office Finisher	19.4 in./495 mm	30 in./761 mm	16.9 in./430 mm	31 lb./14 kg
BR Booklet Maker Finisher	30 in./764 mm	30.5 in./774 mm	47.4 in./1203 mm	169.7 lb./77 kg
Horizontal Transport for BR Booklet Maker Finisher	21 in./533 mm	23.1 in./589 mm	12.6 in./319 mm	14.3 lb./6.5 kg

CERTIFICATIONS

To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.

PRINT			
First-Print-Out Time	As fast as 15 seconds color		
	As fast as 14 seconds monochrome		
Print Resolution	Up to 1200 x 2400 dpi		
Page Description Languages	Adobe® PostScript® 3™		
Color Management	Xerox Color Management for 12 different media colors		
Maximum Print Area	4 mm from lead edge of the paper, 2 mm from side and trail edges of the paper		
Print Features	Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Finishing (requires finishing) Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on the first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings		
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016, Server 2019 macOS® 10.14, 10.15, 11 Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com .		

Fonts	PostScript fonts: 136
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox Devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
SECURITY	
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM) *Requires HDD/Productivity Kit
ACCOUNTING	
XEROX® STANDARD ACCOUNT	ING/NETWORK ACCOUNTING (STANDARD)
Tracking	Print usage
Accounting	Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 accounting records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS - NETW	/ORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)
	 Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device print usage Numerous solutions are available through Xerox Alliance Partners. For details, visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at the control panel and pass to third-party Networking Account

PAPER HANDLING					
BYPASS TRAY					
Capacity ⁵	100 sheets				
Sizes		n. to 12.6 x 19 in./88.9 x 98.4 mm to 320 x 12.6 x 52 in./88.9 x 98.4 mm to 320 x 1320			
Weights	Simplex and Duplex: 18	lb. bond to 110 lb. cover/64 to 300 gsm			
Types	Bond Plain Paper Cardstock Custom Envelopes Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Pre-Printed Postcards Recycled		
TRAY 1 AND 2	<u>-</u>				
Capacity ⁵	520 sheets each	520 sheets each			
Sizes		Tray 1: 3.9 x 5.8 in. to 11.7 x 17 in./100 x 148 mm to 297 x 431.8 mm Tray 2: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm			
Weights	Simplex and Duplex: 18	Simplex and Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm			
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Plain Paper Labels Lightweight Glossy Cardstock Cardstock Heavyweight Cardstock Pre-printed Custom Heavyweight Glossy Cardstock Recycled			
TWO-TRAY MODULE	•				
Capacity ⁵	1,040 sheets	1,040 sheets			
Sizes	Custom sizes: 3.9 x 5.8 i	Custom sizes: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm			
Weights	Simplex and Duplex: 18	Simplex and Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm			
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Plain Paper Labels Lightweight Glossy Cardstock Cardstock Heavyweight Cardstock Pre-Printed Custom Heavyweight Glossy Cardstock Recycled			

TANDEM TRAY MODULE					
Capacity⁵	2,000 sheets				
Sizes	8.5 x 11 in., 7.25 x 10.5 i	n./A4, B5			
Weights	Simplex and Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm				
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Lightweight Cardstock Labels Lightweight Glossy Cardstock Heavyweight Cardstock Pre-Printed Heavyweight Glossy Cardstock Recycled Letterhead			
HIGH-CAPACITY FEEDER					
Capacity ⁵	2,000 sheets				
Sizes	8.5 x 11 in., 7.25 x 10.5 i	n./A4, B5			
Weights	18 lb. bond to 95 lb. cov	rer/64 to 216 gsm			
Types	Bond Plain Paper Cardstock Custom	Glossy Cardstock Hole Punched Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Recycled		
ENVELOPE TRAY – REPLACES TR	RAY 1 (OPTIONAL)				
Capacity ⁵	Up to 50 envelopes				
Sizes	#10 commercial, Monarc Custom sizes: 3.5 x 3.85	h, DL, C4, C5, C6 5 in. to 9.5 x 13.1 in./90 x 98 mm to 241 x 3	32 mm		
TOTAL CAPACITY	•				
VersaLink® C8000/DT/W	1,140 sheets				
Maximum Capacity ⁵	5,140 sheets				
FINISHING					
OUTPUT TRAYS					
Dual Offset Catch Tray (Standard when finishers are not attached)		nter tray) nter tray when offset is off) ter tray when offset is on)			
OFFICE FINISHER (OPTIONAL)	- 1				
Capacity ⁵	750 sheets dual stapled	eets unstapled or 1,000 sheets single staple (8.5 x 11 in./A4) ted sets of standard size paper (8.5 x 11 in			
Sizes	11.7 x 17 in./297 x 432	mm minimum for stapling 210 x 148 mm			
Weights	18 lb. bond/60 to 256 gsm				
Multi-position Stapling	50 sheets of 24 lb. bond/90 gsm				
Hole Punch (Optional) North America: Europe and Other Geographies:	Up to 65 lb. cover (220 2/3-hole punch 2/4-hole punch	gsm uncoated)			
BOOKLET MAKER FOR OFFICE F	FINISHER (SCORE/CREASE	, SADDLE-STITCH STAPLE) (OPTIONAL)			
Capacity ⁵	40 booklets (2 to 15 sheet	ets per booklet 20 lb./80 gsm or less)			
Sizes	Letter 8.5 x 11 in./A4 SEF Legal 8.5 x 14 in./B4 SEF Ledger 11 x 17 in./A3 SEF				

Saddle-stitch Stapling	2 to 15 sheets/8-60-page booklet 18 lb. bond to 24 lb. bond/60 to 90 gsm (up to 220 gsm can be used for cover only)		
Score/Crease	1 to 15 sheets/unstapled/60 to 105 gsm only		
OPTIONAL BR BOOKLET MAK	(ER FINISHER (REQUIRES HORIZONTAL TRANSPORT KIT)		
Capacity ⁵	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3		
Sizes	4 x 6 in. to 11 x 17 in./A6 to A3 for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling		
Weights	16 lb. bond to 110 lb. cover/60 to 300 gsm (coated and uncoated)		
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported		
Hole Punch North America Europe	2/3-hole punch 2/4-hole punch 4 hole "Swedish" punch (optional)		
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported		
DEVICE MANAGEMENT			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ Most protocols not in use can be disabled		
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS		
REMOTE CONTROL PANEL			
	Enables faster, more convenient technical support and user training IT administrators and other authorized users can control the device remotely from a web page on any device Remote user experience is identical to performing tasks directly at the device		
XEROX® CENTREWARE® WEB			
	 A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running on Windows or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 		
XEROX® EMBEDDED WEB SER	RVER – INTEGRATED DEVICE WEB PAGE		
Device Status	 Tray status/Contents Consumables Status Billing/Usage Quick Links Online Support 		
Print Queue Viewing	Job print queue management view and delete		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		

Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™			
REMOTE SERVICES	1			
Xerox® Automated Meter Reads (AMR)	Automates the process of collecting and submitting meter re usage. Eliminates the need for time-consuming end-user inv submitted to Xerox on time.			
WHAT'S IN THE BOX				
	VersaLink® C8000W/DT Color Printer Starter Capacity Print Cartridge: One of each (Cyan, Mage White: 5,000 print capacity) Drum Cartridge One of each (Cyan, Magenta, Yellow, 8 Quick User Guide Install Guide VersaLink C8000W Starter and Sample Media Kit Software and Documentation CD (with Drivers, Warranty Disposal Guide) Power Cord	White: 240,000 print capacity) ⁷		
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER		
SUPPLIES				
Standard Capacity Toner Cartridges	Cyan: 7,600 standard pages ⁶ Magenta: 7,600 standard pages ⁶ Yellow: 7,600 standard pages ⁶ White: 5,000 standard pages ⁸	106R04034 106R04035 106R04036 106R04646		
High-Capacity Toner Cartridges	Cyan: 16,500 standard pages ⁶ Magenta: 16,500 standard pages ⁶ Yellow: 16,500 standard pages ⁶	106R04046 106R04047 106R04048		
Drum Cartridge	Cyan: 190,000 standard pages ⁷ Magenta: 190,000 standard pages ⁷ Yellow: 190,000 standard pages ⁷ White: 190,000 standard pages ⁹ 101R00602			
Waste Cartridge	Up to 47,000 standard pages ¹⁰	108R01504		
IBT Cleaner	160,000 standard pages ⁷	104R00256		
Transfer Roller	200,000 standard pages ⁷ 116R00015			
Office Finisher Booklet Maker Cartridge (8 cartridges per container)	16,000 staples (2,000 each cartridge) 008R12897			
Staple Refills for Office Finisher (3 refills per container)	15,000 staples (5,000 each refill) 008R12941			
Staple Cartridges for BR Finisher and Office Finisher (1 cartridge per carton)	5,000 staples (5,000 each cartridge) 008R12964			
Staple Cartridges for BR Booklet Maker (1 cartridge per carton)	5,000 staples 008R13177 (5,000 each cartridge)			

ACCESSORIES/OPTIONS	
Two-Tray Module	097S04969
Tandem Tray Module	097S04970
High-Capacity Feeder	097S04845
Envelope Tray (Replaces Tray 1)	497K17880
Office Finisher	097S05019
2/3 Hole Punch for Office Finisher (available in Eastern Hemisphere)	497K20600
2/4 Hole Punch for Office Finisher (available in Western Hemisphere)	497K20610
Booklet Maker for Office Finisher	497K20590
BR Booklet Maker Finisher with 2/3 Hole Punch (requires Horizontal Transport Kit)	097S04981
BR Booklet Maker Finisher with 2/4 Hole Punch (requires Horizontal Transport Kit)	097S04982
Horizontal Transport Kit for BR Finisher	497K17440
320 GB HDD	097S04971
Wireless Network Adapter Kit	497K16750
Internal Card Reader/RFID Kit	497K18120 (Western Hemisphere) 497K18140 (Eastern Hemisphere)
Bianco Digitale SW Kit	497N07139

Declared print speed in accordance with ISO/IEC 24734.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.



² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Recommended average throughput is not a minimum but is intended to cover a range of volumes for different environments.
Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

Paper capacities are based on 20 lb./75 gsm stock, capacities will vary with different weight stocks.
 Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage, and print mode.
 Approximate pages. Declared yield will vary depending on job run length, media size/orientation, and machine speed. For more information, visit: http://www.office.xerox.com/latest/SUPGL-01.pdf.

⁸ Using 5% coverage.

⁹ Up to 240,000 standard pages running White pages only.

¹⁰ Max yield running 100% white pages with 5% coverage. expected yield 30.4K running 50% WCMY, 40%W, 10%CMY pages.





The VersaLink® C9000 Color Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.

SYSTEM SPECIFICATIONS	VERSALINK® C9000DT	
One-Sided Speed ¹ 8.5 x 11 in./A4 8.5 x 11 in./A4 SEF 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm/ 12 x 18 in/SRA3/320 x 450 mm	Up to 55 ppm (pages per minute) long edge feed (LEF) Up to 40 ppm Up to 32 ppm Up to 27 ppm	
Two-Sided Speed ¹ 8.5 x 11 in./A4 8.5 x 11 in./A4 SEF 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm/ 12 x 18 in/SRA3/320 x 450 mm	Up to 55 ppm LEF Up to 40 ppm Up to 21 ppm Up to 19 ppm	
Monthly Duty Cycle ²	Up to 270,000 pages/month	
Recommended Average Monthly Print Volume³	Up to 30,000 pages per month	
Hard Drive	320 GB HDD	
Processor	1.6 GHz Dual-Core	
Memory	4 GB	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox App Gallery App, Xerox® Standard Accounting Tool, Role Based Permissions, Convenience Authentication Enabled	
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan	

DEVICE SPECIFICATIONS					
ELECTRICAL REQUIREMENTS					
North America		Voltage: 110-127V +/-10% Frequency: 50/60 Hz +/-3%, 12A			
Europe and Other Geographies	Voltage: 220-240V +/-10 Frequency: 50/60 Hz +/-3				
POWER CONSUMPTION					
Printing ⁴	For 110V: 2.85 kWh For 220V: 2.82 kWh				
Standby Mode ⁴	110V: 75.3 Watts or less 220V: 73.8 Watts or less				
Sleep Mode ⁴	0.71 watts or less				
OPERATING ENVIRONMENT					
Required Temperature Range(Storage)	Below 48° C, and in comp	pliance with MN2-810.13			
Required Temperature Range(Operating)	50° to 83° F (10° to 28° C	C) Must be 28° C or below if	humidity is at 85 %		
Required Relative Humidity	15% to 85%; must be 6	2.5% or below at 32°C			
Sound Power Levels	Printing: 6.83 B(A) or less Standby: 3.24 B(A) or less				
	Full System (including finisher) Printing: 7.64 B(A) Standby: 3.38 B(A)				
Sound Pressure Levels	Printing: 58.2 dB or less Standby: 15.1 dB or less				
	Full System (including fir Printing: 58.1 dB Standby: 15.3 dB	nisher)			
Boot Time (from Off to UI Ready)	Less than 60 seconds				
Warm-up Time (from Sleep to UI Ready)	Less than 16 seconds				
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT	
VersaLink® C9000/DT	24.4 in./620 mm	28.5 in./723 mm	31.9 in./809.3 mm	178 lb./80.8 kg	
Two Tray Module	26.3 in./668.5 mm	28.5 in./723 mm	10.3 in./261.2 mm	60.0 lb./27.2 kg	
Tandem Tray Module	26.3 in./668.5 mm	28.5 in./723 mm	10.3 in./261.2 mm	74.5 lb./33.8 kg	
High-Capacity Feeder	15.3 in./389 mm	23.7 in./602.9 mm	15.0 in./380.01 mm	63.9 lb./29.0 kg	
Office Finisher LX	22 in./559.8 mm 21.7 in./552 mm 39.8 in./1012 mm 61.7 lb./28.0 kg				
Office Finisher with Booklet Maker attached	59.5 in./1513 mm 28.4 in./723 mm 42.3 in./1076 mm 334.2 lb./151.6 kg				
BR Booklet Maker Finisher	30.28 in./769.2 mm 28.5 in./723 mm 41.5 in./1055.1 mm 134.3 lb./60.9 kg				

DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C9000/DT	32.8 in./833 mm	28.2 in./717 mm	33.4 in./852 mm	209.4 lb./95 kg
High-Capacity Feeder	20.7 in./526 mm	29.8 in./756 mm	19.3 in./491 mm	74.3 lb./33.7 kg
Two Tray Module	32.7 in./830 mm	33.5 in./850 mm	15.75 in./400 mm	72.7 lb./33 kg
Tandem Tray Module	32.7 in./830 mm	33.5 in./850 mm	15.75 in./400 mm	86 lb./39 kg
Office Finishers	27.2 in./690 mm	40.2 in./1021 mm	25.7 in./654 mm	82 lb./37 kg
Booklet Maker Finisher	20 in./507 mm	30 in./761 mm	17.2 in./437 mm	31 lb./14 kg
BR Booklet Maker Finisher	30 in./764 mm	30.5 in./774 mm	47.4 in./1203 mm	169.7 lb./77 kg
Horizontal Transport for BR BookletMaker Finisher	21 in./533 mm	23.1 in./589 mm	12.6 in./319 mm	14.3 lb./6.5 kg

CERTIFICATIONS

To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.

PRINT	
First-Print-Out Time	As fast as 10.5 seconds color
	As fast as 10 seconds black
Print Resolution	Up to 1200 x 2400 dpi
Page Description Languages	Adobe® PostScript® 3™ PCL® 5c, 6 PDF XPS TIFF JPEG HP-GL
Color Management	Embedded spot color table with the ability to swap out PANTONE® approved color table, Custom spot color editor, Xerox® Precise Color Management System software
Maximum Print Area	4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper

Print Features	Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Color Adjustments (lightness, contrast, saturation, color balance) Color Correction Draft Mode Finishing (requires finishing) Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Stored Jobs Deletion Two-sided Printing (as default)	
	Watermark (predefined and custom) Xerox® Earth Smart Driver Settings	
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A	
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016, Server 2019 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® UNIX® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com.	
Fonts	PostScript fonts: 136 PCL fonts: 83	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade, and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	

MOBILE SOLUTIONS AND MOBILE DEVICE APPS		
Apple® AirPrint®	Print email, photos, and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Mopriα® Certified	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria certification ensures you can print wirelessly from your Mopria supported (Android™) smartphone, tablet, and other mobile devices instantly and easily.	
Xerox® @printbyXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address and release them at the MFP panel.	
Xerox [®] Print Services plug-in for Android™	The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamline mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers using a wireless network. A robust print option set includes two-sided printing, stapling, and secure code release. A free download is available from the Google Play™ store.	
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Solutions boost productivity and reduce costs with a modular print management and mobility solution. Control and manage your printer fleet while enabling mobile productivity with simplified workflows, convenience, and security—for any brand printer, anywhere. Xerox® Workplace Solutions offer flexible license options to suit any size business with the ability to scale as you grow. • Xerox® Workplace Suite: On-site, your server • Xerox® Workplace Cloud: Simple setup, cloud administration To learn more about the Xerox® Workplace Suite and Xerox® Workplace Cloud, visit www.xerox.com/Mobility.	
SOFTWARE SOLUTIONS		
Xerox® ConnectKey® Apps (Found at the Xerox App Gallery App)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC, or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the device.	

SECURITY	
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPV3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM)
ACCOUNTING	Trasted Flate of Third Control of the Control of th
	NTING/NETWORK ACCOUNTING (STANDARD)
Tracking	Print usage
Accounting	Xerox® Standard Accounting Tool Up to 9,999 User Accounts Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 60,000 User IDs; Up to 60,000 Account IDs Up to 14,000 Accounting Records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NE	TWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)
	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device print usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account
PAPER HANDLING	
BYPASS TRAY	
Capacity⁵	100 sheets
Sizes	Custom sizes: 3.5 x 3.9 in. to 12.6 x 19 in./88.9 x 98.4 mm to 320 x 482.6 mm Banners: 3.5 x 3.9 in. to 12.6 x 52 in./88.9 x 98.4 mm to 320 x 1320.8 mm
Weights	Simplex: 18 lb. bond to 130 lb. cover/64 to 350 gsm Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm

Types	Bond Plain Paper Cardstock Custom Envelopes Extra Heavyweight Cardstock Extra Heavyweight Glossy Cardst	Glossy Cardstock Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock ock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Postcards Recycled	
TRAY 1 AND 2				
Capacity ⁵	520 sheets each			
Sizes		Tray 1: 3.9 x 5.8 in. to 11.7 x 17 in./100 x 148 mm to 297 x 431.8 mm Tray 2: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm		
Weights	18 lb. bond to 110 lb. cover/64 to 3	300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled	
TWO TRAY MODULE				
Capacity⁵	1,040 sheets	1,040 sheets		
Sizes	Custom sizes: 3.9 x 5.8 in. to 12.6 x	Custom sizes: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm		
Weights	18 lb. bond to 110 lb. cover/64 to 3	18 lb. bond to 110 lb. cover/64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled	
TANDEM TRAY MODUL	E			
Capacity ⁵	2,000 sheets			
Sizes	8.5 x 11 in., 7.25 x 10.5 in./A4, B5			
Weights	18 lb. bond to 110 lb. cover/64 to 3	300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled	
HIGH-CAPACITY FEEDE	R			
Capacity ⁵	2,000 sheets			
Sizes	8.5 x 11 in., 7.25 x 10.5 in./A4, B5			
Weights	18 lb. bond to 80 lb. cover/64 to 21	18 lb. bond to 80 lb. cover/64 to 216 gsm		
Types	Bond Plain Paper Cardstock Custom	Glossy Cardstock Hole Punched Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Recycled	

ENVELOPE TRAY – REPLACES TRAY	(1 (OPTIONAL)	
Capacity ⁵	Up to 50 envelopes	
Sizes	#10 commercial, Monarch, DL, C4, C5, C6 Custom sizes: 3.5 x 3.85 in. to 9.5 x 13.1 in./90 x 98 mm to 241 x 332 mm	
TOTAL CAPACITY		
VersaLink® C9000/DT Capacity⁵	1,140 sheets	
Maximum Capacity ⁵	5,140 sheets	
FINISHING		
OUTPUT TRAYS		
Catch Tray	500 sheets (without center tray) 2x 250 sheets (with center tray when offset is off) 2x 125 sheets (with center tray when offset is on)	
OFFICE FINISHERS (OPTIONAL)		
Capacity ⁵	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4) (dual stapling only with optional booklet maker) Offset available for collated sets of standard size paper (8.5 x 11 in./A4 to 11 x 17 in./A3)	
Sizes		
Office Finisher LX:	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm	
Office Finisher: Weights	5.8 to 11.7 in. x 5.8 to 17 in./148.0 to 297.0 mm x 148.0 to 432.0 mm	
Office Finisher LX:	16 lb. bond to 80 lb. cover/60 to 220 gsm	
Office Finisher	16 lb. bond to 95 lb. cover/60 to 256 gsm	
Multiposition Stapling	50 sheets of 24 lb. bond/90 gsm	
Hole Punch (Optional) North America: Europe:	Office Finisher LX: up to 65 lb. cover (200 gsm)/Office Finisher: up to 80 lb. cover (220 gsm) 2/3 hole punch 2/4 hole punch	
BOOKLET MAKER FOR OFFICE FIN	ISHERS (SCORE/CREASE, SADDLE-STITCH STAPLE) (OPTIONAL)	
Capacity ⁵	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or less)	
Sizes	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Ledger – 11 x 17 in./A3 SEF	
Saddle-stitch Stapling	2-15 sheets/8-60 page booklet 16 lb. bond to 24 lb. bond/60 to 90 gsm	
Score/Crease	1-15 sheets/unstapled/60-105 gsm only	
OPTIONAL BR BOOKLET MAKER FINISHER (REQUIRES HORIZONTAL TRANSPORT KIT)		
Capacity ⁵	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3	
Sizes	4 x 6 in. to 11 x 17 in./A6 to A3 for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling	
Weights	16 lb. bond to 110 lb. cover/60 to 300 gsm (coated and uncoated)	
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported	

Hole Punch North America Europe	2/3 hole punch 2/4 hole punch 4 hole "Swedish" punch (optional)	
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported	
DEVICE MANAGEMENT		
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS	
REMOTE CONTROL PANEL		
	 Enables faster, more convenient technical support and user training IT administrators and other authorized users can control the device remotely from a web page on any PC Remote user experience is identical to performing tasks directly at the device 	
XEROX® CENTREWARE® WEB		
	 A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 	
XEROX® EMBEDDED WEB SERVER	– INTEGRATED DEVICE WEB PAGE	
Device Status	 Tray status/contents Consumables status Billing/Usage Quick Links Online Support 	
Print Queue Viewing	Job print queue management—view and delete	
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG, TXT, PRN, TIF)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Browsers	Microsoft [®] Internet Explorer [®] Microsoft Edge [™] Mozilla [™] Firefox [®] Apple [®] Safari [®] Google Chrome [™]	
REMOTE SERVICES		
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	

WHAT'S IN THE DOX		
WHAT'S IN THE BOX		
	 VersaLink® C9000 Color Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 12,000 print capacity⁶, Black:18,000 print capacity⁶ Drum Cartridge – One of each (Cyan, Magenta, Yellow, and Black 190,000 print capacity)⁶ Quick Use Guide Install Guide Software and Documentation CD (with Drivers, Warranty Statement and Safety Regulatory Recycle Disposal Guide) Power Cord 	
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES		
Standard Capacity Toner Cartridges	Cyan: 12,300 standard pages ⁵ Magenta: 12,300 standard pages ⁵ Yellow: 12,300 standard pages ⁵ Black: 18,900 standard pages ⁵	106R04062 106R04063 106R04064 106R04065
High Capacity Toner Cartridges	Cyan: 26,500 standard pages ⁶ Magenta: 26,500 standard pages ⁶ Yellow: 26,500 standard pages ⁶ Black: 31,400 standard pages ⁶	106R04074 106R04075 106R04076 106R04077
Drum Cartridge	Cyan: 190,000 standard pages ⁶ Magenta: 190,000 standard pages ⁶ Yellow: 190,000 standard pages ⁶ Black: 190,000 standard pages ⁶	101R00602
Waste Cartridge	47,000 standard pages ⁷	108R01504
IBT Cleaner	160,000 standard pages ⁷	104R00256
Transfer Roller	200,000 standard pages ⁷	116R00015
Office Finisher Booklet Maker Cartridge (8 cartridges per container)	16,000 staples (2,000 each cartridge)	008R12897
Staple Refills for Office Finisher(3 refills per container)	15,000 staples (5,000 each refill)	008R12941
Staple Cartridges for BR Finisher and Office Finisher (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R12964
Staple Cartridges for BR Booklet Maker (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R13177
ACCESSORIES / OPTIONS		
Two Tray Module		097S04969
Tandem Tray Module		097S04970
High-Capacity Feeder		097S04845
Envelope Tray (Replaces Tray 1)		497K17880
Office Finisher LX (includes Gap Filler)		097S04848
Office Finisher		097S05019
2/3 Hole Punch for Office Finisher LX (available in Western Hemisphere)		497K03860
2/3 Hole Punch for Office Finisher (available in Western Hemisphere)		497K20600
2/4 Hole Punch for Office Finisher LX (available in Eastern Hemisphere)		497K03870

2/4 Hole Punch for Office Finisher (available in Eastern Hemisphere)	497K20610
Booklet Maker for Office Finisher LX	497K03852
Booklet Maker for Office Finisher	497K20590
BR Booklet Maker Finisher with 2/3 Hole Punch (comes with Horizontal Transport)	497K21000
BR Booklet Maker finisher with 2/4 Hole Punch	097504982
Swedish 4 Hole Punch for BR Finisher	497K14370
Wireless Network Adapter Kit	497K16750
Xerox Precise Color Management System	097S04974
Internal Card Reader/RFID Kit	497K18120 (Western Hemisphere) 497K18140 (Eastern Hemisphere)

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.



¹ Declared print speed in accordance with ISO/IEC 24734.
2 Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
3 Recommended average throughput is not a minimum but is intended to cover a range of volumes for different environments.
4 Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.
5 Paper capacities are based on 20 lb. 75 gsm stock; capacities will vary with different weight stocks.
6 Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.
7 Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: http://www.offlce.xerox.com/Latest/SUPGL-01.pdf.