

# Xerox® PrimeLink® C9265 / C9275 / C9281 Printer



Meet the Xerox® PrimeLink® C9265 / C9275 / C9281. Engineered to make a great first impression, these intuitive printers come complete with spot-on color fidelity, best-in-class media latitude and professional finishing capabilities.

SYSTEM SPECIFICATIONS	XEROX® PRIMELINK® C9265		XEROX® PRIMELINK® C9275		XEROX® PRIMELINK® C9281	
SIMPLEX SPEEDS	COLOR	BLACK AND WHITE	COLOR	BLACK AND WHITE	COLOR	BLACK AND WHITE
<b>8.5 x 11 in. / A4</b> 52 to 128 gsm uncoated 129 to 176 gsm uncoated 177 to 220 gsm uncoated 221 to 300 gsm uncoated 301 to 350 gsm uncoated 106 to 176 gsm coated 177 to 220 gsm coated 221 to 256 gsm coated 257 to 300 gsm coated 301 to 350 gsm coated	Up to 65 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm Up to 30 ppm Up to 65 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm Up to 30 ppm	Up to 65 ppm Up to 65 ppm Up to 51 ppm Up to 35 ppm Up to 35 ppm Up to 65 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm Up to 30 ppm	Up to 75 ppm Up to 51 ppm Up to 35 ppm Up to 35 ppm Up to 35 ppm Up to 51 ppm Up to 51 ppm Up to 35 ppm Up to 35 ppm Up to 30 ppm	Up to 75 ppm Up to 75 ppm Up to 51 ppm Up to 51 ppm Up to 35 ppm Up to 51 ppm Up to 51 ppm Up to 35 ppm Up to 35 ppm Up to 30 ppm	Up to 81 ppm Up to 51 ppm Up to 35 ppm Up to 35 ppm Up to 35 ppm Up to 51 ppm Up to 51 ppm Up to 35 ppm Up to 35 ppm Up to 35 ppm	Up to 81 ppm Up to 81 ppm Up to 51 ppm Up to 51 ppm Up to 35 ppm Up to 51 ppm Up to 51 ppm Up to 35 ppm Up to 35 ppm Up to 35 ppm
<b>11 x 17 in. / A3</b> 52 to 105 gsm uncoated 106 to 128 gsm uncoated 129 to 176 gsm uncoated 177 to 220 gsm uncoated 221 to 300 gsm uncoated 301 to 350 gsm uncoated 106 to 176 gsm coated 177 to 220 gsm coated 221 to 350 gsm coated	Up to 34 ppm Up to 34 ppm Up to 21 ppm Up to 18 ppm Up to 18 ppm Up to 18 ppm Up to 21 ppm Up to 21 ppm Up to 18 ppm	Up to 34 ppm Up to 34 ppm Up to 34 ppm Up to 27 ppm Up to 18 ppm Up to 18 ppm Up to 21 ppm Up to 21 ppm Up to 18 ppm	Up to 37 ppm Up to 37 ppm Up to 27 ppm Up to 18 ppm Up to 18 ppm Up to 18 ppm Up to 27 ppm Up to 27 ppm Up to 27 ppm Up to 16 ppm	Up to 37 ppm Up to 37 ppm Up to 37 ppm Up to 27 ppm Up to 27 ppm Up to 18 ppm Up to 27 ppm Up to 27 ppm Up to 27 ppm Up to 16 ppm	Up to 42 ppm Up to 42 ppm Up to 27 ppm Up to 18 ppm Up to 18 ppm Up to 18 ppm Up to 27 ppm Up to 27 ppm Up to 27 ppm Up to 18 ppm	Up to 42 ppm Up to 42 ppm Up to 42 ppm Up to 27 ppm Up to 27 ppm Up to 18 ppm Up to 27 ppm Up to 27 ppm Up to 27 ppm Up to 18 ppm
<b>12 x 18 in. / SRA3</b> 52 to 105 gsm uncoated 106 to 128 gsm uncoated 129 to 176 gsm uncoated 177 to 220 gsm uncoated 221 to 300 gsm uncoated 301 to 350 gsm uncoated 106 to 176 gsm coated 177 to 220 gsm coated 221 to 350 gsm coated	Up to 30 ppm Up to 30 ppm Up to 20 ppm Up to 16 ppm Up to 16 ppm Up to 16 ppm Up to 20 ppm Up to 20 ppm Up to 16 ppm	Up to 30 ppm Up to 30 ppm Up to 30 ppm Up to 24 ppm Up to 16 ppm Up to 16 ppm Up to 24 ppm Up to 24 ppm Up to 16 ppm	Up to 34 ppm Up to 34 ppm Up to 24 ppm Up to 16 ppm Up to 16 ppm Up to 16 ppm Up to 24 ppm Up to 24 ppm Up to 24 ppm Up to 16 ppm	Up to 34 ppm Up to 34 ppm Up to 34 ppm Up to 24 ppm Up to 24 ppm Up to 16 ppm Up to 24 ppm Up to 24 ppm Up to 24 ppm Up to 16 ppm	Up to 38 ppm Up to 38 ppm Up to 24 ppm Up to 16 ppm Up to 16 ppm Up to 16 ppm Up to 24 ppm Up to 24 ppm Up to 24 ppm Up to 16 ppm	Up to 38 ppm Up to 38 ppm Up to 38 ppm Up to 24 ppm Up to 24 ppm Up to 16 ppm Up to 24 ppm Up to 24 ppm Up to 24 ppm Up to 16 ppm

# Xerox® PrimeLink® C9265 / C9275 / C9281 Printer

<b>Monthly Duty Cycle</b>	Up to 300,000 pages (maximum volume capacity expected in any one month, not expected to be sustained on a regular basis) <sup>1</sup>
<b>Average Monthly Print Volume (AMPV)</b>	10,000 to 60,000 pages per month <sup>2</sup>
<b>Technology</b>	Ultra-Low-Melt High Definition Emulsion Aggregate (HD EA) Toner with advanced LED imaging technology and 2400 x 2400 dpi resolution
<b>Control Panel Languages</b>	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian and Catalan
<b>ACCESSORIES</b> —Note: Available accessories may vary by geography	
<b>Optional</b>	<ul style="list-style-type: none"> <li>Xerox® EX-i C9200 Series Print Server Powered by Fiery® (FS600 Platform)</li> <li>Xerox® EX C9200 Series Print Server Powered by Fiery® (FS600 Platform)</li> <li>Offset Catch Tray and Offset Catch Tray Fan Kit</li> <li>One-Tray High Capacity Feeder (A4)</li> <li>One-Tray Oversized High Capacity Feeder With Storage Cabinet</li> <li>Two-Tray Oversized High-Capacity Feeder</li> <li>Xerox® Interface Decurler Module</li> <li>Xerox® Business Ready Finisher 2.0 (requires a Vertical Transport Kit)</li> <li>Xerox® Business Ready Booklet Maker Finisher 2.0</li> <li>Xerox® Production Ready Finisher (requires Interface Decurler Module)</li> <li>Xerox® Production Ready Booklet Maker Finisher (requires Interface Decurler Module)</li> <li>Xerox® C/Z Folder</li> <li>GBC® AdvancedPunch Pro™</li> <li>Xerox® Crease and Two-Sided Trimmer</li> <li>Xerox® SquareFold® Trimmer module</li> <li>Xerox® Inserter</li> <li>Convenience Stapler</li> <li>Foreign Device Interface Kit</li> <li>PostScript Kit</li> <li>VoIP Fax (SW) Kit</li> <li>Fax Kits</li> <li>Xerox® SIPRNet Enablement Kit</li> <li>Smart Card Enablement Kit</li> <li>Integrated RFID Card Reader Kit</li> <li>Optical Character Recognition (OCR) Kit</li> <li>USB Hub Kit</li> <li>WiFi Kit</li> <li>Xerox® FreeFlow® VI Compose</li> <li>Xerox® FreeFlow® VI Design Pro</li> <li>Banner Feed Guide</li> <li>Work Surface</li> <li>Top Tray Aligner</li> <li>Top Tray Extension Kit for Banners (requires Production Ready Finisher)</li> </ul>

<b>ELECTRICAL REQUIREMENTS</b>			
<b>North America</b>	Voltage: 110 to 127V Frequency: 50 / 60 Hz + / - 10V, 16 A		
<b>Europe</b>	Voltage: 220 to 240V Frequency: 50 / 60 Hz + / - 3%, 10 A		
<b>Accessories</b> North America: Europe:	Each module requires 120V, 15 A Each module requires 220V, 10 A		
<b>POWER CONSUMPTION</b>			
<b>Standby</b>	195 W		
<b>Running (Average)</b>	PrimeLink® C9265: 1,224 Watts; PrimeLink® C9275: 1,774 Watts; PrimeLink® C9281: 2,104 Watts		
<b>Sleep Mode (Average)</b>	0.5 W (default time to Sleep Mode = 1 minute)		
<b>Low Power Mode</b>	150 W		
<b>Sleep Mode (Recovery)</b>	30 seconds		
<b>OPERATING ENVIRONMENT</b>			
<b>Required Temperature Range</b>	50° to 82° F / 10° to 28° C (Relative Humidity less than 62.5% when the temperature is 90° F / 32° C or lower)		
<b>Required Relative Humidity</b>	15% to 85% (no condensation)		
<b>Sound Pressure Levels</b>	Running: 76 db(A) or lower    Standby: 58 db(A) or lower		
<b>Weight (Approximate Base Unit Only)</b>	542 lbs. / 246 kg		
<b>DIMENSIONS</b> (Estimated Sizes for Individual Modules)	<b>WIDTH</b>	<b>DEPTH</b>	<b>HEIGHT</b>
<b>Base Unit</b>	30.7 in. / 780 mm	31.2 in. / 793 mm	45.4 in. / 1,154 mm
<b>Base Unit with Offset Catch Tray and Bypass Open</b>	62 in. / 1,575 mm	31.2 in. / 793 mm	45.4 in. / 1,154 mm
<b>Business Ready Finisher 2.0</b>	30.4 in. / 771 mm	27.2 in. / 692 mm	41.5 in. / 1,054 mm
<b>Business Ready Booklet Maker Finisher 2.0</b>	30.6 in. / 776 mm	27.2 in. / 692 mm	41.5 in. / 1,054 mm
<b>Business Ready Booklet Maker Finisher 2.0 and C/Z Folder</b>	39.9 in. / 1,013 mm	27.2 in. / 692 mm	41.5 in. / 1,054 mm
<b>Production Ready Finisher and Interface Decurler Module</b>	47 in. / 1,195 mm	28.5 in. / 725 mm	47.2 in. / 1,200 mm
<b>Production Ready Booklet Maker Finisher and Interface Decurler Module</b>	48.5 in. / 1,232 mm	28.5 in. / 725 mm	47.2 in. / 1,200 mm
<b>Production Ready Booklet Maker Finisher and C/Z Folder</b>	57.8 in. / 1,469 mm	28.5 in. / 725 mm	47.2 in. / 1,200 mm

# Xerox® PrimeLink® C9265 / C9275 / C9281 Printer

<b>Crease and Two-Sided Trimmer</b>	23.8 in. / 605 mm	28.5 in. / 725 mm	39.1 in. / 992 mm
<b>Interface Decurler Module</b>	13.38 in. / 340 mm	28.5 in. / 725 mm	39.1 in. / 992 mm
<b>SquareFold® Trimmer</b>	42 in. / 1,066 mm	28.5 in. / 725 mm	21.7 in. / 552 mm
<b>Inserter</b>	6.5 in. / 165 mm	28.5 in. / 725 mm	48.6 in. / 1,235 mm
<b>High Capacity Feeder</b>	15.3 in. / 389 mm	24 in. / 610 mm	14.8 in. / 377 mm
<b>One-Tray Oversized High Capacity Feeder</b>	38.9 in. / 988 mm	30 in. / 762 mm	39 in. / 992 mm
<b>Two-Tray Oversized High Capacity Feeder</b>	38.9 in. / 988 mm	30 in. / 762 mm	39 in. / 992 mm

**CERTIFICATIONS**—To view the latest list of certifications, go to [xerox.com/OfficeCertifications](http://xerox.com/OfficeCertifications).

<b>Graphic Arts Credentials</b>	<p>PANTONE® Matching System*</p> <p>PANTONE® GOE*</p> <p>PANTONE® PLUS*</p> <p>Adobe® PDF Print Engine*</p> <p>Adobe® PostScript® 3™*</p> <p>FOGRA certification**</p> <p>IDEAlliance Digital Press Certified* to GRACoL® specifications**</p> <p>*Requires an additional Fiery® print server option</p> <p>**Coming in 2025</p>
---------------------------------	--

## PAPER HANDLING

### SINGLE-PASS DUPLEX AUTOMATIC DOCUMENT FEEDER (DADF)—NETWORK SCANNING

<b>Capacity<sup>3</sup></b>	250 sheets of plain paper—20 lb. / 75 gsm
<b>Speed</b>	Up to 270 ipm color / 270 ipm black-and-white (two-sided, 8.5 x 11 in. / A4)
<b>Weights</b>	16 to 53 lb. bond / 38 to 200 gsm

### TRAY 5 (BYPASS)

<b>Capacity<sup>3</sup></b>	250 sheets
<b>Sizes</b>	Custom sizes: 3.93 x 5.82 in. to 13 x 19.2 in. / 100 x 148 mm to 330 x 488 mm XLS sheet size: Up to 13 x 56 in. / 330 x 1,300 mm
<b>Weights</b>	16 lb. bond to 129 lb. cover / 52 to 400 gsm (52 to 350 gsm uncoated; 106 to 350 gsm coated); XLS sheet: 52-220 gsm uncoated / 106 to 220 gsm coated; limit XLS in Tray 5 (Bypass) to 5 or fewer sheets
<b>Envelope Capacity</b>	30 to 50 envelopes
<b>Envelope Sizes</b>	#10 Commercial, Monarch (including custom size), C4, C5 (Available as Tray 5 (Bypass)). Paper Size Default within tools. Run flap open at the trail edge. Custom sizes: 7.5 x 6.7 in. to 9.45 x 6.81 in. / 190 x 170 mm to 240 x 173 mm Digital or Laser Printer Grade recommended.
<b>Envelope Weights</b>	64 to 150 gsm

### TRAYS 1 TO 4

<b>Capacity<sup>3</sup></b>	<p>Tray 1: 540 sheets</p> <p>Tray 2: 540 sheets</p> <p>Tray 3: 890 sheets</p> <p>Tray 4: 1,280 sheets</p>
<b>Total Capacity<sup>3</sup></b>	3,500 sheets (including Tray 5: 250 sheets)
<b>Sizes</b>	<p>Tray 1: 5.5 x 8.5 in. to 12 x 18 in. / A5 to SRA3</p> <p>Tray 2: 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3</p> <p>Tray 3: 7.25 x 10.5 in. to 8.5 x 11 in. / B5, A4</p>

Xerox® PrimeLink® C9265 / C9275 / C9281 Printer

	Tray 4: 7.25 x 10.5 in. to 8.5 x 11 in. / B5, A4
<b>Weights</b>	Trays 1 and 2: 16 lb. bond to 111 lb. cover / 60 to 300 gsm (52 to 300 gsm uncoated; 106 to 300 gsm coated) Trays 3 and 4: 16 lb. bond to 111 lb. cover / 60 to 300 gsm (52 to 300 gsm uncoated; 106 to 300 gsm coated)

**(OPTIONAL) HIGH CAPACITY FEEDER (HCF)\***

<b>Capacity<sup>3</sup></b>	2,000 sheets
<b>Sizes</b>	7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4)
<b>Weights</b>	16 lb. bond to 80 lb. cover / 60 to 220 gsm (uncoated and coated)

**(OPTIONAL) OVERSIZED HIGH CAPACITY FEEDER (OHCF): ONE- OR TWO-TRAY OPTIONS**

<b>Capacity<sup>3</sup></b>	One-Tray OHCF: 2,000 sheets with Storage Cabinet Two-Tray OHCF: 4,000 sheets Tray 5 (Bypass): Up to 250 sheets; XLS capacity varies by media; limit XLS in Tray 5 (Bypass) to 5 or fewer sheets
<b>Sizes</b>	One-Tray OHCF: Tray 6: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in. / 330 x 488 mm Two-Tray OHCF: Tray 6 and 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in. / 330 x 488 mm Custom sizes via Tray 5 (Bypass): 4 x 6 in. to 13 x 51 in. (XLS) / 102 x 152 mm to 330 x 1,300 mm (XLS)
<b>Weights</b>	One-Tray OHCF: 52 to 350 gsm (52 to 350 gsm uncoated; 106 to 350 gsm coated) Two-Tray OHCF: 52 to 400 gsm (52 to 400 gsm uncoated; 106 to 400 gsm coated)

**TOTAL CAPACITY**

<b>Standard Capacity</b>	3,500 sheets (includes Tray 5 and Trays 1–4)
<b>Maximum Capacity</b>	7,500 sheets (includes Tray 5, Trays 1–4 and Two-Tray Oversized High Capacity Feeder)
<b>Two-Sided</b>	All Trays (1–4) up to 300 gsm auto duplex Trays 5–7 up to 350 gsm auto duplex Note: Extra-Long Sheets (XLS) / Banner media can only run simplex, up to 220 gsm

**FINISHING**

**OFFSET CATCH TRAY**

<b>Capacity<sup>3</sup></b>	Up to 500 sheets stacking
-----------------------------	---------------------------

**(OPTIONAL) BUSINESS READY FINISHER 2.0**

<b>Capacity<sup>3</sup></b>	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) 11 x 17 in., 8.5 x 14 in. / A3 or 200 sets (single-position staple) 8.5 x 11 in. / A4
<b>Sizes</b>	4 x 6 in. to 13 x 19.2 in. / A5 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling 5.5 x 8.5 in. / A5 output to Top Tray; punch and offset
<b>Weights</b>	16 lb. bond to 129 lb. cover / 60 to 400 gsm (coated and uncoated) Top Tray 16 lb. bond to 94 lb. cover / 60 to 256 gsm (coated and uncoated) Stacker Tray
<b>Stapling</b>	Single and multi-position stapling Auto stapling (50 sheets maximum)–24 lb. / 90 gsm Letter, Legal, Tabloid, A3, A4, A4 Cover, Executive, 8 x 10 in., 8.5 x 13 in., 11 x 15 in., 215 x 315 mm, B4 and B5 sizes supported
<b>Hole Punch</b> North America: Europe:	2–3 Hole Punch 2–4 Hole Punch 4-Hole Swedish Punch (Optional)

<b>(OPTIONAL) BUSINESS READY BOOKLET MAKER FINISHER 2.0</b>	
<b>Capacity<sup>3</sup></b>	Offsetting Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled Stacking XLS output quantity is limited Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 (single-position stapling, dual or 4-position stapling) or 100 stapled sets of 11 x 17 in. / A3 / SRA3
<b>Sizes</b>	4 x 6 in. to 12 x 18 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling 5.5 x 8.5 in. / A5 output to Top Tray; punch and offset
<b>Weights</b>	Top Tray and Stacker Tray: 16 lb. bond to 129 lb. cover / 52 to 400 gsm (coated and uncoated) Booklet Tray: 16 lb. bond to 110 lb. cover / 52 to 256 gsm (coated and uncoated) Stacker
<b>Stapling</b>	Single and multi-position stapling Auto stapling (50 sheets maximum)—24 lb. / 90 gsm Letter, Legal, Tabloid, A3, A4, A4 Cover, Executive, 8 x 10 in., 8.5 x 13 in., 11 x 15 in., 215 x 315 mm, B4 and B5 sizes supported
<b>Hole Punch</b> North America: Europe:	2–3 Hole Punch 2–4 Hole Punch 4-Hole Swedish Punch (Optional)
<b>Booklet Maker</b>	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated), Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, B4, B5, Executive, 8.5 x 13 in., 11 x 15 in., 215 x 315 mm, 12 x 18 in., 13 x 19.2 in. and SRA3 supported
<b>(OPTIONAL) C/Z FOLDER UNIT FOR BUSINESS READY FINISHER 2.0</b>	
<b>Types</b>	C-Fold, Z-Fold and Z-Half-Fold
<b>Capacity<sup>3</sup></b>	40 sheets
<b>Sizes</b>	C-Fold and Z-Fold: Letter—8.5 x 11 in. / A4 SEF only Z-Half-Fold: Tabloid—11 x 17 in. / A3 only
<b>Weights</b>	16 to 24 lb. bond / 60 to 90 gsm
<b>Output Tray</b>	Envelope Tray: C-Fold, Z-Fold and Tri-Fold Stacker Tray or Top Tray: Z Half-fold
<b>(OPTIONAL) PRODUCTION READY FINISHER: REQUIRES INTERFACE DECURLER MODULE</b>	
<b>Capacity</b>	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Stacker Tray: 3,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
<b>Sizes</b>	4 x 6 in. to 13 x 26 in. / A6 to SRA3
<b>Weights</b>	16 lb. bond to 129 lb. cover / 60 to 400 gsm (coated and uncoated) Top Tray 16 lb. bond to 94 lb. cover / 60 to 256 gsm (coated and uncoated) Stacker Tray
<b>Multi-Position Stapling</b>	Up to 100 sheets of 20 lb. bond / 80 gsm
<b>Hole Punch</b> North America: Europe:	2–3 Hole Punch 2–4 Hole Punch 4-Hole Swedish Punch (Optional)
<b>Inserter</b> Capacity: Sizes: Weights:	200 sheets of 126 gsm 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 11 x 17 in., / A3, A4, B4, B5 18 lb. bond to 130 lb. cover / 64 to 350 gsm
<b>Decurling</b>	Active decurling included in base unit; optional decurling. included with Interface Decurler Module and Standard Finisher Bi-Directional with Auto and Manual settings

<b>(OPTIONAL) PRODUCTION READY FINISHER WITH BOOKLET MAKER: REQUIRES INTERFACE DECURLER MODULE</b>	
<b>Capacity</b>	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Stacker Tray: 2,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
<b>Sizes</b>	4 x 6 in. to 13 x 19.2 in. / A6 to SRA3
<b>Weights</b>	18 lb. bond to 129 lb. cover / 60 to 400 gsm (coated and uncoated) Top Tray 18 lb. bond to 94 lb. cover / 60 to 256 gsm (coated and uncoated) Stacker Tray 18 lb. bond to 94 lb. cover / 60 to 256 gsm (coated and uncoated) Booklet Maker
<b>Multi-Position Stapling</b>	Up to 100 sheets of 20 lb. bond / 80 gsm
<b>Hole Punch</b> North America: Europe:	2–3 Hole Punch (Optional) 2–4 Hole Punch (Optional) 4-Hole Swedish Punch (Optional)
<b>Inserters</b> Capacity: Sizes: Weights:	200 sheets of 128 gsm 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 11 x 17 in., / A3, A4, B4, B5 18 lb. bond to 80 lb. cover / 64 to 220 gsm
<b>Decurling</b>	Included with Interface Module and Standard Finisher Bi-Directional with Auto and Manual settings
<b>Booklet Making Capacity</b>	Saddle-stitch 2 to 30 sheets of 90 gsm (uncoated) or up to 15 sheets of 120 gsm (coated); Bi-Fold up to 5 sheets 8.5 x 11 in., 8.5 x 13 in., 8.5 x 14 in., 9 x 11 in., 11 x 15 in., 11 x 17 in., 12 x 18 in. / A4, B4, A3, SRA3
<b>(OPTIONAL) XEROX® CREASE AND TWO-SIDED TRIMMER</b>	
<b>Sizes</b>	Crease: 7.25 x 10.5 in. to 13 x 19.2 in. / A4 to SRA3, custom sizes 7.2 x 8.3 in. to 13 x 19.2 in. / 182 x 210 mm to 330 x 488 mm Trim: 8 x 10 in. to 13 x 19.2 in. / A4 to SRA3, custom sizes 7.2 x 10 in. to 13 x 19 in. / 182 x 257 mm to 330 x 488 mm
<b>Weights</b>	Crease: 18 lb. bond to 129 lb. cover / 60 to 350 gsm Trim: 18 lb. bond to 129 lb. cover / 60 to 350 gsm
<b>(OPTIONAL) GBC® ADVANCEDPUNCH PRO™</b>	
<b>Punch Configuration</b> <b>Sizes</b>	A3, A4, A5, SRA3, 8.5 x 11 in., 8.5 x 14 in., 11 x 17 in. and 12 x 18 in.
<b>Weights</b>	20 lb. bond to 129 lb. cover / 75 to 350 gsm (uncoated); 28 lb. bond to 129 lb. cover / 106 to 350 gsm (coated)
<b>Dies</b>	Wide selection of slide-in / slide-out GBC® punch die sets available
Note: When printing XLS with the GBC® AdvancedPunch Pro™, the Xerox® Inserter must be included in the system configuration	
<b>(OPTIONAL) XEROX® SQUAREFOLD® TRIMMER MODULE</b>	
<b>Capacity</b>	Up to 30 sheets of 90 gsm
<b>Sizes</b>	Custom sizes: 8.5 x 11 in. to 12 x 18 in. / A4 to SRA3
<b>Weights</b>	18 lb. bond to 94 lb. cover / 64 to 220 gsm
<b>(OPTIONAL) CONVENIENCE STAPLER</b>	
<b>Capacity</b>	50 sheets (24 lb. / 90 gsm media)

<p><b>Extra-Long Sheets (XLS) Finishing Limitations</b></p> <p>XLS will output to OCT, Business Ready Top Tray and Production Ready Top Tray. However, stacking quality will be limited. XLS Extension Tray Kit is available for the Production Ready Finisher to improve the stacking of multiple sheets.</p> <p>When printing XLS with the GBC® AdvancedPunch Pro™, the Xerox® Inserter must be included in the system configuration.</p>	
<p><b>PRINT</b></p>	
<p><b>Print Resolution</b></p>	<p>Up to 2400 x 2400 dpi</p>
<p><b>Line Screens</b></p>	<p>600, 300, 200 and 150 Clustered Dot, 200 Rotated Line Screen (depending on the print server / controller selected)</p>
<p><b>Registration</b></p>	<ul style="list-style-type: none"> <li>• Advanced registration technology for tighter control</li> <li>• Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity (Available on all configurations as a Maintenance Tool; Alignment Adjustment)</li> <li>• Up to 0.5 mm; variation will occur based on paper size, tray and environmental conditions</li> </ul>
<p><b>First-Print-Out Time</b></p>	<p>Varies with each ppm model: in seconds</p> <p>C9265: Color 7.1 / BW 5.7</p> <p>C9275: Color 6.2 / BW 5.1</p> <p>C9281: Color 6.7 / BW 5.5</p>
<p><b>Print Drivers</b></p>	<p>Job Identification, Bi-Directional Status, Job Monitoring, Xerox® Global Print Driver®, Application Defaults, Xerox® Pull Print Driver, Microsoft® Universal Print</p> <p>For information about supported print drivers, please visit our Drivers and Downloads page and specify your device at <a href="http://support.xerox.com">support.xerox.com</a></p>
<p><b>PRINT SOLUTIONS</b></p>	
<p><b>Mobile Printing</b></p>	<p>Apple® AirPrint®, Mopria® Print, Mopria® Print Service Plug-in for Android, Xerox® @PrintByXerox App, Xerox® Workplace Suite Mobile Printing Solution and Xerox® Workplace Cloud Mobile Printing Solution</p> <p>Learn more at <a href="http://xerox.com/MobileSolutions">xerox.com/MobileSolutions</a></p>
<p><b>COPY</b></p>	
<p><b>First-Copy-Out Time</b></p> <p>From the Platen:</p> <p>From the DADF:</p>	<p>As fast as / warmed-up state: C9265: Color 5.4 / BW 4.1 C9275: Color 5.4 / BW 4.1 C9281: Color 5.4 / BW 4.1</p> <p>As fast as / warmed-up state: C9265: Color 9.1 / BW 6.9 C9275: Color 7.4 / BW 5.9 C9281: Color 7.3 / BW 5.8</p>
<p><b>Warm-up Time</b></p>	<p>90 seconds (from cold powered down to Ready Copy)</p>
<p><b>Digital Imaging</b></p>	<p>Auto color</p> <p>Auto rotation</p> <p>Image shift</p> <p>Edge erase</p> <p>Auto centering</p> <p>Original type selection (photo and text, photo, text and map)</p> <p>Lighter / Darker</p> <p>Background suppression</p> <p>Auto and manual contrast</p> <p>Sharpness</p> <p>Color balance, color shift and saturation</p>
<p><b>Reduce / Enlarge</b></p>	<p>Variable zoom from 25% to 400% in 1% increments</p> <p>Anamorphic zoom</p> <p>Six user-programmable percentages</p>
<p><b>Special Features</b></p>	<p><b>Copy Features:</b></p> <p>Auto color</p> <p>Auto paper select</p> <p>Reduce and enlarge 25–400%</p> <p>Pages per side</p> <p>Lighter / Darker</p>

	<p><b>Finishing:</b>                  Staple                  Hole punch                  Folding                  Copy output (Collate / Uncollate)                  Output destination                  Face up / face down</p> <p><b>Originals types : Photo and text, photo, text and map</b>                  Mixed                  Orientation                  Sharpness                  Saturation                  Image enhancement                  Color effects                  Color balance                  Color shift                  Gloss level</p> <p><b>Book copying:</b>                  Two-sided book copying                  Edge erase                  Image shift                  Mirror image                  Negative image                  Image rotation                  Booklet creation                  Covers                  Posters                  Repeat image                  Preset repeat image                  Annotation                  Watermark                  Joint job</p> <p><b>Other:</b>                  Auto tray switching                  Interrupt                  Automatic job recovery</p>
<b>SCAN</b>	
<b>Concurrency</b>	Scan while printing or while it is transferring, scan to network or fax jobs
<b>Scan Features</b>	Mixed-size originals Edge erase Reduction / Enlargement Fit to size Scan build job Compression quality / File size control Original type (photo and text, photo and text) Auto background and shadow suppression Job flow sheets Scan to USB Preview scan job
<b>INPUT SPEED</b>	
	Up to 270 images per minute Duplex
<b>Resolution</b>	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi
<b>Maximum Scan Area</b>	Originals up to 11 x 17 in. / A3
<b>File Formats</b>	PDF image only

	Searchable PDF (optional) PDF (A-1) TIFF V6
<b>Scan Features</b>	Mixed-size originals Edge erase Reduction / Enlarge Fit to size Quality file size Original type Background Scan to USB Scan to folder Preview scan job Shadow suppression Book scanning File naming PDF security Skew correction
<b>Supported Scan Destinations</b>	Scan to Email, Scan to Folder, Scan to PC, Scan to Mailbox (private and public), Scan to USB, FTP and Scan to SMB
<b>Scan to Email Features</b>	Color scanning, auto color, grayscale, black and white Direct document email from the device Manual or directory Exchange / Notes / LDAP address searching Signing and encryption Email over SSL Preview scan job
<b>Authentication</b>	SMTP authentication, POP before SMTP, system credentials and single sign-on (LDAP, SMB and Kerberos authentication) Scanning security–TLS
<b>FAX (OPTIONAL): ONE- OR THREE-LINE FAX OPTIONS</b>	
<b>Maximum Scan Area</b>	11 x 17 in. / SEF
<b>Fax Features</b>	VoIP iFax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination
<b>DEVICE MANAGEMENT</b>	
<b>XEROX® EMBEDDED WEB SERVER–INTEGRATED WEB PAGES PROVIDED BY THE DEVICE</b>	
<b>Remote UI</b>	Providing remote view and operation of the PrimeLink® Printer Remote operations provide helpful collaborations and training administrators can enable / disable features and user restrictions
<b>Device Status</b>	Web server embedded in Network Controller: <ul style="list-style-type: none"> <li>• Tray status / contents</li> <li>• Consumables status</li> <li>• Alerts</li> </ul>
<b>Job Submission</b>	Print ready files: PDF, XPS®, PCL® 6, HP-GL2 (direct submission), TIFF, JPEG and Adobe® PostScript® 3™ (highly recommended option) Output feature selection (two-sided, output color, collate, orientation, staple, hole punch, folding and output destination) Delivery options (Immediate, sample set, delay and secure, save job or reprint)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device

# Xerox® PrimeLink® C9265 / C9275 / C9281 Printer

<b>Browsers</b>	Internet Explorer Safari Mozilla Firefox Opera Chrome
<b>Support</b>	Install print / scan drivers and online support available via the web page
<b>Languages Supported</b>	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian and Polish

## REMOTE SERVICES

<b>Automated Meter Readings (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage; eliminates the need for time-consuming, end-user involvement, and ensures that meter reads are submitted to Xerox on time
<b>Automatic Supplies Replenishment (ASR)</b>	Automatically orders supplies for Xerox® devices based on actual usage, eliminating the need to manually manage supplies inventory

## SECURITY

<b>Features</b>	<ul style="list-style-type: none"> <li>Access controls</li> <li>AES 256-bit encryption</li> <li>Audit log</li> <li>Certificate Revocation List (CRL) / Status Protocol (OCSP)</li> <li>Detection of external program Falsification (XCP Plug-in)</li> <li>Domain filtering</li> <li>FIPS 140-3</li> <li>Firmware verification</li> <li>Immediate disk overwrite</li> <li>IP address filtering</li> <li>IPsec</li> <li>Network authentication</li> <li>Pre-installed self-signed certificates</li> <li>Role-based permissions</li> <li>Secure print</li> <li>Security certificate management</li> <li>Smart card enablement (CAC / PIV / .NET)</li> <li>SNMPv3</li> <li>TLS / SSL (TLS 1.0, 1.1, 1.2)</li> <li>SIPRnet</li> </ul>
-----------------	--

## PRINT SERVER

### INTEGRATED COLOR SERVER FOR THE XEROX® PRIMELINK® C9200 SERIES PRINTER

<b>Processor</b>	1.6 GHz dual-core
<b>Memory</b>	4 GB RAM
<b>System Disk</b>	320 GB Hard Disk Drive
<b>Display</b>	10 in. color touchscreen flat-panel display
<b>Device Operating System</b>	Linux®
<b>PDLs Page Description Languages</b>	PDF, XPS®, PCL® 6, HP-GL2 (direct submission), TIFF, JPEG and Adobe® PostScript® 3™ (highly recommended option)
<b>Print Drivers Supported</b>	Please refer to <a href="http://xerox.com/support">xerox.com/support</a> for specifics. As new operating system versions are added, support is also added for the Xerox® PrimeLink® C9200 Series Printer. Also, note that there is more than one print driver based on the configuration purchased (e.g., digital front ends and Xerox® Global Print Driver)
<b>Print Features</b>	Automatic two-sided Secure print

	<p>Delay print                  Sample set                  Booklet creation                  Cover selection                  Paper selection by attribute                  N-up                  Watermarks                  Banner sheets                  Output tray selection                  Standard USB                  Paper catalog (up to 400 entries)</p>
<b>Connectivity</b>	Ethernet interface (10 MBTX / sec, 100 MBTX / sec, 1000 MBTX / sec)
<b>ADDITIONAL PRINT SERVER OPTIONS</b>	
<b>XEROX® EX-i C9200 SERIES PRINT SERVER POWERED BY FIERY® (FS600 PLATFORM)</b>	
<b>Processor</b>	Intel® G7400E Processor
<b>Memory</b>	8 GB
<b>Hard Drive</b>	500 GB HDD
<b>Server Operating System</b>	Linux®
<b>File Formats</b>	Adobe® PostScript® Level 1, 2, 3; Adobe® PDF; PDF / X-1a, 3, 4; Enhanced PCL® 6 / PCL 5; Microsoft® Native Formats (doc / x, xls / x, pub / x, ppt / x) via the Fiery® driver or Fiery® Hot Folders; EPS and TIFF
<b>Features</b>	<ul style="list-style-type: none"> <li>• Productivity starts with a fast RIP; the Integrated Fiery® Color Server enables you to print large and/or complex Microsoft® Office documents, PowerPoint® files and color-critical PDFs accurately and quickly</li> <li>• Simplify and streamline your workflow; automate job submission of repetitive job types to achieve productive, error-free workflows with Hot Folders and Virtual Printers</li> <li>• Take advantage of commonly used Fiery® presets to save time when submitting jobs; with Fiery® server technology, even novice users can perform complex jobs using the preset drivers configured for the task</li> <li>• Get the color right; produce precise, exact color from all applications, platforms and formats with Fiery® color management tools including Fiery® TrueBrand and Fiery® Spot-On™</li> <li>• Offer personalized printing with Fiery® FreeForm™ Create; quickly personalize existing files by adding various elements such as text, images or barcodes</li> <li>• The Fiery® Essential Driver increases productivity with a simple, intuitive way to print common office documents in just a few clicks; or, use the Xerox® Global Print Driver</li> <li>• Easily print files with mixed paper sizes and types</li> <li>• Command WorkStation</li> <li>• Standard Fiery® JDF connectivity boosts digital workflow efficiency by integrating with existing prepress, web-to-print, or MIS / ERP systems to eliminate manual touchpoints, errors and resource waste</li> <li>• Secure erase</li> <li>• Paper catalog</li> <li>• Fiery® Compose</li> <li>• Fiery® Remote Scan</li> </ul>
<b>Connectivity</b>	<p><b>Single and Dual TCP / IP connectivity for integration with Xerox Extensible Interface Platform® (EIP):</b></p> <ul style="list-style-type: none"> <li>• TCP / IP, Bonjour support, SNMP, Port 9100, IPP 2.0, FTP, SMB, WSD, point and print, print via email (PS / PDF), IPv6 support, LDAP authentication</li> <li>• Native support for Universal Print by Microsoft®</li> <li>• Compliant with Mopria® industry standard</li> </ul>
<b>Additional Options</b>	<p><b>Packages / Suites / Kits:</b></p> <ul style="list-style-type: none"> <li>• Fiery® Color Profiler Suite with ES-3000</li> <li>• Fiery® Automation Package</li> <li>• Fiery® ColorRight Package</li> <li>• Fiery® JobExpert and PDF Processing Kit</li> </ul>

Xerox® PrimeLink® C9265 / C9275 / C9281 Printer

	<b>Features (optional–available separately):</b> <ul style="list-style-type: none"> <li>• Fiery® Impose</li> <li>• Fiery® JobMaster</li> </ul>
	For more information, go to <a href="http://xerox.com">xerox.com</a>
<b>XEROX® EX C9200 SERIES PRINT SERVER POWERED BY FIERY® (FS600 PLATFORM)</b>	
<b>Processor</b>	Intel® Core™ i3-12100 Processor
<b>Memory</b>	8 GB
<b>Hard Drive</b>	1 TB HDD
<b>Server Operating System</b>	Microsoft® Windows 10 IoT Enterprise 2021 LTSC
<b>Print Languages (PDL)</b>	Adobe® PostScript® Level 3, Adobe® PDF, EPS, PCL® 6C, PCL 5, TIFF, JPG, Microsoft® native formats via Fiery® Hot Folders and Adobe® PDF Print Engine (APPE)
<b>Features</b>	<ul style="list-style-type: none"> <li>• Job-based calibration integration <ul style="list-style-type: none"> <li>– Fiery® Spot-On finds the best match of PANTONE®, PANTONE® Series, RGB, CMYK, L*a*b* and Spot Colors– color modes for professional proofing and enhanced production color requirements–maximum print density</li> </ul> </li> <li>• Easily handle heavy workloads and provide faster turnaround times with the most powerful DFE for the Xerox® PrimeLink® C9200 Series Printer; Fiery® Edge technology gets the most precise and stunning results from PrimeLink® printers; it achieves the best possible gamut for both spot and process color reproduction</li> <li>• The Fiery® Command WorkStation increases your production and reduces errors and waste by centralizing job management via its intuitive user interface; simplify your labor-intensive document composition and imposition tasks even more by using Fiery® Impose and Compose’s intuitive interface</li> <li>• Print high-quality photos and images</li> <li>• Fiery® FreeForm™ Create for quick personalization; provides variable text, images and barcode elements; supporting VDP formats like PDF / VT-1 and 2, PPML, VPS and Xerox® VIPP®</li> <li>• Easily print files with mixed paper sizes and types</li> <li>• Paper catalog</li> <li>• Fiery® JDF</li> <li>• Fiery® JobExpert analyzes files and dynamically chooses the optimal print settings</li> <li>• Fiery® TrueBrand ensures accurate spot colors for all job types, even Microsoft® Office documents</li> </ul>
<b>Connectivity</b>	Single and Dual TCP / IP connectivity for Integration with Xerox Extensible Interface Platform® (EIP): <ul style="list-style-type: none"> <li>• TCP / IP, Bonjour support, SNMP, Port 9100, IPP 2.0, FTP, SMB, WSD, point and print, print via email (PS / PDF), IPv6 support and LDAP authentication</li> <li>• Log in with single sign-on (SSO), native support for Universal Print by Microsoft®</li> <li>• Compliant with Mopria® industry standard</li> </ul>
<b>Additional Options</b>	<b>Packages / Suites / Kits:</b> <ul style="list-style-type: none"> <li>• Fiery® Color Profiler Suite With ES-3000</li> <li>• Fiery® Graphic Arts Pro Package</li> <li>• Hard Drive Security Kit</li> <li>• Additional Drives Kit</li> <li>• Fiery® NX Station GL</li> </ul> <b>Features (optional–available separately):</b> <ul style="list-style-type: none"> <li>• Fiery® JobMaster</li> </ul>
	For more information, go to <a href="http://xerox.com">xerox.com</a>

# Xerox® PrimeLink® C9265 / C9275 / C9281 Printer

SUPPLIES		YIELD	PART NUMBER
<b>Toner Cartridges</b> (Metered)	Black	34,500 pages <sup>4</sup>	006R04847
	Cyan	37,500 pages <sup>4</sup>	006R04848
	Magenta	37,500 pages <sup>4</sup>	006R04849
	Yellow	37,500 pages <sup>4</sup>	006R04850
<b>Toner Cartridges (Sold)</b>	Black	34,500 pages <sup>4</sup>	006R04851 (North America, Western Europe) 006R04855 (All other regions)
	Cyan	37,500 pages <sup>4</sup>	006R04852 (North America, Western Europe) 006R04856 (All other regions)
	Magenta	37,500 pages <sup>4</sup>	006R04853 (North America, Western Europe) 006R04857 (All other regions)
	Yellow	37,500 pages <sup>4</sup>	006R04854 (North America, Western Europe) 006R04858 (All other regions)
<b>Xerox CRU</b> (Drum Cartridge)	1 Common Cartridge for CMY and K	122,500 pages <sup>4</sup>	013R00703
<b>Waste Toner Container</b>	1 Container	50,000 pages <sup>4</sup>	008R08159

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>4</sup> Approximate pages. Declared Yield based on 5-page job size, 30% color and 70% black-and-white ratio, using letter / A4 media. Yield will vary based on media size, image area coverage, job run length, media orientation and usage patterns. These yields are based on 5% coverage area.

Return spent imaging supplies through the Xerox® Green World Alliance® collection / reuse / recycling program.  
For more information, visit [xerox.com/About-Xerox/Recycling](https://www.xerox.com/About-Xerox/Recycling).

Learn more at [xerox.com/PrimeLink](https://www.xerox.com/PrimeLink).