

# Xerox® AltaLink® Multifunction Printers



B8245/B8255/B8270



AltaLink® B8200 Series Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to [www.ConnectKey.com](http://www.ConnectKey.com).

System Specification	AltaLink® B8245	AltaLink® B8255	AltaLink® B8270
<b>Speed<sup>1</sup></b>	Up to 45 ppm	Up to 55 ppm	Up to 72 ppm
<b>Monthly Duty Cycle<sup>2</sup></b>	Up to 200,000 pages	Up to 250,000 pages	Up to 300,000 pages
<b>Hard Drive/ Processor/Memory</b>	Minimum 256 GB NVMe SSD/ <b>Optional:</b> 1 TB NVMe SSD HDD/Intel® Atom™ Quad Core 1.91 GHz/4 GB system memory		
<b>Connectivity</b>	Ethernet 10/100/1000 Base-T, High-speed USB 2.0 direct print, NFC; <b>Optional:</b> Wi-Fi®/Wi-Fi Direct® with Xerox® Dual Band WiFi® and Bluetooth® Kit (Bluetooth for iBeacon™)		
<b>Controller Features</b>	Configuration Cloning, Configuration Watchdog, Fleet Orchestrator, Remote Control Panel, Unified Address Book, Security Dashboard, Adaptive Learning		
<b>Copy and Print</b>			
<b>Copy and Print Resolution</b>	<b>Copy:</b> Up to 600 x 600 dpi; <b>Print:</b> Up to 1200 x 2400 dpi		
<b>First-Print-Out Time (as fast as)</b>	3.7 seconds	3.2 seconds	3.0 seconds
<b>First-Copy-Out Time (as fast as) (from platen/warmed-up state)</b>	4.1 seconds	3.6 seconds	3.0 seconds
<b>Page Description Language</b>	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6		
<b>Print Features</b>	Application Defaults, Bi-directional Real-time Status, Booklet Layout, Encrypted Secure Print, Hold All Jobs, Job Identification, Job Monitoring, Long Sheet (Banner) Printing, Print Around, Print from Cloud Repositories (Dropbox, OneDrive, and Google Drive), Print from USB, Print on Alternate Paper, Scaling, Store and Recall Driver Settings, Two-sided Printing (as default), Xerox® Earth Smart Driver Settings, Microsoft Universal Print/IPP with Print Support Application; <b>Optional:</b> Print from and Scan to Xerox® DocuShare® Go content management		
<b>Mobile- and Cloud-Ready</b>			
<b>Mobile Connectivity</b>	Near Field Communication (NFC); <b>Optional:</b> Wi-Fi Direct®, Wi-Fi® (802.11 b/g/n/ac), AirPrint (iOS) including iBeacon™ (Bluetooth®)		
<b>Mobile Printing</b>	Mopria® Print, Apple™ AirPrint™, Xerox® Print Service (Android), @PrintByXerox App; <b>Optional:</b> Xerox® Workplace Mobile App (iOS/Android) AirPrint™ (iOS) including iBeacon™ (Bluetooth® for AirPrint Discovery)		
<b>Mobile Scanning</b>	Mopria® Scan, Apple™ AirPrint™, <b>Xerox Easy Assist App;</b> <b>Optional:</b> Xerox® Workplace Mobile App (iOS/Android)		
<b>Mobile Apps and Xerox App Gallery</b>	Automate everyday processes with optional apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate. Visit <a href="http://xerox.com/WorkplaceApps">xerox.com/WorkplaceApps</a> to find apps by industry or workflow. Software and services: Xerox® DocuShare® ( <a href="http://xerox.com/ecm">xerox.com/ecm</a> ), XMPie® ( <a href="http://xerox.com/XMPie">xerox.com/XMPie</a> ), Xerox® Workplace Solutions ( <a href="http://xerox.com/WorkplaceSolutions">xerox.com/WorkplaceSolutions</a> )		
<b>Xerox® Workflow Central Platform</b>	<b>Optional:</b> One-platform consistency for seamless productivity across computers, mobile devices and printers. With Workflow Central's ever-expanding suite of cloud-based workflows, you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable and shareable text, translate to/from over 40 different languages, and automatically redact Personal Identifiable Information using set words or phrases ( <a href="http://xerox.com/en-us/office/software-solutions/workflow-central">xerox.com/en-us/office/software-solutions/workflow-central</a> )		
<b>Xerox® Workplace Suite and Xerox® Workplace Cloud</b>	<b>Optional:</b> Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their printer fleet while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud-based version (Workplace Cloud) of this solution ( <a href="http://xerox.com/en-us/office/print-management-solutions">xerox.com/en-us/office/print-management-solutions</a> )		
<b>Cloud Identity Provider (IdP) Integration</b>	Use your desktop, laptop, or mobile login credentials to log in to your AltaLink® MFPs with direct connections to popular cloud identity providers, Okta, Ping Identity, and Microsoft® Azure		

# Xerox® AltaLink® B8245/B8255/B8270 Multifunction Printer

Scan	
<b>Standard Features</b>	<b>Destinations:</b> Scan to USB/PC via USB port/Email/Network (SMB, sFTP, FTP, HTTP, HTTPS destinations), Scan to Print; <b>File Formats:</b> PDF, PDF/A, JPEG, TIFF; <b>Convenience Features:</b> 1-Touch Apps, Imaging Security with AltaLink's proprietary marking and infrared detection technology (only Detect Mark feature is supported on monochrome MFPs), Optical Character Recognition (OCR), Password-protected PDF, Scan Preview, Scan to Folder, Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Touchless Workflow Accelerators, TWAIN Support, Unified Address Book
<b>Optional Features</b>	Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive). Xerox® Scanning App for DocuShare®, other solutions available through various Xerox® Business Innovation Partners at <a href="http://xerox.com/Software-Solutions">xerox.com/Software-Solutions</a> , Print from and Scan to Xerox® DocuShare® Go content management
Fax	
<b>Standard Features</b>	Network Server Fax Enablement, Fax Build Job
<b>Optional Features</b>	Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email or SMB Share)
Security	
<b>Standard Features</b>	802.1x, Access Control, Audit Log, Automated threat response through Trellix DXL*/Cisco® pxGrid integration, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, Configuration Watchdog, Security Dashboard, Encrypted Secure Print, Encrypted Storage Drive (AES 256-bit), FIPS 140-3, Firmware Verification, HTTPS, Imaging Security (copy, print, scan, email) with AltaLink's proprietary infrared detection technology (only Detect Mark feature is supported on monochrome MFPs), IPsec, Job Level Encryption via HTTPS and Drivers, Local Authentication (Internal Database), Microsoft Universal Print/IPP with Print Support Application (Secure Print and Secure Release), Network Authentication, Port/IP/Domain Filtering, Security Certificates utilizing ECDSA, Security Dashboard, Security Templates, Serverless Card Authentication, sFTP and Encrypted Email, SHA-256 Hash Message Authentication, SIEM integration (Splunk, LogRhythm, Trellix ESM*), Signed Email, SNMPv3, TLS 1.1/1.2/1.3, Trusted Platform Module (2.0), Trellix Embedded Control Allowlisting*, Trellix ePolicy Orchestrator®, Trusted Boot, User Access and Internal Firewall, User Permissions, Common Criteria Certification (ISO 15408) will be made available in a future firmware release
<b>Optional Features</b>	Trellix Integrity Control*, Smart Card Enablement Kit (CAC/PIV/.NET) <sup>3</sup> , Xerox® Integrated RFID Card Reader, Encrypted Storage Drive (AES 256-bit, FIPS 140-3), WPA2™ and WPA3™ with Xerox® Dual Band WiFi® and Bluetooth® Kit (Bluetooth for iBeacon™), Xerox® Workplace Cloud/Suite Print Management and Content Security, learn more at <a href="http://xerox.com/WorkplaceSolutions">xerox.com/WorkplaceSolutions</a>
Print Management	
<b>Standard Features</b>	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement
<b>Optional Features</b>	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Services; learn more at <a href="http://xerox.com/PrintManagement">xerox.com/PrintManagement</a>
Embedded Pre-installed Artificial Intelligence Apps	
<b>Standard Features</b>	<p><b>Xerox® Note Converter App</b> utilizes the power of AI to make sense of handwriting, allowing you to quickly convert your notes into an MS Word document or a digital file. Easily edit, store and share your notes with everyone in that important meeting you just left, saving you precious time</p> <p><b>Xerox® Summarizer App</b> creates a summary of documents for viewing, printing, and emailing. Using artificial intelligence (AI), Xerox® Summarizer condenses dozens or even hundreds of pages by reducing the original scanned document to a percentage of the original or create a short and concise interpretation of the source text</p> <p><b>Xerox® Auto-Redaction App</b> takes advantage of cutting-edge AI technology in Google's Data Loss Prevention (DLP) software, which allows you to select preset Personally Identifiable Information (PII) or custom words and phrases and then automatically redact it</p> <p>See Xerox® AltaLink® 8200 Multifunction Printer Series Embedded AI Apps Frequently Asked Questions (FAQs) for more information</p>

# Xerox® AltaLink® B8245/B8255/B8270 Multifunction Printer

## Features and Accessories



### Single-pass Duplex Automatic Document Feeder (DADF)

saves time by simultaneously scanning both sides of a document with up to 270 impressions per minute (ipm).

### USER INTERFACE



**Intuitive Tablet-like 10.1-inch Color Touchscreen** is customizable and lets you perform tasks in just a few taps. Try it out at [www.xerox.com/SIM7](http://www.xerox.com/SIM7).

### PAPER INPUT<sup>4</sup>

**Two 520-sheet Adjustable Trays** (common with all configurations). Tray 1 handles media sizes up to 11.7 x 17 in./A3 and Tray 2 handles media sizes up to 12 x 18 in./SRA3.



**Envelope Kit** (optional — replaces Tray 1) provides feeding of up to 60 envelopes.



**High Capacity Tandem Tray Configuration** holds a total paper capacity of up to 3,140 sheets.

**Bypass Tray** handles up to 100 sheets; Custom sizes: 3.5 x 3.9 in. to 12.6 x 52 in./89 x 98 mm to 320 x 1,320 mm.



**High Capacity Feeder** (optional) holds 3,000 sheets of letter/A4 paper, increasing the maximum paper capacity to 6,140 sheets.



### INNOVATIVE TECHNOLOGIES



**Xerox® Integrated RFID Card Reader** (optional) adds card-based authentication with support for over 90 access cards.



**Near Field Communication (NFC) Tap-to-Pair** allows users to tap their mobile devices to the AltaLink® B8200 Series user panel and quickly connect with the MFP.



**Smart Proximity Sensor** detects when users are nearby. It conserves energy during inactive periods and automatically activates the device when a user approaches.

### PAPER OUTPUT/FINISHERS<sup>4</sup>



**Office Finisher** (optional) provides advanced finishing functions, optional crease/score, and saddle-stitch booklet, capable of 60-page booklets (2 to 15 sheets).



**Business Ready (BR) Finisher** (optional) gives you advanced finishing functions at a great value.



**C-Fold/Z-Fold Unit** (optional) adds C-fold, Z-fold, and Z-half-fold capability to the BR Finisher or BR Booklet Maker Finisher.



**BR Booklet Maker Finisher** (optional) creates 64-page saddle-stitched booklets (2 to 16 sheets).



**Dual Offset Catch Tray** (available when no finishers are installed; Single Offset Catch Tray with finishers).



**Integrated Office Finisher** (optional with B8245/B8255) provides 500-sheet stacking and 50-sheet, 2-position stapling.



**Convenience Stapler** (optional) staples up to 50 sheets of 20 lb./75 gsm media.

### LONG SHEET PRINTING

**Long Sheet Feed Kit** (optional) provides the ability to print up to 12.6 x 52 in./320 x 1,320 mm media.



# Xerox® AltaLink® B8245/B8255/B8270 Multifunction Printer

Device Specification			
<b>Control Panel Languages</b>	US English, Catalan, Czech, Danish, German, International English, International Spanish, International French, Croatian, Italian, Hungarian, Dutch, Norwegian, Polish, Brazilian Portuguese, Romanian, Finnish, Swedish, Turkish, Greek, Russian, Ukrainian, Arabic		
Accessories			
<b>Optional</b>	1TB NVMe SSD Booklet Maker for Office Finisher BR (Business Ready) Finisher (requires Horizontal Transport Kit) BR Booklet Maker Finisher (requires Horizontal Transport Kit) C-fold/Z-fold Unit for BR Finisher or BR Booklet Maker Finisher Convenience Stapler (includes Work Surface5) Envelope Tray (Replaces Tray 1) Foreign Device Interface (Also known as Auxiliary Access Device Interface) for third-party access control devices, such as coin machines and card readers High Capacity Feeder 3000 A4/Letter Hole Punch (2/3, 2/4, Swedish) Horizontal Transport Kit Integrated Office Finisher (Available with AltaLink® B8245, B8255) Long Sheet Feed Kit (banner printing) Trellix Integrity Control Enablement Kit* Multi-feed Detection Kit (AltaLink® B8270 only) Office Finisher Scan To Cloud Enablement Kit Smart Card Enablement Kit <sup>3</sup> Unicode Font Kit USB Keyboard/Shelf Kit Walk-up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi®/Wi-Fi Direct® with Xerox® Dual Band Wi-Fi® and Bluetooth® Kit (Bluetooth for iBeacon™) Xerox® Integrated RFID Card Reader Kit		
Electrical Requirements	AltaLink® B8245	AltaLink® B8255	AltaLink® B8270
<b>North America</b>	Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 15 A		Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 20 A
<b>Europe</b>	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A		Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A

# Xerox® AltaLink® B8245/B8255/B8270 Multifunction Printer

Device Specification (continued)			
Power Consumption	AltaLink® B8245	AltaLink® B8255	AltaLink® B8270
<b>Running (Average)</b>	115V: 717 watts 230V: 674 watts	115V: 806 watts 230V: 760 watts	115V: 929 watts 230V: 908 watts
<b>Standby Mode</b>	115V: 71 watts 230V: 71 watts	115V: 72 watts 230V: 70.3 watts	115V: 91.1 watts 230V: 79 watts
<b>Auto Off/Sleep Mode</b>	115V: 0.58 watts 230V: 0.60 watts (Default time to sleep mode = 0 minutes)	115V: 0.58 watts 230V: 0.61 watts (Default time to sleep mode = 0 minutes)	115V: 0.59 watts 230V: 0.61 watts (Default time to sleep mode = 0 minutes)
<b>Warm-up (from Off)</b>	As fast as 82 seconds		
<b>Recovery from Sleep</b>	As fast as 4.5 seconds		
Operating Environment			
<b>Required Temperature Range</b>	50 to 82° F/10 to 28° C		
<b>Required Relative Humidity</b>	15% to 85%		
<b>Sound Power Levels</b>	Operating: 63.7/64.2 dB(A) Standby: 40.0/40.0 dB(A)	Operating: 65.2/67.3 dB(A) Standby: 43.0/43.0 dB(A)	Operating: 70.4 dB(A) Standby: 43.0 dB(A)
Dimensions and Weight			
<b>Base Configuration</b>	Width: 24.4 in./620 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 286 lb./129.5 kg		Width: 24.4 in./620 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 319.2 lb./144.8 kg
<b>With Office Finisher (with Booklet Maker)</b>	Width: 47.5 in./1,207 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 370.3 lb./168 kg		Width: 47.5 in./1,207 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 406 lb./184.2 kg
<b>Base Configuration with Business Ready (BR) Finisher</b>	Width: 55 in./1,395 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 382.3 lb./173.4 kg		Width: 55 in./1,395 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 415.4 lb./188.4 kg
<b>Base Configuration with BR Booklet Maker Finisher</b>	Width: 59 in./1,496.3 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 419.7 lb./190.4 kg		Width: 59 in./1,496.3 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 453.3 lb./205.6 kg
<b>Base Configuration with BR Booklet Maker Finisher and C-fold/Z-fold Unit</b>	Width: 64.3 in./1,632 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 530.6 lb./240.7 kg		Width: 64.3 in./1,632 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 564.2 lb./255.9 kg
<b>Base Configuration with BR Booklet Maker Finisher, C-fold/Z-fold Unit, and High Capacity Feeder</b>	Width: 93 in./2,361 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 598.8 lb./271.6 kg		Width: 93 in./2,361 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 632.8 lb./287 kg
System Certifications/Regulatory Compliances			
<b>Certifications</b>	To view the latest list of certifications, go to <a href="http://xerox.com/OfficeCertifications">xerox.com/OfficeCertifications</a>		

# Xerox® AltaLink® B8245/B8255/B8270 Multifunction Printer

Paper Handling	AltaLink® B8245	AltaLink® B8255	AltaLink® B8270
<b>Single-pass Duplex Automatic Document Feeder (DADF)</b>			
<b>Capacity<sup>4</sup></b>	130 sheets		250 sheets
<b>Speed (Up to)</b>	82 ppm black-and-white (simplex) 161 ipm black-and-white (duplex)		135 ppm black-and-white (simplex) 270 ipm black-and-white (duplex)
<b>Paper Sizes Sensed</b>	3.4 x 4.9 in. to 11.7 x 17 in./85 x 125 mm to 297 x 432 mm		
<b>Weights</b>	16 lb. to 32 lb. bond/60 to 128 gsm		
<b>Bypass Tray (Standard)</b>			
<b>Capacity<sup>4</sup></b>	100 sheets		
<b>Sizes</b>	<b>Custom Sizes:</b> 3.5 x 3.9 in. to 12.6 x 52 in./89 x 98 mm to 320 x 1320 mm (SEF); <b>Optional:</b> Long Sheet Feed Kit (Banner Printing)		
<b>Weights</b>	16 lb. bond to 110 lb. cover/52 to 300 gsm, <b>Long sheets/banners</b> (>19 in./483 mm): 28lb Bond - 120lb Index/106 - 220 gsm		
<b>Media Types</b>	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies  <b>Long Sheets/Banners:</b> Card Stock Card Stock Reloaded Lightweight Card Stock Lightweight Card Stock Reloaded		
<b>Trays 1 and 2 (Standard)</b>			
<b>Capacity<sup>4</sup></b>	520 sheets each		
<b>Sizes</b>	<b>Tray 1:</b> Custom Sizes: 5.5 x 7.2 in. to 11.7 x 17 in./140 x 182 mm to 297 x 432 mm (SEF) <b>Tray 2:</b> Custom Sizes: 5.5 x 7.2 in. to 12 x 18 in./140 x 182 mm to SRA3 (SEF)		
<b>Weights</b>	16 lb. bond to 110 lb. cover/52 to 300 gsm		
<b>Media Types</b>	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies		

# Xerox® AltaLink® B8245/B8255/B8270 Multifunction Printer

Paper Handling (continued)	AltaLink® B8245	AltaLink® B8255	AltaLink® B8270
<b>High Capacity Tandem Tray (Available with all models)</b>			
<b>Capacity<sup>4</sup></b>	<b>Tray 3:</b> 867 sheets <b>Tray 4:</b> 1,133 sheets		
<b>Sizes</b>	8.5 x 11 in./A4, JIS B5, Executive (7.25 x 10.5 in) LEF		
<b>Weights</b>	16 lb. bond to 110 lb. cover/52 to 300 gsm		
<b>Media Types</b>	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted		
<b>Envelope Tray (Optional - Replaces Tray 1)</b>			
<b>Capacity<sup>4</sup></b>	Up to 60 envelopes		
<b>Sizes</b>	#10 Commercial (9.25 x 4.125 in.)/Monarch, DL, C5 Custom Sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./98 x 148 mm to 162 x 241 mm		
<b>Weights</b>	20 lb. to 24 lb. bond/75 to 90 gsm		
<b>High Capacity Feeder (HCF) (Optional with all models)</b>			
<b>Capacity<sup>4</sup></b>	3,000 sheets		
<b>Sizes</b>	Standard Sizes: 8.5 x 11 in. or 7.25 x 10.5 in./A4 or B5 LEF		
<b>Weights</b>	16 lb. bond to 110 lb. cover/52 to 300 gsm		
<b>Total Capacity</b>			
<b>Device Total Capacity<sup>4</sup></b>	High Capacity Tandem Tray Module: 3,140 sheets High Capacity Tandem Tray Module with High Capacity Feeder: 6,140 sheets		

# Xerox® AltaLink® B8245/B8255/B8270 Multifunction Printer

Finishing	AltaLink® B8245	AltaLink® B8255	AltaLink® B8270
<b>Output Trays (Standard) (Dual Offset Catch Trays not available with Integrated Office Finisher and limited to one with Office Finisher and BR Finishers)</b>			
<b>Stacking Tray Capacity<sup>4</sup></b>	Dual Offset Catch Tray: Up to 250 sheets each Left Side Face-up Tray: Up to 100 sheets		
<b>Integrated Office Finisher (Optional with AltaLink® B8245/B8255 only)</b>			
<b>Stacking Tray Capacity<sup>4</sup></b>	500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4 or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in./A3		
<b>Sizes</b>	3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 432 mm		
<b>Weights</b>	16 lb. bond to 110 lb. cover/52 to 300 gsm		
<b>Stapling</b>	Single/Dual Position Auto-Stapling: 50 sheets maximum: Letter/A4/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers)		
<b>Office Finisher (Optional)</b>			
<b>Stacking Tray Capacity<sup>4</sup></b>	2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4)		
<b>Stacking Tray Sizes</b>	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm		
<b>Weights</b>	16 lb. bond to 110 lb. cover/52 to 300 gsm		
<b>Multiposition Stapling</b>	50 sheets maximum: Letter/A4/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers)		
<b>Hole Punch (Optional)</b>	<b>North America:</b> 2/3-hole punch <b>Europe:</b> 2/4-hole punch <b>Optional:</b> 4-hole "Swedish" punch		
<b>Booklet Maker for Office Finisher (Score/Crease, Saddle-stitch Staple) (Optional)</b>			
<b>Top Tray Capacity<sup>4</sup></b>	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or less)		
<b>Sizes</b>	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Tabloid – 11 x 17 in./A3 SEF		
<b>Saddle-Stitch Stapling</b>	2-15 sheets/8-60 page booklet 16 lb. bond to 80 lb. cover/64 to 220 gsm		
<b>Score/Crease</b>	1-15 sheets/unstapled 16 lb. bond to 28 lb. bond/64 to 105 gsm		
<b>Business Ready (BR) Finisher (Optional) (Requires Horizontal Transport Kit)</b>			
<b>Capacity<sup>4</sup></b>	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4		
<b>Sizes</b>	3.9 x 5.8 in. to 12.6 x 19.2 in./100 x 148 mm x 320 x 488 mm for top tray 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 488 mm for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling		
<b>Weights</b>	16 lb. bond to 110 lb. cover/52 to 300 gsm		
<b>Stapling</b>	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4, and B5 sizes supported		
<b>Hole Punch</b>	<b>North America:</b> 2/3-hole punch <b>Europe:</b> 2/4-hole punch <b>Optional:</b> 4-hole "Swedish" punch		
<b>BR Booklet Maker Finisher (Optional) (Requires Horizontal Transport Kit)</b>			
<b>Capacity<sup>4</sup></b>	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3		
<b>Sizes</b>	3.9 x 5.8 in. to 12.6 x 19.2 in./100 x 148 mm x 320 x 488 mm for top tray 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 488 mm for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling		
<b>Weights</b>	16 lb. bond to 110 lb. cover/52 to 300 gsm		
<b>Stapling</b>	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4, and B5 sizes supported		
<b>Hole Punch</b>	<b>North America:</b> 2/3-hole punch <b>Europe:</b> 2/4-hole punch <b>Optional:</b> 4-hole "Swedish" punch		
<b>Booklet Maker</b>	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported		

# Xerox® AltaLink® B8245/B8255/B8270 Multifunction Printer

Finishing (continued)	AltaLink® B8245	AltaLink® B8255	AltaLink® B8270
<b>C-fold/Z-fold Unit (Optional with BR Finisher and BR Booklet Maker Finisher)</b>			
<b>Types</b>	C-fold, Z-fold, and Z-half-fold		
<b>Capacity<sup>4</sup></b>	40 sheets		
<b>Sizes</b>	C-fold and Z-fold: Letter – 8.5 x 11 in./A4 SEF only Z-half-fold: Tabloid – 11 x 17 in./A3 only		
<b>Weights</b>	16 lb. to 24 lb. bond/64 to 90 gsm		
<b>Output Trays</b>	Envelope Tray: C-fold, Z-fold, and Tri-fold Stacker Tray or Top Tray: Z-half-fold		
<b>Convenience Stapler (Optional - Includes Work Surface<sup>5</sup>)</b>			
<b>Capacity<sup>4</sup></b>	50-sheet stapling 5,000 staples Requires separate power outlet		
Copy	AltaLink® B8245	AltaLink® B8255	AltaLink® B8270
<b>First-Copy-Out Time (from platen/warmed up)</b>	As fast as 4.1 seconds	As fast as 3.6 seconds	As fast as 3.0 seconds
<b>Sides (input:output)</b>	1-1, 1-2, 2-2, 2-1		
<b>Quantity</b>	1 to 9,999		
<b>Resolution (max)</b>	Up to 600 x 600 dpi		
<b>Reduction/Enlargement</b>	Variable zoom from 25% to 400% in 1% increments		
<b>Concurrency</b>	Program-ahead to allow the job to be queued while the initial job is processed (Copy, Print, Fax, and Scan)		
<b>Copy Features</b>	Annotation and Bates™ stamping Authentication for Services Auto Paper Select Auto Reduction & Enlargement (To fit selected paper size) Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (enables page-level programming and also lets you proof each section or delete the last section as the job is built) Collation Covers (front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Imaging Security (only Detect Mark feature is supported on monochrome MFPs) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling Touchless Workflow Accelerators Transparencies		

# Xerox® AltaLink® B8245/B8255/B8270 Multifunction Printer

Print	AltaLink® B8245	AltaLink® B8255	AltaLink® B8270
<b>First-Print-Out Time (as fast as)</b>	3.7 seconds	3.2 seconds	3.0 seconds
<b>Resolution (up to)</b>	1200 x 2400 dpi		
<b>Print Features</b>	<p>Application Defaults            Banner Sheet Enable/Disable            Booklet Layout            Cover Selection            Delay Print (specific time) User Permissions            Finishing            Fit to New Paper Size            Hold All Jobs            Image Options (Toner Saver, Resolution (Standard, Enhanced, High))            Job Identification (Print ID or Banner, Print ID in margins on the first page only or all pages)            LAN Fax (requires optional Fax Kit)            Long Sheet/Banner            Layout/Watermark            N-up (up to 16 pages per sheet)            Paper Selection by Attribute Sample Set            Print From Cloud Repositories (Dropbox, OneDrive, and Google Drive)            Saved Job            Secure Print with Timed Deletion            Special Pages (exception page programming: covers, inserts, exception pages)            Store and Recall Driver Settings            Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)            Two-sided Printing (as default)</p>		
<b>Print from USB</b>	<p>Allows walk-up printing from Type A USB port on the front panel            Supports direct printing from a computer via Type B USB port            Supported file formats: PDF, JPEG, TIFF, PS, PCL            Color jobs can be printed as black-and-white</p>		
<b>Operating Systems</b>	<p>Windows 10 (32 and 64 bit)            Windows 11 (64 bit)            MacOS 12.x, 13.x, 14.x            Red Hat Linux 7.x, 8.x, 9.x            Ubuntu Linux 18.04, 20.04, 22.04, 23.04, 24.04            OpenSUSE Linux Server 15.5</p> <p>MS Windows 2012 Server (64 bit)            MS Windows 2016 Server (64 bit)            MS Windows 2019 Server (64 bit)            MS Windows 2022 Server (64 bit)            Red Hat Linux Server 7.x, 8.x            SuSe Linux Server 12.2-12.4, 15.x</p> <p><b>Note:</b> For latest supported versions please visit our Drivers &amp; Downloads page and specify your device at <a href="https://support.xerox.com">support.xerox.com</a></p>		
<b>Network Protocols</b>	<p>TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD            Microsoft Windows Networking over IP            Bonjour®/AirPrint™            IPv6            Most protocols not in use can be disabled</p>		
<b>Font Capability</b>	PCL: 93 scalable fonts, line printer, and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts		
<b>Xerox® Global Print Driver®</b>	A truly universal print driver that lets IT administrators install, upgrade, and manage non-Xerox and Xerox® Devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management. Support for Microsoft Universal Print with Print Support Application (PSA)		
<b>Xerox® Pull Print Driver</b>	Makes it easy for IT managers to qualify, deploy, and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos®, and others		
<b>Unified Address Book for Fax, Email, and Scan to...</b>			
<b>Features</b>	<p>Services supported: Fax, Email, Scan to            Maximum contacts: 5,000            Contacts: Supports 1 or more destinations            Favorites for quick access of all services supported</p>		

# Xerox® AltaLink® B8245/B8255/B8270 Multifunction Printer

Scan	AltaLink® B8245	AltaLink® B8255	AltaLink® B8270
<b>Concurrency</b>	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)		
<b>Input Speed (up to)</b>	82 ppm black-and-white and color (simplex) 161 ipm black-and-white and color (duplex)		135 ppm black-and-white and color (simplex) 270 ipm black-and-white and color (duplex)
<b>Resolution</b>	150 x 150 dpi to 600 x 600 dpi		
<b>Bit Depth</b>	1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)		
<b>Maximum Scan Area</b>	11 x 17 in./A3		
<b>Scan Template Management</b>	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers' confirmation sheet options		
<b>Network Protocols</b>	sFTP, FTP, SMB, HTTP, HTTPS		
<b>File Compression</b>	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression – single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for black-and-white and within MRC)) Linearized PDF/PDF/A		
<b>Document Management Fields (Metadata)</b>	Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> <li>• 1 to 6 user-programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of a field name, default value, and other configurations</li> <li>• Customized fields viewed on user interface for variable data input</li> </ul> Scan To with Metadata <ul style="list-style-type: none"> <li>• Embedded in scan files using XMP formats</li> <li>• Works with expert systems workflow</li> </ul>		
<b>Scan Features</b>	Auto Background and Shadow Suppression Bound Originals Compression Quality/File Size Control Edge Erase Imaging Security (only Detect Mark feature is supported on monochrome MFPs) Mixed Size Originals Original Type (Photo and Text, Photo, Text, Map, Newspaper/Magazine) Reduction/Enlargement Scan Build Job Scan to Home Scan to Mailbox Scan to Network (using FTP/sFTP/SMB/HTTP/HTTPS) Scan to Network Folder (using FTP/sFTP/SMB/HTTP/HTTPS) Single Touch Scan buttons (up to 10) Size for Size (for mixed size originals) TWAIN Support/WIA 2.0 Support		
<b>Scan to Email (Standard)</b>			
<b>Scan Features</b>	<ul style="list-style-type: none"> <li>• Auto send to self</li> <li>• Email signatures (6 lines each of 128 character max), email message body (user-configurable), email Embedded Web Server confirmation sheet options</li> <li>• Email signing (requires Smart Card option)</li> <li>• Scan to Email S/MIME Encryption</li> <li>• Touchless Workflow Accelerators</li> </ul>		
<b>Directory Access</b>	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino), Device Address Book		
<b>Scan To</b>			
<b>Standard Features</b>	Scan Preview Scan to Email Scan to Network (using sFTP) Scan to Network Folder (using sFTP) Scan to PC via USB port Scan to PC/Server Client (SMB or FTP) Scan to Print Scan to USB Touchless Workflow Accelerators		
<b>Optional Features</b>	Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive)		
<b>Scanning Solutions and Apps</b>			
<b>Scanning Software</b>	Autostore v7 eCopy ShareScan v5.2 eCopy ScanStation v5.2		
<b>Scanning Apps and Xerox App Gallery</b>	Scan to: Dropbox, Google Drive, Microsoft OneDrive, Microsoft Office 365™, Box®, Xerox® Workplace Mobile App (iOS/Android) See the full list of apps available in the Xerox App Gallery: <a href="http://xerox.com/AppGallery">xerox.com/AppGallery</a>		

# Xerox® AltaLink® B8245/B8255/B8270 Multifunction Printer

Security	AltaLink® B8245	AltaLink® B8255	AltaLink® B8270
<b>Features</b>	<ul style="list-style-type: none"> <li>• Audit Log</li> <li>• Cisco® Identity Services Engine (ISE) compatible</li> <li>• Configuration Watchdog (Monitor and remediate 75 security settings in the following areas):               <ul style="list-style-type: none"> <li>- 802.1x</li> <li>- Admin Password Reset</li> <li>- Audit Log</li> <li>- Automatic Software Upgrade</li> <li>- Email Alerts</li> <li>- FIPS 140-3</li> <li>- Hold All Jobs</li> <li>- Installation Policies</li> <li>- Job Data Removal</li> <li>- Trellix Embedded Control*</li> <li>- PII - Login Name</li> <li>- PostScript Passwords</li> <li>- Remote Services Enablement</li> <li>- Remote Start (Mopria® or AirPrint™)</li> <li>- Remote Start (TWAIN)</li> <li>- Reprint Saved Jobs</li> <li>- Scan to Mailbox (Internal storage)</li> <li>- Secure Passcode Length</li> <li>- Secure Print Device Policies</li> <li>- SIEM</li> <li>- SNMP</li> <li>- System Timeout</li> <li>- USB (Print from USB)</li> <li>- USB (Scan to USB)</li> <li>- USB Port Management</li> <li>- User Data Encryption</li> </ul> </li> <li>• Erase Customer Data securely removes all data from SSD</li> <li>• Expanded Authentication               <ul style="list-style-type: none"> <li>- Encrypted and authentication to SMTP server for Scan to Email</li> <li>- Encrypted/Password-protected PDF (when using Email and Network Scan Templates only)</li> <li>- FIPS 140-3, 256 bit Hard Disk Encryption, TLS, IPPS, HTTPS, sFTP, SNMPv3</li> <li>- Local Authentication (internal database)</li> <li>- Network authentication to access device and/or device services via Kerberos (UNIX/Windows Server 2008), SMB (Windows Server 2008, Windows server 2012), NDS, LDAP authentication</li> <li>- On-demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk</li> <li>- Secure Data</li> <li>- Smart Card authentication – 144k CAC/PIV Card Support (2048 bit certificate key)/.NET</li> </ul> </li> <li>• Expanded Authorization               <ul style="list-style-type: none"> <li>- Authorization per user per service</li> <li>- SA access based on network credentials</li> <li>- Secure Network Access</li> <li>- User Permissions required to access Print and Print Features (e.g., time restrictions) reflects in the print driver</li> </ul> </li> <li>• Full System Common Criteria certification by NIAP under HD Protection Profile for Hardcopy Devices v1.0 (HCD-PP v1.0) will be made available in a future firmware release</li> <li>• Hide Print Job Names</li> <li>• Imaging Security (only Detect Mark feature is supported on monochrome MFPs)</li> <li>• IP Filter, IPsec, IPv6, TLS V1.1, V1.2, V1.3, SNMP V1, V2, V3, HTTPS, 802.1X, sFTP</li> <li>• Job Data Removal on SSD</li> <li>• Trellix Embedded Control* (Allowlisting), Trellix Integrity Control* (optional)</li> <li>• Port disablement including USB ports</li> <li>• Secure Print (up to 10 digit PIN or Network Authentication)</li> <li>• Security Dashboard</li> <li>• Security Information and Event Management (SIEM) support for Trellix Enterprise Security Manager*, LogRhythm, and Splunk</li> <li>• Security Templates</li> <li>• Trusted Platform Module 2.0</li> <li>• WPA2™ and WPA3™ are supported by the Dual Band Wi-Fi® and Bluetooth® Kit</li> </ul>		
<b>Xerox® Integrated RFID Card Reader (Optional kit)</b>	Integrated support for most industry security cards providing additional security; with embedded multifunction printer card readers in the multifunction printer panel		

# Xerox® AltaLink® B8245/B8255/B8270 Multifunction Printer

Fax	AltaLink® B8245	AltaLink® B8255	AltaLink® B8270
<b>Network Server Fax Features</b>			
<b>Compatibility</b>	ITU (CCITT) group 3; Various Xerox® Business Innovation Partner Solutions		
<b>Maximum Scan Area</b>	11 x 17 in./A3		
<b>Fax Send Features</b>	One- or Two-sided Scanning (up to 11 x 17 in./A3) Add to Send List (200 numbers maximum) Build Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text)		
<b>Fax Print Features</b>	One- or Two-sided Printing, Staple, Secure Print		
<b>Transmission Resolution</b>	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi		
<b>Walk-up Fax Features (Optional; Customer-installable – 1 and 2 lines)</b>			
<b>Compatibility</b>	ITU (CCITT) Group 3		
<b>Speed/Modems</b>	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time		
<b>Compression/Speed</b>	MH/G3, MR/G3, MMR/SG3, JBIG/SG3		
<b>Resolution</b>	<b>Walk-up Send:</b> Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi <b>Receive:</b> Accepts all sizes		
<b>Fax Send Features</b>	Auto Fax Transmission Reduction Automatic Cover Sheets Automatic Memory Resend Batch Send (up to memory capacity) Delay Start, Build Job, Favorites Device Address Book (up to 5,000 contacts) LAN Fax (fax from print driver) Page-by-page Job Status at the Machine PSTN Fax		
<b>Fax Receive Features</b>	Auto Answer Delay One- or Two-sided Printing Output Tray Selection Receive Print Mode – Manual (size, margin, stock, header)/Auto Receive Timestamp Secure Receive Stapled or Unstapled Up to 200 Password Protected Mailboxes		
<b>Fax Forward</b>	Forward to Email or SMB Location Fax Forward on Receive Only		
<b>Fax Reports</b>	Activity, Transmission Confirmation, Pending Fax, Options Report, Mailbox Report, Broadcast Report		
<b>Directory Access</b>	Utilizes the Unified Address Book Group fax available		
<b>Auto Redial</b>	Up to 14 attempts (per country requirements) 1 to 25-minute intervals		
<b>Auto Resend</b>	Up to 5 attempts		

# Xerox® AltaLink® B8245/B8255/B8270 Multifunction Printer

Device Management	
<b>Administrative Protocols</b>	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS
<b>Management Support</b>	SNMP Version 1, SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System- Power MIB, Fleet Orchestrator, Configuration Watchdog, Security Dashboard, <b>Xerox® Easy Assist App</b>
<b>Xerox® CentreWare® Web</b>	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX, or any other operating system: <ul style="list-style-type: none"> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Remote configuration of SNMP v3</li> <li>• Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> <li>• Requires Windows 7 and Internet Explorer 6.0 and higher</li> <li>• Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote installation</li> </ul>
<b>Xerox® Device Manager</b>	<b>Optional:</b> Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: <ul style="list-style-type: none"> <li>• Device monitoring and troubleshooting</li> <li>• Remote configuration of SNMP v3</li> <li>• Extensive reporting and discovery of new devices</li> <li>• Usage collection, chargeback, and billing capabilities</li> <li>• Auto-detect Xerox® Device Manager server and download configurations files for touchless remote installation</li> </ul>
<b>Xerox® Workplace Cloud</b>	<b>Optional:</b> Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server
<b>Accessibility</b>	<ul style="list-style-type: none"> <li>• Embedded Web Server conforms to Web Content Guidelines (WCAG)</li> <li>• Touchscreen tilt and user interface inversion</li> <li>• Touchscreen zoom and pan</li> <li>• Touchscreen navigation with keyboard</li> <li>• Speech output</li> </ul>
<b>Fleet Orchestrator</b>	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files, and 1-Touch App files. Auto-assembly feature allows a new AltaLink to automatically set itself on the network and configure
<b>Novell NDPS/NEPS</b>	Server gateway application: centralized management tool
<b>Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)</b>	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. For more information, visit <a href="http://office.xerox.com/Software-Solutions">office.xerox.com/Software-Solutions</a>
<b>Xerox® Device Types for SAP Environment</b>	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download <a href="http://office.xerox.com/Software-Solutions">office.xerox.com/Software-Solutions</a>
Xerox® Embedded Web Server – Integrated Device Web Pages Provided by the Device	
<b>Device Status</b>	Web server embedded in Network Controller: <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Alerts</li> <li>• Remote Control Panel</li> </ul>
<b>Job Submission</b>	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Templates
<b>Browsers</b>	Microsoft Edge version 88+ Microsoft Chromium Edge version 79+ Mozilla Firefox 91.9.0, 100.0 Safari 13.1.2, 14.1.2, 15.4 Opera 2020, 2021 Google Chrome version 80.0.x+
<b>Support</b>	Install print/scan drivers and online support available via <a href="http://support.xerox.com">support.xerox.com</a>
<b>Languages Supported</b>	US English, Danish, German, Spanish, French, Croatian, Italian, Dutch, Norwegian, Brazilian Portuguese, Finnish, Swedish, Russian, Ukrainian, Arabic
Remote Services	
<b>Xerox® Automatic Meter Readings (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time
<b>Xerox® Automatic Supplies Replenishment (ASR)</b>	Automatically orders supplies for output devices from Xerox based on actual usage, eliminating the need to manually manage supplies inventory
Accounting	
Xerox® Standard Accounting Feature (Standard)	
<b>Tracking</b>	Copy, Print, Fax, Scan, and Email usage
<b>Accounting</b>	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)
<b>Features</b>	<ul style="list-style-type: none"> <li>• Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>• Administrator can import or export User Accounts, Group Accounts, General Accounts, and User Limits via an industry-standard CSV file</li> </ul>

# Xerox® AltaLink® B8245/B8255/B8270 Multifunction Printer

Accounting Options – Network Accounting (Allows central server to manage all accounting)		
	<ul style="list-style-type: none"> <li>Enhanced network accounting with up-to-the-minute data on how the system is being used</li> <li>Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan, and server fax</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details, visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>Device requests account authentication from third-party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at the control panel and pass to third-party Networking Account</li> <li>Interface with third-party accounting terminal for accounting user interface</li> </ul>	
Supplies	Description	Yield
<b>Toner Cartridge<sup>6</sup></b>	Black	52,000 pages
<b>Transfer Belt Cleaner</b>	1 Assembly	160,000 pages
<b>Second Bias Transfer Roll</b>	1 Assembly	200,000 pages
<b>Staple Cartridges</b>	For BR Finisher, Integrated Office Finisher, Office Finisher, and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge
	For BR Booklet Maker (1 cartridge per carton)	5,000 each cartridge
	For Office Finisher Booklet Maker (8 cartridges per carton)	2,000 each cartridge
<b>Staple Refills</b>	For Integrated Office Finisher, Office Finisher, BR Finisher, and Convenience Stapler (3 refills per carton)	5,000 each refill
Xerox® Smart Kit <sup>9</sup>		
<b>Drum Cartridge<sup>7</sup></b>	1 Cartridge	200,000 pages
<b>Waste Toner Container w/o Suction Filter<sup>8</sup></b>	1 Cartridge (AltaLink® B8245/B8255)	121,000 pages
<b>Waste Toner Container with Suction Filter<sup>8</sup></b>	1 Cartridge (AltaLink® B8270)	121,000 pages

<sup>1</sup> Declared in accordance with ISO/IEC 24734.

<sup>2</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>3</sup> Not available in all geographies.

<sup>4</sup> Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

<sup>5</sup> Sold separately in some geographies.

<sup>6</sup> Average standard pages. Declared in accordance with ISO/IEC 19752. Toner yield can vary due to many factors, including but not limited to image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes, and image quality set-points.

<sup>7</sup> Average drum yield is based on a run length of 5 pages of 8.5 x 11 in./A4 LEF pages, with a split of 35 % color/65 % black-and-white pages.

<sup>8</sup> Waste Toner Container yield will vary depending on the image type, area coverage %, and job run length.

<sup>9</sup> Trellix DXL formerly known as McAfee® DXL, Trellix Embedded Control Allowlisting formerly known as McAfee® Embedded Control Allowlisting, Trellix ePolicy Orchestrator® formerly known as McAfee® ePolicy Orchestrator®, Trellix ESM formerly known as McAfee® ESM, Trellix Integrity Control formerly known as McAfee® Integrity Control, Trellix Enterprise Security Manager formerly known as McAfee® Enterprise Security Manager. Trellix brand name will be reflected in future firmware releases.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. For more information, visit [www.xerox.com/About-Xerox/Recycling](http://www.xerox.com/About-Xerox/Recycling).

For more information, visit us at [www.xerox.com/Office](http://www.xerox.com/Office).